

Tile Adhesive :Grade – Cera Fix

PRODUCT DESCRIPTION

Our premium adhesive is a high-performance tile fixing solution, crafted from a polymer-modified blend combined with grey cement. This advanced formula ensures exceptional bonding strength, making it ideal for fixing Ceramic body tiles. Whether you're working on horizontal or vertical surfaces in interior spaces.

UNIT: Bag

SIZE : 20 Kg

COLOUR : Grey

COVERAGE :

- Approx. 30 sqft per bag at 3 mm thickness
- Approx. 25 sqft per bag at 5 mm thickness
- Approx. 20 sqft per bag at 8 mm thickness

Note : Coverage is depend on surface level of floor and wall it may be more and less.



RECOMMENDED APPLICATION

Ceramic Tiles for Walls:

- Suitable for fixing tiles up to **300x300 mm**.deal for high-strength, secure installations on vertical surfaces. Designed for fixing tiles up to **600x600 mm**.Provides durable and stable bonding for large floor tiles.

Sl. No.	Test Conducted	Average Results	Requirements As per IS: 15477-2019				
			Type 1	Type 2	Type 3	Type 4	Type 5
1	Tensile Adhesion (N/mm ²)						
	a) Dry Condition	0.86	Min. 0.5	Min. 1.0	Min. 1.5	Min. 1.5	Min. 2.0
	b) Wet Condition	---	-	Min. 1.0	Min. 1.0	Min. 1.0	-
2	Shear Adhesion (N/mm ²)						
	a) Dry Condition	1.19	Min. 1.0	Min. 1.25	Min. 1.5	Min. 1.5	Min. 6.0
	b) Wet Condition	---	-	Min. 1.0	Min. 1.0	Min. 1.0	Min. 3.0
	c) Heat Ageing	---	-	Min. 1.0	Min. 1.0	Min. 1.0	-
3	Open Time (Minutes)	15	Not Specified				
4	Adjustability (Minutes)	20	Not Specified				
5	Slip (mm)	0.12	Shall not be more than 0.5 mm				

As furnished by the customer.

Remark: - Cera Fix Grey Tile Adhesive conforms to the requirements of Type-1 T Tile Adhesive as per IS 15477-2019.

COMPANY ADDRESS -Reg.off:-C/ORangoli general store,near meghani school,shaktipark society,avani Chowkadi, Morbi-363641 (Gujarat) INDIA Factory;-Sr.No.509/1/2,nearbarnala,Tankara-Morbiroad,Tankara363650 (Dist.Morbi) (Gujarat)INDIA

CONTACTUS:email–milanoplyllp@gmail.com

Mo:+91 9822009779(Raju Patel)

Mo :+91 9922540020 (Ankur Patel)

TILE ADHESIVE : GRADE – VITRO FIX

PRODUCT DESCRIPTION

Our premium adhesive is a high-performance tile fixing solution, crafted from a polymer-modified blend combined with grey cement. This advanced formula ensures exceptional bonding strength, making it ideal for fixing vitrified and porcelain body tiles. Whether you're working on horizontal or vertical surfaces in interior spaces.

UNIT: Bag

SIZE : 20 Kg

COLOUR : Grey

COVERAGE :

Approx. 30 sqft per bag at 3 mm thickness
Approx. 25 sqft per bag at 5 mm thickness
Approx. 20 sqft per bag at 8 mm thickness

Note : Coverage is depend on surface level of floor and wall it may be more and less.



RECOMMENDED APPLICATION

1. Vitrified Body Tiles for Walls:

- Suitable for fixing tiles up to **600x600, 600x1200**
- Ideal for high-strength, secure installations on vertical surfaces.

2. Vitrified Body Tiles for Floors:

- Designed for fixing tiles up to **600x1200**
- Provides durable and stable bonding for large floor tiles.

3. Tile-on-Tile Installations:

- Perfect for fixing vitrified body tiles up to **600x1200**
- Ensures excellent adhesion and long-lasting results when applying tiles over existing tile

PHYSICAL PROPERTIES:

Sl. No.	Test Conducted	Average Results	Requirements As per IS: 15477-2019				
			Type 1	Type 2	Type 3	Type 4	Type 5
1	Tensile Adhesion (N/mm ²)						
	a) Dry Condition	1.22	Min. 0.5	Min. 1.0	Min. 1.5	Min. 1.5	Min. 2.0
	b) Wet Condition	1.14	-	Min. 1.0	Min. 1.0	Min. 1.0	-
2	Shear Adhesion (N/mm ²)						
	a) Dry Condition	1.39	Min. 1.0	Min. 1.25	Min. 1.5	Min. 1.5	Min. 6.0
	b) Wet Condition	1.19	-	Min. 1.0	Min. 1.0	Min. 1.0	Min. 3.0
	c) Heat Ageing	1.47	-	Min. 1.0	Min. 1.0	Min. 1.0	-
3	Open Time (Minutes)	25	Not Specified				
4	Adjustability (Minutes)	30	Not Specified				
5	Slip (mm)	0.21	Shall not be more than 0.5 mm				

As furnished by the customer.

Remark: - Vitrofix Grey Tile Adhesive conforms to the requirements of Type-2 T Tile Adhesive as per IS 15477-2019.

COMPANY ADDRESS -Reg.off:-C/ORangoli general store,near meghani school,shaktipark society,avani Chowkadi, Morbi-363641 (Gujarat) INDIA Factory;-Sr.No.509/1/2,nearbarnala,Tankara-Morbiroad,Tankara363650 (Dist.Morbi) (Gujarat)INDIA

CONTACTUS:email–milanoplyllp@gmail.com

Mo:+91 9822009779(Raju Patel)

Mo :+91 9922540020 (Ankur Patel)

Tile Adhesive :Grade – Stone Fix

PRODUCT DESCRIPTION

Our premium adhesive is a high-performance tile fixing solution, crafted from a polymer-modified blend combined with grey cement. This advanced formula ensures exceptional bonding strength, making it ideal for fixing vitrified and porcelain body tiles. Whether you're working on horizontal or vertical surfaces in interior spaces.

UNIT: Bag

SIZE : 20 Kg

COLOUR : Grey

COVERAGE :

Approx. 30 sqft per bag at 3 mm thickness

Approx. 25 sqft per bag at 5 mm thickness

Approx. 20 sqft per bag at 8 mm thickness

Note : Coverage is depend on surface level of floor and wall it may be more and less.



RECOMMENDED APPLICATION

Vitrified Body Tiles for Walls:

- Suitable for fixing tiles up to **800x1600 mm**.
- Ideal for high-strength, secure installations on vertical surfaces.

Vitrified Body Tiles for Floors:

- Designed for fixing tiles up to **1200x2400 mm**.
- Provides durable and stable bonding for large floor tiles.

Tile-on-Tile Installations:

- Perfect for fixing vitrified body tiles up to **1200x2400 mm**.
- Ensures excellent adhesion and long-lasting results when applying tiles over existing tile

PHYSICAL PROPERTIES:

Sl. No.	Test Conducted	Average Results	Requirements As per IS: 15477-2019				
			Type 1	Type 2	Type 3	Type 4	Type 5
1	Tensile Adhesion (N/mm ²)						
	a) Dry Condition	1.52	Min. 0.5	Min. 1.0	Min. 1.5	Min. 1.5	Min. 2.0
	b) Wet Condition	1.11	-	Min. 1.0	Min. 1.0	Min. 1.0	-
2	Shear Adhesion (N/mm ²)						
	a) Dry Condition	1.54	Min. 1.0	Min. 1.25	Min. 1.5	Min. 1.5	Min. 6.0
	b) Wet Condition	1.21	-	Min. 1.0	Min. 1.0	Min. 1.0	Min. 3.0
	c) Heat Ageing	1.33	-	Min. 1.0	Min. 1.0	Min. 1.0	-
3	Open Time (Minutes)	30	Not Specified				
4	Adjustability (Minutes)	35	Not Specified				
5	Slip (mm)	0.26	Shall not be more than 0.5 mm				

As furnished by the customer.

Remark: - Stonefix Grey Tile Adhesive conforms to the requirements of Type-3 T Tile Adhesive as per IS 15477-2019.

COMPANY ADDRESS -Reg.off:-C/ORangoli general store,near meghani school,shaktipark society,avani Chowkadi, Morbi-363641 (Gujarat) INDIA Factory;-Sr.No.509/1/2,nearbarnala,Tankara-Morbiroad,Tankara363650 (Dist.Morbi) (Gujarat)INDIA

CONTACTUS:email–milanoplylp@gmail.com

Mo:+91 9822009779(Raju Patel)

Mo :+91 9922540020 (Ankur Patel)

Tile Adhesive :Grade – Stone Fix White

PRODUCT DESCRIPTION

Our premium adhesive is a high-performance tile fixing solution, crafted from a polymer-modified blend combined with grey cement. This advanced formula ensures exceptional bonding strength, making it ideal for fixing vitrified and porcelain body tiles. Whether you're working on horizontal or vertical surfaces in interior spaces.

COVERAGE

Approx. 30 sqft per bag at 3 mm thickness.

Approx. 25 sqft per bag at 5 mm thickness

Approx. 20 sqft per bag at 8 mm thickness

Note : Coverage is depend on surface level of floor and wall it may be more and less.

RECOMMENDED APPLICATION

UNIT: Bag

SIZE : 20 Kg

COLOUR : Grey

RECOMMENDED APPLICATION

Vitrified Body Tiles for Walls:

- Suitable for fixing tiles up to **800x1600 mm**.
- Ideal for high-strength, secure installations on vertical surfaces.

Vitrified Body Tiles for Floors:

- Designed for fixing tiles up to **1200x2400 mm**.
- Provides durable and stable bonding for large floor tiles.

Tile-on-Tile Installations:

- Perfect for fixing vitrified body tiles up to **1200x2400 mm**.
- Ensures excellent adhesion and long-lasting results when applying tiles over existing tile



PHYSICAL PROPERTIES:

Sl. No.	Test Conducted	Average Results	Requirements As per IS: 15477-2019				
			Type 1	Type 2	Type 3	Type 4	Type 5
1	Tensile Adhesion (N/mm ²)						
	a) Dry Condition	1.55	Min. 0.5	Min. 1.0	Min. 1.5	Min. 1.5	Min. 2.0
	b) Wet Condition	1.12	-	Min. 1.0	Min. 1.0	Min. 1.0	-
2	Shear Adhesion (N/mm ²)						
	a) Dry Condition	1.54	Min. 1.0	Min. 1.25	Min. 1.5	Min. 1.5	Min. 6.0
	b) Wet Condition	1.19	-	Min. 1.0	Min. 1.0	Min. 1.0	Min. 3.0
	c) Heat Ageing	1.32	-	Min. 1.0	Min. 1.0	Min. 1.0	-
3	Open Time (Minutes)	30	Not Specified				
4	Adjustability (Minutes)	35	Not Specified				
5	Slip (mm)	0.27	Shall not be more than 0.5 mm				

As furnished by the customer.

Remark: - Stonefix White Tile Adhesive conforms to the requirements of Type-3 T Tile Adhesive as per IS 15477-2019.

COMPANY ADDRESS -Reg.off:-C/ORangoli general store,near meghani school,shaktipark society,avani Chowkadi, Morbi-363641 (Gujarat) INDIA Factory;-Sr.No.509/1/2,nearbarnala,Tankara-Morbiroad,Tankara363650 (Dist.Morbi) (Gujarat)INDIA

CONTACTUS:email-milanoplylp@gmail.com

Mo:+91 9822009779(Raju Patel)

Mo :+91 9922540020 (Ankur Patel)

TILE ADHESIVE : GRADE – MARBO FIX

PRODUCT DESCRIPTION

Made from a tile fixing chemical combination of polymers modified with white cement, this adhesive is used for fixing glass mosaic tiles, Italian marble, and large-format floor and wall tiles. In addition to the Indian Standards, it's also compliant with the EN 12004: C2 TE SI quality standard. Suitable for vitrified body, full-body, natural stone, marble(Italian marble) glass, mosaic, granite, internal and external for wall cladding. (Available in two variants GREY/ WHITE Up to 1200x2400

UNIT: Bag

SIZE : 20 Kg

COLOUR : White/Grey

COVERAGE :

Approx. 30 sqft per bag at 3 mm thickness
Approx. 25 sqft per bag at 5 mm thickness
Approx. 20 sqft per bag at 8 mm thickness

Note : Coverage is depend on surface level of floor and wall it may be more and less.

RECOMMENDED APPLICATION

1.Vitrified Body Tiles for Walls:

- Suitable for fixing tiles up to **2400x2400**
- Ideal for high-strength, secure installations on vertical surfaces.

2.Vitrified Body Tiles for Floors:

- Designed for fixing tiles up to **3200x3200**
- Provides durable and stable bonding for large floor tiles.

3.Tile-on-Tile Installations 3200x3200

- **Ensures excellent adhesion and long-lasting results when applying tiles over existing tile**



PHYSICAL PROPERTIES:

Sl. No.	Test Conducted	Average Results	Requirements As per IS: 15477-2019				
			Type 1	Type 2	Type 3	Type 4	Type 5
1	Tensile Adhesion (N/mm ²)						
	a) Dry Condition	1.63	Min. 0.5	Min. 1.0	Min. 1.5	Min. 1.5	Min. 2.0
	b) Wet Condition	1.04	-	Min. 1.0	Min. 1.0	Min. 1.0	-
2	Shear Adhesion (N/mm ²)						
	a) Dry Condition	1.52	Min. 1.0	Min. 1.25	Min. 1.5	Min. 1.5	Min. 6.0
	b) Wet Condition	1.16	-	Min. 1.0	Min. 1.0	Min. 1.0	Min. 3.0
	c) Heat Ageing	1.32	-	Min. 1.0	Min. 1.0	Min. 1.0	-
3	Open Time (Minutes)	35	Not Specified				
4	Adjustability (Minutes)	40	Not Specified				
5	Slip (mm)	0.18	Shall not be more than 0.5 mm				
6	Deformability (mm)	2.69	Deformable adhesive, S1 ≥2.5 mm, < 5.0 mm Highly deformable adhesive, S2 ≥ 5.0 mm				

As furnished by the customer.

Remark: - Marbofix White Tile Adhesive conforms to the requirements of Type-4 T S1 Tile Adhesive as per IS 15477-2019.

COMPANY ADDRESS -Reg.off.-C/ORangoli general store,near meghani school,shaktipark society,avani Chowkadi, Morbi-363641 (Gujarat) INDIA Factory;-Sr.No.509/1/2,nearbarnala,Tankara-Morbiroad,Tankara363650 (Dist.Morbi) (Gujarat)INDIA

CONTACTUS:email–milanopolyllp@gmail.com

Mo:+91 9822009779(Raju Patel)

Mo :+91 9922540020 (Ankur Patel)