



FOTON



AUMAN D
4x2 270HP

AUMAN D 4x2-270HP TRACTOR HEAD

Main Parameter		
Complete vehicle dimension parameters	Wheelbase (mm)	3700
	Chassis Dimensions(LxWxH) (mm)	6020x2532x2900
Complete vehicle mass parameter	Chassis kerb mass (kg)	5800
	GCW (Design) (kg)	35000
Complete vehicle performance parameter	Maximum speed (km/h)	85
	Maximum climbing capacity, % (full load)	> 23
Product configuration		
Cab	Body type	AUMAN D 2200 Plat roof
	Carrying number	single sleeper
Engine	Model	ISD270 50
	Emission standard	Euro V
	Displacement (mL)	6690
	Rated power (ps/rpm)	270/2500
	Maximum output torque(Nm/rpm)	970/1000-1300
Gearbox	Model	FAST 8JS118TB-B
	Speed control mode	MT
Front axle	Rated load	5T
	Brake type	Drum
Rear axle	Model/Axle housing type	Single reduction/ Welding
	Rated load/speed ratio	11T/5.286
	Brake type	Drum
Suspension	Front suspension/spring number	Multi leaf spring + Hydraulic shock absorber + Stabilizer bar / 8
	Rear suspension/spring number	Multi leaf spring with balance shaft / 9+6
Tire	Specification	11.00R20
	Quantity	6+1
Brake	Service brake	Double return air pressure drum brake
	Parking brake	Spring energy storage breaks the air brake
	Auxiliary brake	Engine exhaust brake
	ABS	ABS
Fuel tank	Specification and material	350L
Other Configurations	Cab suspension	Full floating airbag
	Cab lifting	Electric control
	Seat type	Airbag seat
	AC	Standard

Note: FOTON reserves the right to make changes in the specifications and other information contained in this document without prior notification

GERMAN QUALITY



MONEY MASTER

Contact:

PT. Foton Pemasaran & Penjualan Indonesia

+62 81340610050

huoxianqiang2@foton.com.cn

www.foton-global.com

