For Home and Business

	Back-UPS CS 350	Back-UPS CS 500	Back-UPS 650
PART NUMBER	**BK350**	**BK500**	**BK650MC**
INPUT			
Capacity	350VA (210W)	500VA (300W)	650VA (400W)
Nominal Input	120 Vac single-phase, 50 or 60 Hz ± 5%		
OUTPUT			
Voltage (on battery)	Stepped approximation to sine wave output at 115 Vac ± 8% (auto sensing)		
SURGE PROTECTION			
Dataline protection	Single phone/fax/modem/DSL		
PHYSICAL			
Total number of receptacles	3 battery + surge, 3 surge only. 2 transformer block-spaced outlets		
Maximum Dimensions (H x W x L)	6.5″ x 3.6″ x 11.2″ (16.5 x 9.1 x 28.3 cm)		6.6″ x 4.7″ x 14.2″ (16.8 x 11.9 x 36.1 cm)
Net weight	13.1 lbs (5.9 kg)	15.3 lbs (7.0 kg)	23.0 lbs (10.4 kg)
USER REPLACEABLE BATTERIES			
Type	User-replaceable, Hot swappable, sealed, maintenance-free lead acid		Maintenance-free lead acid
Typical recharge time	6-8 hours		5-10 hours
DIAGNOSTICS AND MANAGEMENT			
Visible indicators	On-line, on battery, UPS overload, replace battery		On-line
Audible alarms	On battery, low battery, UPS overload, replace battery		
Management	14 Day automatic self-test		Manual self-test, adjustable battery transfer points and alarm settings
USB Connector	Data saving and unattended shutdown for Windows XP, Windows Me, Windows 98 and Mac OS 9 (9.0.4 or higher) included. Configuration software for Windows 2000 also included.		–
Serial Connector	Free optional in-box offer (Data saving and unattended shutdown for Windows XP Windows Me, Windows 98, Windows 95, Windows 2000 and Windows NT included.)		Data saving and unattended shutdown for Windows XP, Windows Me, Windows 98, Windows 95, Windows 2000 and Windows NT included.
CONFORMANCE			
Agency Approvals	UL 1778, C-UL, FCC Part 68		FCC Part 68, UL 1778, CSA
Warranty	2 year comprehensive, including battery		
Equipment Protection Policy	$100,000 lifetime protection, including lightning (see policy for details)		
TYPICAL RUNTIME IN MINUTES (Runtimes may vary depending on your equipment. For the most recent sizing information go to *sizing.apcc.com*)			
	Back-UPS CS 350	**Back-UPS CS 500**	**Back-UPS 650**
Typical runtimes	16	22	44