



SIYA RAM ENTERPRISES

FIRE SOLUTIONS SINCE 2021

YOUR PARTNER IN FIRE PROTECTION AND OVERALL SAFETY



ISO 9001:2015
CERTIFIED COMPANY

FIRE EXTINGUISHERS

• ABC • DCP • CO2 • Clean Agent • Foam • Water • Modular



EASY SNAP
SAFETY SEAL



STATE-OF-THE-ART
PRESSURE GAUGE



CONTROLLABLE
DISCHARGE MECHANISM



EPDM RUBBER
HOSEPIPE



WORLD CLASS QUALITY
CONTROL SYSTEMS

Fire Extinguishers | Hydrant | Hose Boxes | Fire Hose | Reels | Sprinklers | Accessories

Email id: siyaramenterprises1998@gmail.com , Contact No.: [+917827238894](tel:+917827238894)

OFFICE ADDRESS: 1/17, SWAROOP NAGAR, BURARI ROAD NEAR AZAD PLACE, NEW DELHI -110042.

MULTI-PURPOSE

ABC DRY POWDER

STORED PRESSURE TYPE FIRE EXTINGUISHER

Suitable for Class A, B & C fires that involve Wood, Paper, Paints, Solvents, Liquid Petrol, Cloth, Flammable Gas, Electric Stated Fire. Easily operated by one person.



TECHNICAL SPECIFICATIONS

Capacity	ABC 1 KG	ABC 2 KG	ABC 4 KG	ABC 6 KG	ABC 9 KG
BIS Specification	IS 15683:2018	IS 15683:2018	IS 15683:2018	IS 15683:2018	IS 15683:2018
Type of Fire	ABC	ABC	ABC	ABC	ABC
Extinguisher Type	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure	Stored Pressure
Extinguishing Media	Dry Powder (Mono Ammonium Phosphate) Pressurized with N2 gas	Dry Powder (Mono Ammonium Phosphate) Pressurized with N2 gas	Dry Powder (Mono Ammonium Phosphate) Pressurized with N2 gas	Dry Powder (Mono Ammonium Phosphate) Pressurized with N2 gas	Dry Powder (Mono Ammonium Phosphate) Pressurized with N2 gas
Min. Effective Discharge(%)	90	90	90	90	90
Min. Jet Length (mtr)	2	2	4	6	6
Test Pressure (kgf/cm ²)	35	35	35	35	35
Charged Pressure (kgf/cm ²)	15	15	15	15	15
Operation Position	Upright	Upright	Upright	Upright	Upright
Operating Valve	Squeeze Grip Type with Nozzle	Squeeze Grip Type with Nozzle	Squeeze Grip Type with Discharge Pipe & Nozzle	Squeeze Grip Type with Discharge Pipe & Nozzle	Squeeze Grip Type with Discharge Pipe & Nozzle
Operating Temperature	-10° to +60°C	-10° to +60°C	-10° to +60°C	-10° to +60°C	-10° to +60°C
Fire Rating	1A, 21B	1A, 34B	2A, 55B	3A, 89B	4A, 144B

ALSO AVAILABLE IN MAP 90 POWDER



Wood, Paper,
Fabric etc.



Oil, Kerosene,
Petrol, etc.



Flammable
Gases



Electrical
Started



Email id: siyaramenterprises1998@gmail.com , Contact No.: [+917827238894](tel:+917827238894)

OFFICE ADDRESS: 1/17, SWAROOP NAGAR, BURARI ROAD NEAR AZAD PLACE, NEW DELHI -110042.

DRY CHEMICAL POWDER



TYPE FIRE EXTINGUISHER

Suitable for Class B & C fires that involve Flammable Liquid Petroleum Products, Flammable Gases, Plastics & Electrical Fires.

TECHNICAL SPECIFICATIONS

Capacity	DCP 4 KG	DCP 6 KG	DCP 9 KG
BIS Specification	IS 15683:2018	IS 15683:2018	IS 15683:2018
Type of Fire	BC	BC	BC
Extinguisher Type	Stored Pressure/Gas Cartridge	Stored Pressure/Gas Cartridge	Stored Pressure/Gas Cartridge
Extinguishing Media	Dry Powder Sodium Bi Carbonate	Dry Powder Sodium Bi Carbonate	Dry Powder Sodium Bi Carbonate
Min. Effective Discharge(%)	90	90	90
Min. Jet Length (mtr)	4	6	6
Test Pressure (kgf/cm ²)	35	35	35
Charged Pressure (kgf/cm ²)	15	15	15
Operation Position	Upright	Upright	Upright
Operating Valve	Squeeze Grip Type with Discharge Pipe & Nozzle	Squeeze Grip Type with Discharge Pipe & Nozzle	Squeeze Grip Type with Discharge Pipe & Nozzle
Operating Temperature	-10° to +60°C	-10° to +60°C	-10° to +60°C
Fire Rating	55B	89B	144B



Oil, Kerosene,
Petrol, etc.



Flammable
Gases



Electrical
Started



CARBON DIOXIDE GAS

TYPE FIRE EXTINGUISHER

Suitable for Class B & C fires that involve material like fabric, Oil, Gases, Live Electric & Delicate Machineries.

TECHNICAL SPECIFICATIONS

Capacity	CO ₂ 2 KG	CO ₂ 3 KG	CO ₂ 4.5 KG
BIS Specification	IS 15683:2018	AS PER IS 15683	IS 15683:2018
Type of Fire	BC	BC	BC
Extinguisher Type	Stored Pressure	Stored Pressure	Stored Pressure
Extinguishing Media	CARBON DIOXIDE	CARBON DIOXIDE	CARBON DIOXIDE
Min. Jet Length (mtr)	2	2	2
Test Pressure (kgf/cm ²)	250	250	250
Operation Position	Upright	Upright	Upright
Operating Valve	Squeeze Grip /Wheel Type	Squeeze Grip /Wheel Type	Squeeze Grip /Wheel Type
Operating Temperature	-10° to +60°C	-10° to +60°C	-10° to +60°C
Fire Rating	21B	21B	55B



Oil, Kerosene,
Petrol, etc.



Flammable
Gases



Electrical
Started



Email id: siyaramenterprises1998@gmail.com , Contact No.: [+917827238894](tel:+917827238894)

OFFICE ADDRESS: 1/17, SWAROOP NAGAR, BURARI ROAD NEAR AZAD PLACE, NEW DELHI -110042.

			
Nozzle	Fog Nozzle	Revolving Branch	Triple Purpose Nozzle
			
M/F Hose Coupling	Monitor	Auto. Operated Monitor	FB-5X FB-10X
			
Two Way Inlet	Three Way Inlet	Four Way Inlet	Smoke Detector
			
PVC Hose Reel	R.R.L. Hose	Manual and Electric Siren	Hooter MS / Hooter ABS
			
Fire Bucket & Stand	Traffic Cone & Chain	MCP / MCB ABS	Sprinklers
			
Fire Axe & Beater	Double Door Hose Box	Single Door Hose Box	Fire Ball

Design and specification are subject to change without notice owing to continuous product up-gradation. Technical specifications are subject to production tolerances, we can not be held responsible for printing errors, should they occur.

PRODUCTS BY:

SIYA RAM ENTERPRISES

Email id: siyaramenterprises1998@gmail.com , Contact No.: [+917827238894](tel:+917827238894)

OFFICE ADDRESS: 1/17, SWAROOP NAGAR, BURARI ROAD NEAR AZAD PLACE, NEW DELHI -110042.