


ISO 13485:2016 & ISO 9001:2015 Certified Company



# NICU PRODUCT CATALOGUE



As the name suggests, we believe in delivering *Accuracy*, which is the most important parameter in healthcare equipment field, while maintaining product quality and reliability to highest standards. Innovative, user friendly solutions with true value for money products & prompt customer support being our greatest strength.



# Continually evolving care for newborns...

Our neonatal care technology enable you as caregivers to deliver life-sustaining, non-invasive, developmental care to neonates in a nurturing and supporting environment. Our goal is to help you improve patient outcomes during the newborn's golden hour, transport flow and NICU stay. As your specialist in acute care, we continue developing outstanding technology and delivering innovative designs that is focussed on your newborns - helping to ease work flows, improve therapy and support developmental care and infection prevention practices.

"Saving Children's Lives, A Responsibility We Share"



# **Infant Phototherapy Stand**

**Acculoc PT540** 



# **Acculoc Pt540 - Features**




#### **IRRADIANCE**

Adjustable intensity (20 - 50 µW/cm2/nm)



# MODES OF OPERATION

Program(Timeout setting) and Manual Control



### WAVELENGTH

Optimal wavelength LED(445 - 465 nm) ensures Maximum bilirubin metabolism



#### **DISPLAY**

LCD for Treatment Time, Total LED lifetime, Intensity Level & Mode




LAMP TYPE

LEDs (40,000 hours)



### NUMBER OF LEDS

18 Blue LEDS (3 - Watts) 6 white LEDS (Examination)



SAFETY

Light free of UV and IR



COOLING FAN

2 Noiseless cooling fan



MOBILITY

3 Swivel Casters with brakes



TILTING

Tilt up-to +/- 90 Degrees



CONSTRUCTION

**MS Powder Coated** 



POWER 80 Watts

SUPPLY VOLTAGE

110-240V AC, 50/60 Hz



ALARMS

**High Temperature** 



DIMENSIONS 60×90×(100-160) cm

WEIGHT

15Kgs

PT-540 assures fastest bilirubin breakdown, with high light intensity, treating neonatal jaundice in least possible time.

# Infant Phototherapy Double Surface




- 1. Acculoc PT 540 Stand
- 2. Infant Trolley IT1000
- 3. Acculoc PT 540U (Under Surface)

# **Infant Radiant Warmer Stand**

**Acculoc RHW A002** 



# **Front Panel Controls**



# **Ordering Combinations**









# **Infant Radiant Warmer**

**Acculoc RHW A002 with Infant Trolley** 



- 1. Acculoc RHW A002 Stand
- 2. Infant Trolley IT1000

# **Front Panel**

# **Back Panel**





### **OPERATING MODES**

- SKIN MODE:
  - Body or Skin sensor inputs data to PID heater control, with appropriate timely alarms.
  - AIR MODE:
- Air sensor inputs data to PID heater control, with appropriate timely alarms.

#### MANUAL / PRE-WARM MODE:

User can set heater level for pre heating.

# **DISPLAY INDICATIONS**

### LCD DISPLAY

- Current Mode
- Heating speed
- > APGAR timer.
- Alerts: Low Temp, High Temp, Probe fail
- > Settings: Set Temp, Low Alarm, High Alarm, Manual mode timer, Calibration, Product branding

### SEVEN SEGMENT (DIGIT) DISPLAY:

Displays actual Skin and Air temperature, blinks for out of range values (Low and high alarm) and clears (display dashes) upon probe fail.

### **ALERTS / ALARMS**

#### Power Fail

Alerts when there is a power fail with audio and visual alarm (cannot be muted).

#### Sensor Probe Fail

Alerts when probe is faulty or disconnected. Displays "- - - " on it's temp display.

#### Heater Fail

System senses heater power and generates audio and visual alarm.

#### Low temperature

Actual temp less than set low temp triggers this alarm. Displays blinks.

### High temperature

Actual temp more than set high temp triggers this alarm. Displays blinks.

#### Manual mode Time out

Short sound alert and timer flashing on LCD.

#### System Fail

Alarms when system fails, heater turns off.

# **Acculoc RHW A002 - Features**



# **HEIGHT ADJUSTMENT**

Heater height adjustable to match various bassinets



#### PID Controlled

Ensures least startup time, constant accurate temperature control with power efficiency



#### **HEATER**

650 Watts German ceramic heater, ensuring max efficiency



#### **HEATER ROTATION**

Rotates +/- 90 degrees



#### **BED TILTING**

Smooth bassinet tilting



### SIDE SUPPORT

Acrylic ultra clear side support



IV STAND

Dual IV hooks



#### **EQUIPMENT TRAY**

Steady big size tray, on both sides, with liquid bypass



### SKIN PROBE

High accuracy sensor with long lasting silicon Teflon cable



### AIR PROBE

High accuracy sensor with long lasting silicon Teflon cable



#### XRAY CASSETTE

Sliding XRAY Cassette holder with dimensions marking



### LAMP TYPE

**LED** observation lamp



#### CONSTRUCTION

Mild Steel powder coated



#### MOBILITY

4 Swivel caster wheels, with (2) brakes



# DIMENSIONS

 $3 \times 4 \times 6.5$  feets

WEIGHT 55 Kgs



# POWER 700 Watts SUPPLY VOLTAGE 220- 240V AC, 50/60 Hz

Acculoc belives in providing simple, high quality, innovative products to their customers, enabling them deliver best patient care in most efficient & cost effective way.

**Infant Radiant Warmers** 

**NBUVB Phototherapy Unit** 

**Infant Trolley** 

**Electronic Tourniquet Machine** 

**DVT Pumps** 

**Examination Light** 

Manufactured By (OEM):
APS Embedded Systems
~ Simplyfying Solutions

105, Neelam Industries, Kandivali (West), Mumbai - 400067, Maharashtra, India.



+91- 9029145142 / 8355872880



sales@acculoc.in support@acculoc.in



www.acculoc.in

Channel partner / Distributor