

OP-15

15" Open Frame TFT LCD Industrial Touch Display



Features:

- 15" Color active matrix LCD Module
- XGA 1024X768 Native mode/ LED Backlight
- VGA Signal Input
- Wall mount Vesa screw holes 75X75 mm
- Build 5wire Resistive Touch Screen
- Project Capacitive Multi-Touch Screen Options
- VGA+DVI+HDMI Composite Input Options
- USB , RS-232 , PS2 Touch Interface Options
- Customized By User's Request

Specifications

Model	OP-15	
Display Specifications	LCD Display	15" Color active matrix LCD Module
	Pixels H x V (Max Resolutions)	XGA (1024 X 768) (native mode)
	Active Area	304.1 (H) x 228.1 (V) (15" diagonal)
	Support Color	262K(6-bit) / 16.2M(8-bit) colors
	Pixel Pitch	0.297 (H) x 0.297 (V) mm
	Luminance	300 cd/m ² LED Backlight
	Contrast Ratio	2500 : 1 (Typical)
	Scan frequency	Horizontal: 30 to80 KHz / Vertical : 50 to 75 Hz
	Viewing Angle	176°/176° (H/V)
	Response Time	7/14 ms (tf/tr)
	Input Signal	R/G/B Analog
	Signal type	15 Pin D-sub VGA only
	Plug & Play	DDC 2B
	OSD Controls/Button	Power, Auto, Menu / Enter, Up, Down
	Mechanical Specifications	Power Consumption
Power Management		VESA DPMS
Power Supply		Input : DC 12V/3.0A or DC 12~24V(Options)
Signal Options		VGA+DVI+HDMI Composite Input
Touch Screen Options		5W Resistive Antiglare / Project capacitive
Construction		Metal
Housing Options		Metal , Stainless Steel
Environmental Specifications	Front Bezel	Options
	Dimensions	358 (W) X 290 (H) x 48 (D) (mm)
	Mounting Options	Rear Mount, Wall Mount
	Weight	3.8 KG
	Operating Temperature	-10°C~50°C
	Storage Temp.	-20°C~70°C
Environmental Specifications	Relative Humidity	Less than 85%
	EMC Approved	CE,FCC
	RoHS Compliance	RoHS Compliance

All product specifications are subject to change without notice

Revised Date : 21-APR-2020

