

OPE-190F

19" Panel Mounting Industrial Touch Display



Features:

- ▣ 19" Color active matrix LCD Module
- ▣ SXGA 1280X1024 Native mode/ LED Backlight
- ▣ Wall mount Vesa screw holes 75&100mm
- ▣ Build In 5wire Resistive Touch Screen
- ▣ VGA+DVI+HDMI Signal Input Options
- ▣ Project Capacitive Multi-Touch Screen Options
- ▣ USB , RS-232 Touch Interface Options
- ▣ Customized By User's Request

Specifications

Model	OPE-190F	
Display Specifications	LCD Display	19" Color active matrix LCD Module
	Pixels H x V (Max Resolutions)	SXGA (1280 X 1024) (native mode)
	Active Area	376.32 (H) x 301.056 (V) (19" diagonal)
	Support Color	16.7M colors
	Pixel Pitch	0.294 (H) x 0.294 (V) mm
	Luminance	250 cd/m ²
	Contrast Ratio	1000 : 1 (Typical)
	Scan frequency	Horizontal: 30 to80 KHz / Vertical : 50 to 75 Hz
	Viewing Angle	176°/170° (H/V) (CR=5)
	Response Time	5 ms (tf+tr)
	Input Signal	R/G/B Analog
	Signal type	15 Pin D-SUB
	Plug & Play	DDC 2B
	OSD Controls/Button	Power, Auto, Menu / Enter, Up, Down
	Power Consumption	30W(Max.) /Standby under 4W
	Power Management	VESA DPMS
	Power Supply	Input : DC 12V/4.0A or DC 12~24V(Options)
Signal Input Options	VGA+DVI+HDMI Composite Input	
Touch Screen Options	5W Resistive Antiglare / Project Capacitive Multi-Touch Screen	
Mechanical Specifications	Construction	Aluminum & Varnish
	Housing Options	Metal & Varnish , Stainless Steel
	Front Bezel	Yes
	Dimensions	471.5(W) X 394.5 (H) x 60 (D) (mm)
	Mounting Options	Rear Mount, Wall Mount
	Weight	5.5 KG
Environmental Specifications	Operating Temperature	0°C~50°C
	Storage Temp.	-20°C~60°C
	Relative Humidity	Less than 85%
	EMC Approved	CE,FCC
	RoHS Compliance	RoHS Compliance

