

RA-121E

Metal Chassis 12.1" TFT LCD Industrial Touch Display



Features:

- ▣ 12.1" Color active matrix LCD Module
- ▣ XGA 1024X768 Native mode
- ▣ Wall mount Vesa screw holes 75x75mm
- ▣ Build 5wire Resistive Touch Screen
- ▣ Project Capacitive Multi-Touch Screen Options
- ▣ VGA+DVI+HDMI Input Options
- ▣ USB , RS-232 Touch Interface Options
- ▣ Customized By User's Request

Specifications

Model	RA-121E	
Display Specifications	LCD Display	12.1" Color active matrix LCD Module
	Pixels H x V (Max Resolutions)	XGA (1024 X 768) (native mode)
	Active Area	245.76 (H) x 184.32 (V) (12.1" diagonal)
	Support Color	262K(6-bit) / 16.7M(8-bit) colors
	Pixel Pitch	0.24 (H) x 0.24 (V) mm
	Luminance	350 cd/m ² LED Backlight
	Contrast Ratio	800 : 1 (Typical)
	Scan frequency	Horizontal: 30 to80 KHz / Vertical : 50 to 75 Hz
	Viewing Angle	160°/160° (H/V)
	Response Time	16 ms (tr/tf)
	Input Signal	R/G/B Analog
	Signal type	15 Pin D-sub VGA only
	Plug & Play	DDC 2B
	OSD Controls/Button	Power, Auto, Menu / Enter, Up, Down
	Power Consumption	30W(Max.) /Standby under 4W
	Power Management	VESA DPMS
Power Supply	Input : DC 12V/3.0A	
Signal Options	VGA +DVI+HDMI Composite or VGA Only Input	
Touch Screen Options	5W Resistive Antiglare / Project Capacitive Multi-Touch	
Mechanical Specifications	Construction	Metal & Varnish
	Housing Options	Metal & Varnish , Aluminum , Stainless Steel
	Color Options	Black , White
	Dimensions(WXHXD)	296 X 234 X 41 (mm)
	Mounting Options	Panel Mount ,Desktop, Wall Mount
	Weight	3 KG
	Operating Temperature	-10°C~50°C
	Storage Temp.	-20°C~70°C
Relative Humidity	Less than 85%	

All product specifications are subject to change without notice

