

RA-19

Metal Chassis 19" TFT LCD Industrial Touch Display



Features:

- 19" Color active matrix LCD Module
- SXGA 1280X1024 Native mode
- Wall mount Vesa screw holes 100X100&130X130mm
- VGA Signal Input
- Build 5wire Resistive Touch Screen
- Project Capacitive Multi-Touch Screen Options
- VGA+DVI+HDMI Input Options
- USB , RS-232 Touch Interface Options
- Customized By User's Request

Specifications

Model	RA-19	
Display Specifications	LCD Display	19" Color active matrix LCD Module
	Pixels H x V ((Max Resolutions)	SXGA (1280 X 1024) (native mode)
	Active Area	376.32 (H) x 301.056 (V) (19" diagonal)
	Support Color	16.7M colors
	Pixel Pitch	0.294 (H) x 0.294 (V) mm
	Luminance	250 cd/m ²
	Contrast Ratio	1000 : 1 (Typical)
	Scan frequency	Horizontal: 30 to80 KHz / Vertical : 50 to 75 Hz
	Viewing Angle	176°/170° (H/V) (CR=5)
	Response Time	5 ms (tf+tr)
	Input Signal	R/G/B Analog
	Signal type	15 Pin D-sub VGA only
	Plug & Play	DDC 2B
	OSD Controls/Button	Power, Auto, Menu / Enter, Up, Down
	Power Consumption	35W(Max.) /Standby under 4W
	Power Management	VESA DPMS
Power Supply	Input : DC 12V/3.0A or DC 12~24V(Options)	
Signal Options	VGA +DVI+HDMI Input	
Touch Screen Options	5W Resistive Antiglare / Project Capacitive Multi-Touch	
Mechanical Specifications	Construction	Metal & Varnish
	Housing Options	Metal & Varnish , Stainless Steel
	Color Options	Black , White
	Dimensions	463.8(W) x 384.9 (H) x 45.85 (D) (mm)
	Mounting Options	RACK Mount ,Desktop, Wall Mount
	Weight	8.5 KG
Environmental Specifications	Operating Temperature	-10°C~50°C
	Storage Temp.	-20°C~70°C
	Relative Humidity	Less than 85%
	RoHS Compliance	RoHS Compliance

