



SAE 5W-30

Synthetic Blend Motor Oil

Mobil: (+84) 982 070 575 / Email: sales@trusoilvietnam.com / Website: www.trusoilvietnam.com

TRUSOIL Synthetic Blend SAE 5W-30 Motor Oil a premium quality multi-grade motor oil designed with a state-of-the-art low friction additive system for superior engine protection even under the toughest driving conditions. It outperforms conventional motor oil, reduces friction and wear at start-up and protects your engine against performance robbing sludge and varnish deposits. TRUSOIL Synthetic Blend Motor Oil is recommended for passenger car, truck, sport utility vehicle and other mobile or stationary engines.

TRUSOIL Synthetic Blend SAE 5W-30 Motor Oil meets or exceeds SQ/GF-7A and American Petroleum Institute (API) Resource Conserving SP service classifications and is compatible with all prior API categories. TRUSOIL Synthetic Blend SAE 5W-30 Motor Oil has been field tested to be comparable to most American, Asian and European manufacturers' standards including Chrysler MS 6395 and Ford WSS-M2C929A, WSS-M2C946A and many other OEM's specifications where a synthetic blend API SP motor oil is recommended.

Benefits and Applications

- TRUSOIL Synthetic Blend motor oil outperforms conventional oil
- Excellent wear, corrosion, and rust protection
- Exceptionally resistant to oxidation
- Excellent cold-crank capabilities
- Helps improve fuel economy

Typical Characteristic 5W-30 Synthetic Blend Oil

| | | |
|------------------------|------------|-------------|
| SAE GRADE | Syn Blend | 5W-30 |
| API SERVICE | | SQ/GF-7A |
| API Gravity | ASTM D287 | 33.26 |
| Flash Point, COC °C/°F | ASTM D92 | 221 / 429.8 |
| Pour Point, °C/°F | ASTM D97 | -48 / -54.4 |
| Viscosity @ 40°C, cSt | ASTM D445 | 60.71 |
| Viscosity @ 100°C, cSt | ASTM D445 | 10.23 |
| Viscosity Index | ASTM D2270 | 157 |
| CCS, mPa-sec °C max | ASTM D5293 | 6600 @ -30 |
| Total Base No. TBN | ASTM D2896 | 7.0 |

MEETS API SQ / ILSAC GF-7A

Chrysler MS 6395
Ford WSS-M2C929A,
WSS-M2C946A



Test Method ASTM - Typical test data are average values only. Minor variations, which do not affect performance, may occur.

HANDLING AND SAFETY INFORMATION - Refer to TRUSOIL (SDS) Safety Data Sheets for proper handling and safety information. Use the same care and handling as for any petroleum product. Nothing herein shall be deemed to constitute a warranty, express or implied, that said information or data are correct or that the products described are merchantable or fit for a particular purpose, or that said information, data or products can be used without infringing patents of third parties.

Distributed by: TRUSOIL VIETNAM JSC, E1 Road No. 12, Hoang Gia Industrial Park, Hamlet 2, My Hanh Nam Commune, Duc Hoa District, Long An Province, Vietnam.
Manufactured by: US GLOBAL PETROLEUM, 9101 FULLERTON AVENUE, FRANKLIN PARK, IL 60131