



High Packing Density



MBR – MEMBRANE BIOREACTOR HOLLOW FIBRE MEMBRANE HYPER™ PVDF HMBR-MA10-2.5-RF020



Overview

MEMTIK HMBR PVDF Series, is a high-quality reinforced Hollow Fibre MBR membrane optimized for small to large flux wastewater treatment plants.

Structured with HYPER™ PVDF (permanently hydrophilic polyvinyl difluoride) has **the advantage of dry storage**.

HMBR PVDF Series membranes can be used for a wide variety of treatment applications such as industrial and domestic wastewaters.

- Permanently hydrophilic
- High chlorine tolerance
- Backwashable membrane

Product Specifications

Effective membrane area	m ²	10
Dimensions (w×h×d)	mm	610x1200x45
Weight	Kg	5
OD	mm	2.5
Nominal pore size	µm	0.2
Membrane material	PET tube + HYPER™ PVDF	

Product Performances

Storage & Maintenance	Dry Storage	
Membrane properties	Permanently hydrophilic	
Surface properties	Non-Ionic	
Design flux rate	L/m ² .h	10~20
Peak hourly flux rate	L/m ² .h	25~35
MLSS	mg/L	4,000~12,000

Operating Specifications

Operating temperature	°C	5~40
DO concentration	mg/L	>1
pH range (Operation, Cleaning)		2~10, 1~11
Air integrity test pressure	MPa	0.02
Max. aeration rate	L/min/pc	160
TMP range	MPa	-0.05~0.03
Operating pressure	MPa	-0.02~0
Max. operating pressure	MPa	<-0.05
Backwash pressure	MPa	0.02
Max. backwash pressure	MPa	<0.03



Disclaimer: MEMTIK or its related company is continuously updating and improving its products and services, so please contact us for more detailed information or to confirm specifications. MEMTIK takes no responsibility for any errors resulting from the use of information contained within this document.

Whatsapp: +65-91275988 Email: memtik@c2csiingapore.com Web: membrane.c2csiingapore.com