

SUNTC Air Blast Sprayer



FXS7/340



FXS8/680



FXS7A/340

FEATURES:

- Diaphragm pump
- Anti-drip brass double nozzle
- Hand-washing tank (capacity 10L/15L)
- Circuit-rinsing tank (capacity 40L/80L)
- Outside transparent level gauge
- Suction filter with check-valve.
- Hydraulic liquid stirrer
- Control unit with pressure regulator
- Clutch for ventilation fan gear box
- Hot galvanized frame



FXS8B/680

Model	FXS7/340 FXS7A/340	FXS7/440 FXS7A/440	FXS7/680 FXS7A/680	FXS8/680 FXS8A/680 FXS8B/680
Matching Power (hp)	≥ 35	≥ 35	≥ 50	≥ 50/75
Chemical Tank Capacity (L)	300	400	600	600/800
Radius Range (m)	≥ 10	≥ 10	≥ 10	≥ 10
Nozzles (pcs)	10	10	10	12/12/14
Pump flowrate (L/min)	78	78	78	78
Working pressure (Mpa)	0-4	0-4	0-4	0-4
Ventilation fan diameter (mm)	700	700	700	800
Net Weight (kg)	190	195	266	270/309 280/317
Dimension (cm)	130*100*127	130*100*150	150*136*136	150*136*136 163*143.5*140.5



FXL7B/18/340



FXL7B/18/680

Model	FXL7B/18/340	FXL7B/18/440	FXL7B/18/680	FXL7B/18/880
Matching Power (hp)	≥35	≥35	≥50	≥75
Chemical Tank Capacity (L)	300	400	600	800
Pump flowrate (L/min)	78	78	78	78
Working pressure (Mpa)	0-4	0-4	0-4	0-4
Height of air duct (cm)	180	180	180	180
Ventilation fan diameter (mm)	700	700	700	700
Nozzles (pcs)	14	14	14	14
Net Weight (kg)	256	261	338	345
Dimension (cm)	131*110*184	131*110*184	152*136*192	152*136*192



XQJ50/340



XGT12/340



Model	XQJ50/340	XGJ100/440	XQJ30/13/680	XGT12/340
Matching Power (hp)	≥35	≥35	≥50	≥35
Chemical Tank Capacity (L)	300	400	600	300
Pump flowrate (L/min)	78	78	78	78
Working pressure (Mpa)	0-4	0-4	0-4	0-4
Hose length/diameter (m/mm)	50/8.5	100/8.5	30/13	Boom 1.2*2m
Net Weight (kg)	117	121	197	150
Dimension (cm)	117*100*126	117*100*150	125*136*136	104*100*140



FQS6A/600



FQS7/1000A



FQS8/2000



Model	FQS6A/600	FQS7A/1000A	FQS8/1000A	FQS8/2000	FQS8A2/2000 FQS9A2/2000
Matching Power (hp)	≥15	≥35	≥35	≥50	≥50/75
Chemical Tank Capacity (L)	600	1000	1000	2000	2000
Radius Range (m)	≥10	≥10	≥10	≥10	≥10
Nozzles (pcs)	10	10	12	12	12
Pump flowrate (L/min)	78	125/140	125/140	125/140	125/140
Working pressure (mPa)	0-4	0-4	0-4	0-4	0-4
Ventilation fan diameter (mm)	600	700	800	800	800/900
Net Weight (kg)	305	428	441	635	682/699
Dimension (cm)	212*100*136	236*137*146	251*137*146	349*152*171	350*152*171 354*152*171