# **Boretrak®3**

BORETRAK®3



#### Deploy and Measure at Any Inclination with Full 360° Capability





The Boretrak3 borehole deviation measurement system is a simple-to-use, gyro-based system for measuring the deviation of boreholes at any drill hole operation such as underground and open pit mines, quarries or engineering works.

As a successor to the widely used Boretrak2, the fundamental capabilities of the Boretrak3 are backed by over 40 years of in-the-field history. The Boretrak3 combines this experience into a single, all-purpose unit capable of measuring boreholes in any inclination: down, up or horizontal.

Together with Carlson Boretrak software, the Boretrak3 provides a simple to use system for checking the accuracy of drilled holes and their deviation from design.

#### **Trust Your Measurements**

Boretrak3 high grade gyro sensors deliver high performance and reliable measurements that you can trust.

#### **Sensor Fusion**

Boretrak3 introduces an optional 3D magnetometer output in addition to the existing 3D gyro and accelerometer. This offers an enhanced, stabilised navigation solution.

#### **Optional Magnetometer-Corrected Azimuth**

Reduce gyroscopic azimuth drift with magnetometer corrections or turn off the magnetometer when working near ferrous materials.

# IMU navigation solution

The Boretrak3 utilizes a miniature inertial measurement unit (IMU) which contains a triaxial accelerometer, magnetometer, and gyro. Prior to deployment, the Boretrak is aligned using a known orientation or, alternatively, using the compass heading from the magnetometer. This establishes a starting heading reference for the deployment. As the probe is deployed along the borehole the gyro provides the Boretrak3 with an accurate heading, optionally stabilised by the magnetometer.

# **Deployment Accessories**

The gyro frees up the Boretrak3 to be deployed using a variety of methods. Downhole, the probe can be lowered on a simple wire line. Horizontal and uphole the Boretrak3 can be supplied with a semi-rigid push rod system, spooled out from a cable reel. Alternatively, traditional Boretrak rods can be used and an adaptor allows customised deployment devices to be fabricated for applications unique to your site.



Carlson's Boretrak3 supports both surface and subsurface borehole deviation measurement





Marked steel cable and reel supplied for downhole Boretrak3 deployments





Detailed reports show deltas between the design and actual boreholes

# **Carlson Boretrak**

An Android or Windows tablet is used to run Carlson Boretrak which controls the Boretrak3 operation. Use Carlson Boretrak to setup the project, import hole coordinates, setup design holes and import third party data to form a background to the collected Boretrak3 data. A Bluetooth connection between the probe and mobile device allows setup and calibration prior to the deployment and also synchs the clocks on the probe and the mobile device.

## **Deployment Methodology**

Once in the hole, the probe runs independently – constantly recording data from the IMU onto its internal memory. Each sensor record in the probe is accompanied by a time stamp.

The probe is deployed along the hole at fixed intervals. At each stop, a reading is taken in Carlson Boretrak software. When the end of the hole is reached, the probe is retrieved and, when the Bluetooth link is re-established, all data is downloaded from the probe into Carlson Boretrak.

Carlson Boretrak reads the time stamps recorded on the mobile device and extracts the records in the Boretrak3 probe data which match these time stamps. With reference to a starting hole collar coordinate and a calibrated gyro value, these raw observations are converted into X, Y, Z coordinates. A model of the hole is created, and a comparison made to a design hole or another survey of the same hole.

### **Display and Outputs**

All data from surveyed holes is immediately displayed, in 3D graphical mode, 2D schematic mode, or in tabular formats.

Back in the office, data can be transferred onto Carlson Boretrak running on your desktop or laptop PC for further analysis.

Survey data from the Boretrak3 can be exported seamlessly to other Carlson packages such as CarlsonOPS using the DRL format. Other formats such as DXF and CSV can be used to export to third party CAD and blast design packages.

Reports can be generated for each hole, showing all data in plan, front, side or 3D views, together with tabular data outlining each reading during a deployment.







Carlson Boretrak used in Desktop mode on an office PC

# Carlson Software and Technology Solutions

The Boretrak3 is one of many Carlson hardware and software products dedicated to providing solutions in the mining and quarrying industries.

The Boretrak3 works seamlessly with the Quarryman® Pro profiler and CarlsonOPS blast design software.

Carlson Boretrak software - which drives the Boretrak - also works with the VS+ underground stope scanner and the C-ALS® HD cavity scanner and so can combine surveys of ring blasts and underground scans. Boretrak data can be integrated with stope scans to compare actual hole surveys and the void created from the blast.

Carlson Mining imports borehole data from Boretrak3 and scan data from C-ALS and VS+ to help monitor the as-built world underground.



# **CarlsonOPS for Simple and Comprehensive Blast Design**

CarlsonOPS is a separate software module for blast design and complements workflows supported by the Boretrak3. Work with point clouds to develop meshes, create blast pattern layouts, and ensure proper burden and borehole spacing for more productive blasting and project optimization. Utilize Boretrak3 data to assess borehole deviation from design.

- Plan blast pattern layouts
- Work with burden measurements for hole loading
- Load the holes
- Quality check timing and initiation and more.



# **Specifications**

Construction		
Probe		Stainless steel
Downhole cable		5mm plastic-coated steel cable with metre markers
Push cable		9mm Fibreglass rod with aluminium frame and reel
Physical		
Weight	Probe (inc batteries)	3.4 kg
	System in case (inc	
	50m cable &	13.3 kg
	optional PDA)	
Dimensions	Probe	710 mm x 40 mm (L x Dia)
	Case	625 mm x 500 mm x 218 mm (L x W x H)
Sensor		
Build		IMU with 3-axis gyro, accelerometer and magnetometer
Gyro rotation limit		Configurable: up to 1920° per second
Inclination accuracy		+/-0.1°
System deployment accuracy		Final position within 1% of hole depth*
Power		
Probe		$4 \times 1.5$ D cells (LR20)
Environmental		
IP rating		IP68 waterproof (pressure rated to 300 m)
Operating temperature**		-10° C to +60° C
Storage temperature**		-20° C to +70° C

\* Proved under Carlson test conditions

\*\* The probe operating  $\vartheta$  storage temperature may be limited by the choice of battery.

For further information and the best possible application and performance support please contact Carlson at lasermeasurement@carlsonsw.com

CARLSON SOFTWARE Inc | 33 East Second Street | Maysville, KY 41056 | 800-942-2540 | www.carlsonsw.com