

# **Technical Data Sheet** SolarRinse

#### **Product Information**

Nasiol SolarRinse is a cleaning solution/detergent designed to remove dirt, grime, and other contaminants from all solar panel types, enhancing their performance and efficiency. It is used to wash photovoltaic solar panels and its quick action makes it easy to clean all kinds of dirt.

## **Application Surfaces**

Suitable for all residential, commercial, industrial solar panels

## **Benefits & Key Features**

- Ready to use.
- Easy application.
- Effective results.  $\circ$
- No water spots/stains. 0
- VOC compliant.
- Restores photovoltaic efficiency.
- Formulated for all solar panels Thermal or photovoltaic.

#### Instructions

- Rinse the panels initially with water.
- Then spray the product directly onto the panel surface.
- Leave to act for a few seconds.
- Brush or mop the entire surface of the panels to remove or loose all dirt present on the solar modules.
- Rinse the panels with water to remove any dispersed dirt or excess of product left on the panels.

### **Application Tips**

Before use shake the bottle very well. The product is ready for use, apply without dilution. It can be used with cleaning robots or manual cleaning tools. After spraying, surfaces should be allowed to dwell for a few seconds. Do not allow product to dry.

## **Specifications**

| Packaging               | 500 mL                 |
|-------------------------|------------------------|
|                         | 5L-30L                 |
| Appearance              | Off-White-             |
|                         | Translucent            |
| Density @23°C (73.4°F)  | 1.03 g/cm <sup>3</sup> |
| pH Value                | 2.5-3.5                |
| Application Temperature | 5°C-30°C /             |
|                         | 41°F- 86°F             |
|                         | (≤50% RH)              |

## **Storage**

To achieve a high product effectiveness, keep the unopened packaging in a dry, well ventilated space away from heat and ignition sources, stored at 0°C to + 30°C / 32°F to 86°F. The shelf life of product is 24 months from the date of production when stored in the unopened packaging under suggested storage conditions. After every use, it is recommended to close the lid in order to avoid product loss by evaporation.

#### **Disclaimer**

The technical information described in this document is based on tests and other practical experience that Nasiol believes are reliable. Nasiol cannot guarantee anything but ready to use quality of the product at the time of shipment, disclaims any liability for product performance and incidental or consequential damages, according to selfimplementation within the user's knowledge, beyond the manufacturer's control. Please refer to the Safety Data Sheet (SDS) before use of product.

Users should consult Nasiol for guidance on the suitability of specific applications. Nasiol reserves the right to change the given data without further notice.

+90 262 642 81 54