



CHAINPRO SOLUTIONS

CERTIFIED. SECURE. RELIABLE

MARINE CHAIN

ChainPro Solutions specializes in premium-grade chains for marine and mooring applications, engineered for reliability in demanding coastal environments.

Manufactured to meet strict national and international standards, our chains offer exceptional durability and corrosion resistance. Available in painted, galvanized, or zinc thermal diffused finishes, they provide long-lasting performance for a wide range of maritime needs.



TRAWLINK CHAIN

- Advanced heat treatment process enhances strength, toughness, and resistance to hydrogen embrittlement.
- Superior wear resistance ensures extended durability.
- Rigorous quality assurance testing throughout production.
- Certified to ISO 9001:2015 standards.



GRADE 80+ SHORT LINK CHAIN					
COMMODITY	CHAIN DIAMETER	INSIDE LINK DIMENSIONS (MM)		APPROX MASS (KG/M)	MIN BREAK LOAD (T)
		NOMINAL PITCH	MINIMUM WIDTH		
C8+H100SLSBP	10.0	30	14.0	2.21	13.8
C8+H130SLSBP	13.0	39	18.2	3.73	23.0
C8+H160SLSBP	16.0	48	22.4	5.65	35.0
C8+H190SLSBP	19.0	62	24.0	7.57	49.0
C8+H220SLSBP	22.0	66	30.8	10.67	66.0

GRADE 80+ MID LINK CHAIN					
COMMODITY	CHAIN DIAMETER	INSIDE LINK DIMENSIONS (MM)		APPROX MASS (KG/M)	MIN BREAK LOAD (T)
		NOMINAL PITCH	MINIMUM WIDTH		
C8+H100MLSBP	10.0	40.0	14.0	1.96	13.66
C8+H130MLSBP	13.0	52.0	18.2	3.32	23.04
C8+H145MLSBP	14.5	49.0	19	4.33	28.64
C8+H160MLSBP	16.0	64.0	22.4	5.02	34.86
C8+H200MLSBP	19.0	79.0	28.0	7.88	54.43
C8+H220MLSBP	22.0	86.0	30.8	9.58	65.95

GRADE 5 LONG LINK FLOATING AID CHAIN						
COMMODITY	DESCRIPTION	DIMENSIONS			FORCES	APPROX MASS (KG/M)
		DIAMETER	PITCH (P)			
		(DN) NOM	NOM	W1 MIN	WLL TONNE	
C5A160LLPN	16.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	16.0	64.0	20.8	5.10	5.05
C5A200LLPN	20.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	20.0	80.0	26.0	8.00	7.89
C5A260LLPN	26.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	26.0	104.0	33.8	13.5	13.30
C5A280LLPN	28.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	28.0	112.0	36.4	15.6	15.50
C5A320LLPN	32.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	32.0	128.0	41.6	20.5	20.20
C5A360LLPN	36.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	36.0	144.0	46.8	25.9	25.60
C5A400LLPN	40.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	40.0	160.0	52.0	32.0	31.60
C5A450LLPN	45.0 mm GRADE 5 LONG LINK FLOATING AID CHAIN	45.0	180.0	58.5	40.5	39.90