

Dryer Type	Dryer			Heat Source	Electricity Phase	Electricity		Optional Pre-Cleaner
	Capacity	Model	Material					
Diesel Dryer	6.2Ton X 1	62AX	E. G. I	Diesel	Single	3.7	kw/hr	SPC-05
	6.2Ton X 1	62SAX	Stainless	Diesel	3 Phase	3.7	kw/hr	SPC-05
	12Ton X 1	120BX	E. G. I	Diesel	3 Phase	7.8	kw/hr	SPC-10 with Elevator
	12Ton X 1	120SBX	Stainless	Diesel	3 Phase	7.8	kw/hr	SPC-10 with Elevator
Husk Furnace Dryer	6.2Ton X 1	62AH	E. G. I	HF-100	Single	5.6	kw/hr	SPC-05
	6.2Ton X 1	62SAH	Stainless	HF-100	Single	5.6	kw/hr	SPC-05
	6.2Ton X 2	62AH	E. G. I	HF-170	3 Phase	13	kw/hr	SPC-10 with Elevator
	6.2Ton X 2	62SAH	Stainless	HF-170	3 Phase	13	kw/hr	SPC-10 with Elevator
	12Ton X 1	120EH	E. G. I	HF-170	3 Phase	10	kw/hr	SPC-10 with Elevator
	12Ton X 1	120SH	Stainless	HF-170	3 Phase	10	kw/hr	SPC-10 with Elevator
	15Ton X 1	150EH	E. G. I	HF-170	3 Phase	10	kw/hr	SPC-10 with Elevator
	15Ton X 1	150SH	Stainless	HF-170	3 Phase	10	kw/hr	SPC-10 with Elevator
	15Ton X 3	150EH	E. G. I	HF-550i	3 Phase	35	kw/hr	2 X SPC-10 with Elevators
	15Ton X 3	150SH	Stainless	HF-550i	3 Phase	35	kw/hr	2 X SPC-10 with Elevators
	12Ton X 4	120EH	E. G. I	HF-550i	3 Phase	40	kw/hr	2 X SPC-10 with Elevators
	12Ton X 4	120SH	Stainless	HF-550i	3 Phase	40	kw/hr	2 X SPC-10 with Elevators
	15Ton X 4	150EH	E. G. I	HF-750i	3 Phase	42	kw/hr	2 X SPC-10 with Elevators
	15Ton X 4	150SH	Stainless	HF-750i	3 Phase	42	kw/hr	2 X SPC-10 with Elevators
	25Ton X 2	250MSH	Stainless	HF-550i	3 Phase	42	kw/hr	2 X SPC-10 with Elevators
Dual Type (Diesel + Husk Furnace)	6.2Ton X 1	62AX	E. G. I	Dual (HF100)	Single	6	kw/hr	SPC-05
	6.2Ton X 1	62SAX	Stainless	Dual (HF100)	Single	6	kw/hr	SPC-05
	12Ton X 1	120BX	E. G. I	Dual (HF170)	3 Phase	10	kw/hr	SPC-10 with Elevator
	12Ton X 1	120SBX	Stainless	Dual (HF170)	3 Phase	10	kw/hr	SPC-10 with Elevator