



PT.MBB INDONESIA

Office : Jl. Raya Kebonsari No.19, Surabaya, Jawa Timur
Showroom : Jl. Raya Jemursari No. 69, Surabaya, Jawa Timur

(031) 8274664
(031) 99848032

Specifications and Models : 98 inch MBB INTERACTIVE SMARTBOARD

Display Parameters	Screen size	98"LED Screen(16:9): 2157.9 x 1213.35mm (HxV)
	Screen branding	Original new ultra-clear LED screen
	Resolution	3840(H)×2160(V)
	Viewing angle	178 degree(H):178 degree(V)
	Brightness	350cd/m2
	Contrast	5000 : 1
	Response time	8ms
	Color depth	16.7M
	Frequency of scans	4K-60HZ
	Backlight	DLED
	Display the output	HDMI
	Color system	PAL NTSC
	Sound	3D stereo sound output power 2*10W
	Display protection	Tempered explosion-proof glass
Touch Parameters	Touch embedding method	Built-in all-in-one, non-plug-in
	Touch sensitive technology	Infrared sensor recognition touch technology (20 points)
	Notation	Fingers, stylus or other points not less than 2mm in diameter
	Cursor speed	120 points/s
	Positioning accuracy	More than 90% of the touch area is ±1mm
	Communication interface	USB male type B
	Touch resolution	32767*32767
	The number of touches	Theory unlimited times
	The computer responds	Automatic recognition by the system: < 15ms
	Driver	No drive
	Touch function	Support 20-point computer touch operation, support image zoom,
Parameters of the	Motherboard system	Android 11.0
	Motherboard processor	Amlogic T982 processor quad-core Cortex-A55
	Motherboard storage space	32G
	Motherboard memory	4G
	Enter the port	RJ45 network cable interface *2,
		HDMI input port*2,
		Type-C*1,
		DP*1,
		VGA input*1,
		VGA AUDIO*1,
		YPBPR*1,
		AV input*1,
		RS232*1,
		SMALL*1,
		Headphone jack*1,
		SPDIF 1,
		Dual-band WIFI*1,
		TF Card*1,
		Android USB2.0*1,
		Android USB3.0*1,

of the Whole Machine		USB3.0 (all channels)*4, Type-C (All Channels)*1, Touch USB2.0-B*1, touch USB2.0-A*1	
	Output port	Coaxial output, headphone audio output, touch output interface,	
	Front port	USB*2, HDMI IN, TOUCH USB, TYPE-C	
	Storage environment	Storage temperature: -20°C~60°C; Storage humidity: 10%RH~90%RH	
	Working environment	Operating temperature: -10°C~55°C, working humidity:	
	Installation	Pylon (standard)	
	Pylon hole spacing	1000×400MM	
	Power supply type/mode	Three-core power supply/fixed	
	Power interface specifications	Character holder	
	Power consumption	Approx. 576 watts	
	Voltage range	110-240V/50-60Hz	
	Audio	2 x 8n10W midrange speakers on the front	
	Recessed wall installation dimensions	2216.2*1316.6*106.7	
	Principle of recessed wall installation	20mm larger on one side	
	Standby power consumption	≤0.5W	
	Service life	≥ 50,000 hours	
Computer Configurati on	Medium/i3 configuration	High/i5 configuration	High/i7 configuration
		Intel chipsets	
	Intel Core i3-2th/4th	Intel Core i5-2th/4th	Intel Core i7-2th/4th
	8G DDR3 RAM/2.5" 256GB SSD	8G DDR3 RAM/2.5" 256GB SSD	8G DDR3 RAM/2.5" 256GB SSD
	Intel HD Graphics	Intel HD Graphics	Intel HD Graphics
	Enter the port 1*LAN port, 3*USB3.0 port, 3*USB2.0 port, 1*MIC-IN port		
	Output port 1*HDMI port, 1*VGA port, 1*LINE-OUT port		
	Operating System Windows 7 Ultimate operating system (optional for Win 10 operating system).		
Included Attachment s	Standard Accessories: Touch Pen, Warranty Card, Certificate of Conformity, Manual, Remote Control, 1.5m Power Cord		
	OPS Can be option!!!!		

Hormat Kami,



<https://smartboardinteractive.com/>