

# Technical Data Sheet

## Al-Shamal Luxe

### Product Description

Al Shamal Luxe, A top quality, tough durable performance that has been formulated for the professional user to give easy application and better opacity, it has smooth creamy consistency for better brush loading its coverage combined with a further improved gloss level leads to an excellent finished appearance which lasts.



### Application Data

#### Application

Stir well before use normally two coats are required over primed or previously painted surfaces apply evenly with a brush or short pile with brush or short pile roller, avoid over spreading suitable for use with conventional or airless spray equipment thinning up to with whit spirit may be required for spray application.

#### The Product can be applied by

Roller: Premium Quality

Brush: Nylon / Polyester, recommended to paint corners and edges.

Spray: Airless spray or conventional spray.

#### Conditions During Application

The temperature of the substrate should be minimum 5°C and maximum 35°C.

#### Ingredients

LONG OIL - ALKYD - PIGMENT-DRIERS - ADDITIVES.

#### Coverage rate

15 to 16 m<sup>2</sup> per liter, on smooth non porous surfaces.

#### Thinner & Dilution

Mix thoroughly to achieve a homogeneous appearance. Avoid excessive air entrapment. Thin with no more than half a liter of industrial thinner, white spirit, or kerosene per gallon for paintbrush or paint roller application, and one litter per gallon for spray gun application; stir well after thinning and before use.

#### Drying Time

Touch dry after 2-3 hours and Surface dry 4-6 hours in good and well-ventilated conditions, allow 24 hours before the application of the second coat.

### Product Data

Packaging	18L, 3.6L, 1L ±2%
Color	White, beige and all other colors upon request on (Ral Catalogue).
Finish	High-Gloss
Toch drying	1 to 2 hours
Surface drying	4 to 5 hours
Top Coat drying	6 to 7 hours
Complete drying	7 days, at 24°C and 50% relative Humidity.

### Directions for use

#### Surface preparation

Ensure all surfaces are sound dry clean and free from dust or grease loose and flaking areas remove all poorly adhering paint and prime with the appropriate primer.

---

## Storage & Shelf Life

The product must be stored in accordance with national regulations. Keep the containers in a dry, cool, well-ventilated space and away from sources of heat and ignition. Containers must be kept tightly closed. Handle with care.

5 Years when Stored properly in unopened containers in dry condition between 10 to 25 Degrees Centigrade.

---

## Health and Safety Information

- Use masks while painting.
- Flammable, ensure good ventilation during application and drying.
- Keep away from sources of ignition, no smoking while using.
- Maintain good ventilation during painting.
- Keep out of reach of children.
- If the eyes or skin infected, wash it with water and consult a doctor.
- All tools should be washed with industrial thinner immediately after use.

**KEEP AWAY FROM SOURCES OF IGNITION (FLAMMABLE)**  
**KEEP OUT OF REACH OF CHILDREN**  
**PROTECT FROM FREEZING**

---