

SPP-R200III

2-inch Mobile Receipt Printer



Print Characteristics

Print Method
Direct Thermal
Print Speed
Up to 100 mm/sec (Receipt)
Up to 80 mm/sec (Linerless)
Print Resolution
203 dpi
Print Width
Up to 48 mm
Sensor
Paper End, Paper Cover Open

Media Characteristics

Media Type
Receipt, Liner, Linerless (Optional)
Media Width
58 mm/50 mm (Optional)
Media Roll Diameter
Up to 40 mm
Media Thickness
0.07 ± 0.005 mm
Supply Method
Easy Paper Loading

Physical Characteristics

Dimensions (W x L x H)
79.5 x 124.5 x 44.1 mm
(3.13 x 4.90 x 1.74 inch)
Weight
Including battery: 228 g (0.50 lbs.)
Including MSR: 238 g (0.52 lbs.)
Electrical
7.4 V Li-ion, 1200 mAh,
Rechargeable Charging time: Up to 2.5 hrs
EnergyStar® Certified,
External AC/DC Battery Charger
100-240 VAC, 50/60 Hz

Performance Characteristics

Memory
8 MB SDRAM, 4 MB Flash
Interface
Standard: USB 2.0 FS + Serial
Optional: USB 2.0 FS + Serial + Bluetooth® or
WLAN

WLAN: 802.11a/b/g/n
(Infrastructure, Ad-hoc, Wi-Fi Direct,
SoftAP)-WEP40/104,
WPA1/2 (PSK, EAP)

Easy Bluetooth Pairing™ via NFC

Environment Characteristics

Temperature
Operating: -15 to 50°C (5 to 122°F)
Storage: -30 to 70°C (-22 to 158°F)
Humidity
Operating: 10 to 80% RH
Sealing
IP43 (IP54 with protective case)
Drop Rate
2.1 m (7 ft.)/1.5 m (5 ft.) for MSR model

Software

Emulation
BXL/POS™
Driver/Utility
Windows® Driver, OPOS/JPOS Driver,
Linux®/macOS® CUPS Driver, Utility Program
Network Auto Installer
Developer Tools
Android™/iOS®/Windows SDK, Linux SDK,
Xamarin SDK,
Web Print SDK (Android/iOS/Windows/macOS),
Cordova Plugin, MAUI SDK, Flutter™ Plugin
React Native SDK
Design & Print
mPrint App (Android/iOS)

Fonts/Graphics/Symbologies

Character Size
Font A: 12 × 24 Font B: 9 × 17
Font C: 9 × 24, KOR, CHN, JPN: 24 × 24
Characters Per Line
Font A: 32
Font B, C: 42, KOR, CHN, JPN: 16
Character Sets
Alphanumeric: 95
Expanded Graphics: 128 × 33 page
International: 32
Optional Unicode supported
(UTF-8, UTF-16LE, UTF-16BE)
Barcode Symbologies
1D: Codabar, Code 39, Code 93,
Code 128, EAN-8, EAN-13, ITF,
UPC-A, UPC-E
2D: Aztec, Data Matrix, GS1 Databar,
MaxiCode, PDF417, QR code

Accessories/Supplies

Included in the Box
Belt Clip, Battery, AC/DC Battery Charger,
Power Cord
Options & Accessories
Belt Strap, Case, Protective Case,
Shoulder Strap, Battery Pack_V2
(with outer contacts), Single Battery
Cradle, Single Docking Cradle, Quad
Battery Charger, Quad Docking Cradle,
Vehicle Charger, Vehicle Holder,
USB Charger, Serial/USB Cable
Compatible Supplies
B-linerless™

Integrated Card Reader (Optional)

MSR
3 Track (T-DES/DUKPT (Optional))