

Long live your engine

NEXLUB

Product Catalog



Automotive & Industrial Lubricants




nexlub.com



Long live your engine

NEXLUB

We've got you covered with a full line of lubricants, transmission fluids, gear oils, greases, hydraulic oils and coolants to protect practically every moving part in your machine





Petrol Engine Oils

2



CNG Engine Oils

11



Transmission Fluids

14



Antifreeze / Coolants

18



Industrial Lubricants

20

7

**Diesel
Engine Oils**



12

**Motorcycle
Engine Oils**



16

**Automotive
Gear Oils**



19

**Brake
Fluids**



23


Greases



Long live your engine

NEXLUB

Motor Oils for Gasoline Fueled Engine



**Helps Provide
Full Engine
Performance
Efficiency and
Resilience**

Pace NEO Synthetic Series

Full synthetic motor oils designed with a proprietary cleaning booster to provide ultimate protection that prolongs the peak performance and efficiency of your engine, especially under harsh stop-and-go driving conditions, extreme temperatures and heavy loads.

API SP



1L, 4L, 5L, 20L, 208L



| Performance Levels: | | | | | | |
|---------------------|--------------|--------------|--------------|-------|--------------|--------|
| 0W-20 | 0W-30 | 5W-20 | 5W-30 | 5W-40 | 10W-30 | 10W-40 |
| SP (RC) | SP (RC) | SP (RC) | SP (RC) | SP | SP (RC) | SP |
| SN PLUS (RC) | SN PLUS (RC) | SN PLUS (RC) | SN PLUS (RC) | | SN PLUS (RC) | |
| ILSAC GF-6A | ILSAC GF-6A | ILSAC GF-6A | ILSAC GF-6A | | ILSAC GF-6A | |
| DEXOS1 GEN2 | DEXOS1 GEN2 | DEXOS1 GEN2 | DEXOS1 GEN2 | | | |

Pace NEO Mineral Series

Synthetic-blend and mineral motor oils helps provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going. Helps protect against rust, corrosion, startup wear, varnish build-up.

API SP



1L, 4L, 5L, 20L, 208L



| Performance Levels: | |
|---------------------|--------|
| 15W-40 | 20W-50 |
| SP | SP |

Pace Pro Synthetic Series

Full synthetic motor oils designed with a proprietary cleaning booster to provide ultimate protection that prolongs the peak performance and efficiency of your engine, especially under harsh stop-and-go driving conditions, extreme temperatures and heavy loads.

API SN



1L, 4L, 5L, 20L, 208L



| Performance Levels: | | | | | | |
|---------------------|-------------|-------|-------------|-------------|-------------|-------------|
| 0W-20 | 0W-30 | 5W-20 | 5W-30 | 5W-40 | 10W-30 | 10W-40 |
| SN | SL/CF | SN | SN/CF | SN/CF | SN/CF | SN/CF |
| A5/B5 | A3/B4 | A5/B5 | A3/B4 | A3/B4 | A3/B4 | A3/B4 |
| | 229.5/229.3 | | 229.5/229.3 | 229.5/229.3 | 229.5/229.3 | 229.5/229.3 |
| | BMW LL-01 | | BMW LL-01 | BMW LL-01 | | |

Pace Pro Mineral Series

Pace Pro mineral oil ensures your engine runs smoothly and efficiently, extending its life and enhancing its overall performance. Perfect for all-season use, this advanced formulation delivers exceptional wear resistance, oxidation stability, and sludge control.

Performance Levels:

15W-40

20W-50

| | |
|-----------|-----------|
| SN/CF | SN/CF |
| A3/B4 | A3/B4 |
| 229.1 | 229.1 |
| VW 505 00 | VW 505 00 |

1L, 4L, 5L, 20L, 208L



API SN



Pace X Synthetic Series

Pace X are advanced technology fuel-efficient lubricant crafted from 100% synthetic technology, tailored for gasoline, CNG, and diesel fueled engines. These oils incorporate anti-wear protection, as well as protection against sludge and deposit formation.

Performance Levels:

5W-20

5W-30

5W-40

10W-30

10W-40

| | | | | |
|-----------------|-----------------|-----------------|-----------------|-----------------|
| SM/CF | SM/CF | SM/CF | SM/CF | SM/CF |
| A1/B1 | A3/B3 | A3/B3 | A3/B3 | A3/B3 |
| 229.1 | 229.1 | 229.1 | 229.1 | 229.1 |
| 505 01 / 505 00 | 505 01 / 505 00 | 505 01 / 505 00 | 505 01 / 505 00 | 505 01 / 505 00 |

1L, 4L, 5L, 20L, 208L



API SM



Pace X Mineral Series

Mineral lubricants formulated from premium quality base stocks combined with modern performance additives to give your engine the protection and the performance you expect under a wide variety of operating conditions.

Performance Levels:

15W-40

20W-50

| | |
|-------|-------|
| SM/CF | SM/CF |
| A3/B3 | A3/B3 |

1L, 4L, 5L, 20L, 208L



API SM



Pace III Synthetic Series

Synthetic motor oils formulated for use in passenger cars with metallic detergent and ash less dispersant additive system in these lubricants help prevent engine failure, even under severe operating conditions, by providing superior control of ring belt and piston skirt deposits. These oils help extend engine life.

Performance Levels:

1L, 4L, 5L, 20L, 208L

| 5W-30 | 5W-40 | 10W-30 | 10W-40 |
|-----------------|-----------------|-----------------|-----------------|
| SL/CF | SL/CF | SL/CF | SL/CF |
| A3/B3 | A3/B3 | A3/B3 | A3/B3 |
| | 229.3 | | 229.3 |
| 501 01 / 505 00 | 501 01 / 505 00 | 501 01 / 505 00 | 501 01 / 505 00 |

API SL



Pace III Mineral Series

Multi-grade gasoline engine oils formulated from selected base fluids for use in passenger car and light truck engines requiring API SL or lower performance lubricants. These lubricant helps to remove sludge from dirty engines. High viscosity properties in these oils help reduce leaks in older, high-mileage engines.

Performance Levels:

1L, 4L, 5L, 20L, 208L

| 15W-40 | 20W-50 |
|-----------------|-----------------|
| SL/CF | SL/CF |
| A3/B3 | A3/B3 |
| RN 0700 / 0710 | RN 0700 / 0710 |
| 501 00 / 505 00 | 501 00 / 505 00 |

API SL



Pace II Synthetic Series

Synthetic lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

Performance Levels:

1L, 4L, 5L, 20L, 208L

| 5W-30 | 5W-40 | 10W-30 | 10W-40 |
|--------------|------------|--------|--------|
| SJ/CF | SJ/CF | SJ/CF | SJ/CF |
| A1/B1 | A3/B3 | | |
| ILSAC GF-2 | ILSAC GF-2 | | |
| 913A / 9913B | | | |

API SJ



Pace II Mineral Series

Multi-grade mineral lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

Performance Levels:

15W-40

20W-50

SJ/CF

SJ/CF

1L, 4L, 5L, 20L, 208L



API SJ



Pace I Mineral Series

Mineral lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

Performance Levels:

15W-40

20W-50

SG/CF

SG/CF

1L, 4L, 5L, 20L, 208L



API SG



Pace Mineral Series

Mineral lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge.

Performance Levels:

15W-40

20W-50

SF/CD

SF/CD

1L, 4L, 5L, 20L, 208L




API SF



Long live your engine

NEXLUB

Engine Oils for Diesel Fueled Engine



**Provide Protection
for Modern
Low-Emission
Engines, and offer
Extended Service
Intervals**

Robusta NEO Synthetic Series API CK-4

Heavy-duty, long drain and mixed-fleet lubricants with low ash technology. These oils are designed for on-road vehicles meeting Euro VI and offroad vehicles meeting EU stage IIIA, IIIB, IV and US Tier 4 emission standards. The exceptional low temperature fluidity and pumpability, ensures maximum engine wear performance and supports longer engine life.



1L, 4L, 5L, 20L, 208L



| Performance Levels: | | | | | |
|---------------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| 0W-30 | 0W-40 | 5W-30 | 5W-40 | 10W-30 | 10W-40 |
| CK-4/SN | CK-4/SN | CK-4/SN | CK-4/SN | CK-4/SN | CK-4/SN |
| E6/E7/E9 | E6/E7/E9 | E6/E7/E9 | E6/E7/E9 | E6/E7/E9 | E6/E7/E9 |
| Volvo VDS 4.5 | Volvo VDS 4.5 | Volvo VDS 4.5 | Volvo VDS 4.5 | Volvo VDS 4.5 | Volvo VDS 4.5 |
| Low Ash / LDF-4 | Low Ash / LDF-4 | Low Ash / LDF-4 | Low Ash / LDF-4 | Low Ash / LDF-4 | Low Ash / LDF-4 |

Robusta NEO Mineral Series API CK-4

Heavy-duty, long drain and mixed-fleet lubricants with low ash technology. These oils are designed for on-road vehicles meeting Euro VI and offroad vehicles meeting EU stage IIIA, IIIB, IV and US Tier 4 emission standards. The exceptional low temperature fluidity and pumpability, ensures maximum engine wear performance and supports longer engine life.



1L, 4L, 5L, 20L, 208L



| Performance Levels: | |
|---------------------|-----------------|
| 15W-40 | 20W-50 |
| CK-4/SN | CK-4/SN |
| E6/E7/E9 | E6/E7/E9 |
| Volvo VDS 4.5 | Volvo VDS 4.5 |
| Low Ash / LDF-4 | Low Ash / LDF-4 |

Robusta XI Synthetic Series API CJ-4

Synthetic diesel engines oils providing heavy-duty, long drain performance in modern low emission engines, including those with Exhaust Gas Recirculation (EGR), After-Treatment Systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's). These oils help fight piston deposits, and provide excellent protection engine wear due to soot formation.



1L, 4L, 5L, 20L, 208L



| Performance Levels: | | | | | |
|---------------------|---------------|---------------|---------------|---------------|---------------|
| 0W-30 | 0W-40 | 5W-30 | 5W-40 | 10W-30 | 10W-40 |
| CJ-4/SN | CJ-4/SN | CJ-4/SN | CJ-4/SN | CJ-4/SN | CJ-4/SN |
| ACEA E9 | ACEA E9 | ACEA E9 | ACEA E9 | ACEA E9 | ACEA E9 |
| Volvo VDS 4 | Volvo VDS 4 | Volvo VDS 4 | Volvo VDS 4 | Volvo VDS 4 | Volvo VDS 4 |
| Renault RLD-3 | Renault RLD-3 | Renault RLD-3 | Renault RLD-3 | Renault RLD-3 | Renault RLD-3 |

Robusta XI Mineral Series

Mineral diesel engine oils providing heavy-duty, long drain performance in modern low emission engines, including those with Exhaust Gas Recirculation (EGR), After-Treatment Systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's). These oils help fight piston deposits, and provide excellent protection engine wear due to soot formation.

Performance Levels:

15W-40 **20W-50**

| | |
|---------------|---------------|
| CJ-4/SN | CJ-4/SN |
| ACEA E9 | ACEA E9 |
| Volvo VDS 4 | Volvo VDS 4 |
| Renault RLD-3 | Renault RLD-3 |

1L, 4L, 5L, 20L, 208L



API CJ-4



Robusta X Synthetic Series

Robusta X synthetic oils are premium performance stable, stay in grade heavy duty diesel engine oils formulated for Euro I, II, III, IV and V diesel engines. Help deliver long drain performance while protecting against soot, wear and under severe operating conditions. Delivers excellent performance in modern low emission engines, as well as older, well-maintained engines.

Performance Levels:

0W-30 **0W-40** **5W-30** **5W-40** **10W-30** **10W-40**

| | | | | | |
|-------------|-------------|-------------|-------------|-------------|-------------|
| CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL |
| ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 |
| Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 |
| MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 |

1L, 4L, 5L, 20L, 208L



API CI-4



Robusta X Mineral Series

Robusta X mineral oils are premium performance stable, stay in grade heavy duty diesel engine oils formulated for Euro I, II, III, IV and V diesel engines. Help deliver long drain performance while protecting against soot, wear and under severe operating conditions. Delivers excellent performance in modern low emission engines, as well as older, well-maintained engines.

Performance Levels:

15W-40 **20W-50**

| | |
|-------------|-------------|
| CI-4/SL | CI-4/SL |
| ACEA E7 | ACEA E7 |
| Volvo VDS 3 | Volvo VDS 3 |
| MAN M3275-1 | MAN M3275-1 |

1L, 4L, 5L, 20L, 208L



API CI-4



Robusta XI Mineral Series

Mineral diesel engine oils providing heavy-duty, long drain performance in modern low emission engines, including those with Exhaust Gas Recirculation (EGR), After-Treatment Systems with Diesel Particulate Filters (DPF's) and Diesel Oxidation Catalysts (DOC's). These oils help fight piston deposits, and provide excellent protection engine wear due to soot formation.

Performance Levels:

15W-40 20W-50

| | |
|---------------|---------------|
| CJ-4/SN | CJ-4/SN |
| ACEA E9 | ACEA E9 |
| Volvo VDS 4 | Volvo VDS 4 |
| Renault RLD-3 | Renault RLD-3 |

1L, 4L, 5L, 20L, 208L



API CJ-4



Robusta X Synthetic Series

Robusta X synthetic oils are premium performance stable, stay in grade heavy duty diesel engine oils formulated for Euro I, II, III, IV and V diesel engines. Help deliver long drain performance while protecting against soot, wear and under severe operating conditions. Delivers excellent performance in modern low emission engines, as well as older, well-maintained engines.

Performance Levels:

0W-30 0W-40 5W-30 5W-40 10W-30 10W-40

| | | | | | |
|-------------|-------------|-------------|-------------|-------------|-------------|
| CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL | CI-4/SL |
| ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 |
| Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 | Volvo VDS 3 |
| MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 | MAN M3275-1 |

1L, 4L, 5L, 20L, 208L



API CI-4



Robusta X Mineral Series

Robusta X mineral oils are premium performance stable, stay in grade heavy duty diesel engine oils formulated for Euro I, II, III, IV and V diesel engines. Help deliver long drain performance while protecting against soot, wear and under severe operating conditions. Delivers excellent performance in modern low emission engines, as well as older, well-maintained engines.

Performance Levels:

15W-40 20W-50

| | |
|-------------|-------------|
| CI-4/SL | CI-4/SL |
| ACEA E7 | ACEA E7 |
| Volvo VDS 3 | Volvo VDS 3 |
| MAN M3275-1 | MAN M3275-1 |

1L, 4L, 5L, 20L, 208L



API CI-4



Robusta X7 Synthetic Series

API CH-4

Synthetic motor oils formulated for use in passenger cars with metallic detergent and ash less dispersant additive system in these lubricants help prevent engine failure, even under severe operating conditions, by providing superior control of ring belt and piston skirt deposits. These oils help extend engine life.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| 0W-30 | 0W-40 | 5W-30 | 5W-40 | 10W-30 | 10W-40 |
|-------------|-------------|-------------|-------------|-------------|-------------|
| CH-4/SJ | CH-4/SJ | CH-4/SJ | CH-4/SJ | CH-4/SJ | CH-4/SJ |
| ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 | ACEA E7 |
| Volvo VDS 2 | Volvo VDS 2 | Volvo VDS 2 | Volvo VDS 2 | Volvo VDS 2 | Volvo VDS 2 |
| MAN M3275 | MAN M3275 | MAN M3275 | MAN M3275 | MAN M3275 | MAN M3275 |

Robusta X7 Mineral Series

API CH-4

Multi-grade gasoline engine oils formulated from selected base fluids for use in passenger car and light truck engines requiring API SL or lower performance lubricants. These lubricant helps to remove sludge from dirty engines. High viscosity properties in these oils help reduce leaks in older, high-mileage engines.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| 15W-40 | 20W-50 |
|-------------|-------------|
| CH-4/SJ | CH-4/SJ |
| ACEA E7 | ACEA E7 |
| Volvo VDS 2 | Volvo VDS 2 |
| MAN M3275 | MAN M3275 |

Robusta X5 Synthetic Series

API CG-4

These engines oils are designed for severe duty, high-speed, four-stroke diesel engines used in both on-highway and off-highway applications. These oils provide effective control of high-temperature piston deposits, wear, corrosion, foaming, oxidation stability and soot accumulation.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| 10W-30 | 10W-40 |
|------------|------------|
| CG-4/SJ | CG-4/SJ |
| ACEA A3/B4 | ACEA A3/B4 |
| Volvo VDS | Volvo VDS |
| MAN M3275 | MAN M3275 |

Robusta X5 Mineral Series

These engines oils are designed for severe duty, high-speed, four-stroke diesel engines used in both on-highway and off-highway applications. These oils provide effective control of high-temperature piston deposits, wear, corrosion, foaming, oxidation stability and soot accumulation.

Performance Levels:

10W-30 10W-40

| | |
|------------|------------|
| CG-4/SJ | CG-4/SJ |
| ACEA A3/B4 | ACEA A3/B4 |
| Volvo VDS | Volvo VDS |
| MAN M3275 | MAN M3275 |

1L, 4L, 5L, 20L, 208L



API CG-4



Robusta X3 Mineral Series

Mineral lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge in the engines operating in all driving conditions on highways and in the city.

Performance Levels:

10W-30 10W-40

| | |
|------------|------------|
| CF-4/SJ | CF-4/SJ |
| ACEA A3/B3 | ACEA A3/B3 |
| Volvo VDS | Volvo VDS |
| MAN M3275 | MAN M3275 |

1L, 4L, 5L, 20L, 208L



API CF-4



Robusta X3 Mineral Series

Mineral lubricants formulated with high performance base stocks and premium additive technology which helps deliver outstanding engine protection and prevents the build-up of deposits and sludge.

Performance Levels:

15W-40 20W-50

| | |
|------------|------------|
| CF-4/SJ | CF-4/SJ |
| ACEA A3/B3 | ACEA A3/B3 |
| Volvo VDS | Volvo VDS |
| MAN M3275 | MAN M3275 |

1L, 4L, 5L, 20L, 208L



API CF-4



Diesel Engine Oils

Robusta X2 Mineral Series

Mineral diesel engine oils designed to provide good protection against rust and corrosion, thermal and oxidation stability. These oils help control sludge build-up and deposits; hence they prolongs equipment life and reduces maintenance costs.

API CF



1L, 4L, 5L, 20L, 208L



| Performance Levels: | |
|---------------------|--------------|
| 15W-40 | 20W-50 |
| CF/SF | CF/SF |
| ACEA A3/B3 | ACEA A3/B3 |
| MIL-L-2104-E | MIL-L-2104-E |
| MAN M270 | MAN M270 |

Robusta X1 Mineral Series

Mineral diesel engine oils designed to provide good protection against rust and corrosion, thermal and oxidation stability. These oils help control sludge build-up and deposits; hence they prolongs equipment life and reduces maintenance costs.

API CD



1L, 4L, 5L, 20L, 208L




| Performance Levels: | |
|---------------------|-------------|
| 15W-40 | 20W-50 |
| CD/SF | CD/SF |
| MIL-L-2104D | MIL-L-2104D |
| CAT TO-2 | CAT TO-2 |

Long live your engine

NEXLUB

Motorcycle Oils



**Premium Quality
Engine
Lubricants for
Motorcycles
and Scooters**

Zoom PRO Series

Premium performance multigrade fluids specifically designed for use in four stroke gasoline motorcycle engines, clutches and gearboxes. The anti-friction propertise of these formulations are proven to increase acceleration compared to conventional motorcycle oils. These oils protect the engine, clutch, gears and allows the best functionality of these three critical areas of the motorcycle.

Performance Levels:

| 10W-30 | 10W-40 | 15W-40 | 20W-50 |
|----------|----------|----------|----------|
| API SL | API SL | API SL | API SL |
| JASO MA2 | JASO MA2 | JASO MA2 | JASO MA2 |
| JASO MA | JASO MA | JASO MA | JASO MA |

1L 

API SL



Zoom X7 Series

Motor oil for four-stroke engines of motorcycles, scooters and mopeds. These lubricants are blended by using high-quality base oils and the balanced additive system of quality additive manufacturers. These oils have improved detergency, antiwear, anti-foam properties and offers high resistance to oxidation and corrosion.

Performance Levels:

| 10W-30 | 10W-40 | 15W-40 | 20W-50 |
|---------|---------|---------|---------|
| API SJ | API SJ | API SJ | API SJ |
| JASO MA | JASO MA | JASO MA | JASO MA |

1L 

API SJ



Zoom X5 Series

Motor oil for four-stroke engines of motorcycles, scooters and mopeds. These lubricants are blended by using high-quality base oils and the balanced additive system of quality additive manufacturers. These oils have improved detergency, antiwear, anti-foam properties and offers high resistance to oxidation and corrosion.

Performance Levels:

| 10W-30 | 10W-40 | 15W-40 | 20W-50 |
|---------|---------|---------|---------|
| API SG | API SG | API SG | API SG |
| JASO MA | JASO MA | JASO MA | JASO MA |

1L 

API SG



Gorun X9 Scooter Oil

NEXLUB Gorun X9 Scooter Oils - are high 4-stroke engine lubricant, proven in the streets for urban riders who demand a strong and reliable oil for their trusted scooters. This lubricating oil serves to treat and reduce friction as well as provide protection for motorcycle engines. JASO MB lubricant ensures optimal engine performance and fuel economy on all scooters without a wet clutch.

Performance Levels:

| 10W-30 | 10W-40 | 15W-40 | 20W-50 |
|---------|---------|---------|---------|
| API SL | API SL | API SL | API SL |
| JASO MB | JASO MB | JASO MB | JASO MB |

1L 

API SL



Zoom 2T

NEXLUB Zoom 2T Motorcycle Oils - are general purpose oils for air and water cooled 2-cycle engines. These oils are formulated to provide excellent lubrication and deposit control in a wide range of applications. These oil help keep the engine clean of deposits and will also protect the pistons from scuffing and preignition problems.

Performance Levels:

| SAE 30 | SAE 20 |
|---------|---------|
| API TC | API TC |
| JASO FD | JASO FD |
| ISO EGD | ISO EGD |

1L 

API TC



Long live your engine

NEXLUB

Motor Oils for CNG Fueled Engine



**Helps Provide
Full Engine
Performance
Efficiency and
Resilience**

Transport X5 Mineral

NEXLUB Transport X5 Engine Oils - are performance proven CNG engine lubricant designed to provide faster and cleaner engine protection to make sure of longer engine life. It is designed for use in gas fueled engines in passenger cars and light commercial vehicles. It has special additive system which resists wear under all operating conditions by forming a protective layer on contact surfaces.

Performance Levels:

20W-50 20W-40

| | |
|--------|--------|
| API SM | API SM |
| API SL | API SL |
| API SJ | API SJ |
| API SG | API SG |

1L, 4L, 5L, 20L, 208L



API SM



Transport X3Mineral

NEXLUB Transport X3 Engine Oils - are heavy duty mineral base oil based lubricant formulated specifically for spark ignited CNG and LNG fueled truck, bus engines and small to medium size CNG generators. It provides excellent performance in the challenging operating environment presented by CNG (Compressed Natural Gas) and LNG (Liquefied Natural Gas) and offers extended drain interval capability.

Performance Levels:

15W-40 20W-50 10W-30

| | | |
|------------|------------|------------|
| API CF | API CF | API CF |
| CES 20074 | CES 20074 | CES 20074 |
| DDC 93K216 | DDC 93K216 | DDC 93K216 |

1L, 4L, 5L, 20L, 208L




API SM



Long live your engine

NEXLUB

Transmission Fluids



**Wide Range of
Transmission
Fluids Suitable
for use in a wide
range of vehicle
makes & models**

Tronso +4

NEXLUB Tronso ATF+4 transmission fluids are formulated with high purity synthetic base stocks. This transmission fluid is the recommended fluid for use in FCA Group (formerly known as Chrysler Group) automatic transmissions. Designed to maintain its viscosity through excellent oxidation stability and use of long lasting viscosity modifiers. Tronso ATF+4 is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Chrysler ATF+4, ATF+3 or ATF+2 type fluids.

Performance Levels:

- Chrysler ATF+4® Requirements
- Chrysler MS-9602



Tronso Multi ATF

NEXLUB Tronso Multi transmission fluid is a premium fully synthetic lubricant formulated from selected high-quality synthetic base oils combined with an advanced additive system designed to meet the service fill needs of the broadest range of automatic transmissions in vehicles from European, American and Asian car builder. This transmission fluid provides consistent all-weather smooth shifting and lubrication protection of the transmission components to help extend transmission service life and provide a comfortable driving experience.

Performance Levels:

Acura ATF Z1 (except CVTs), Daimler ATF +3, ATF +4, Fiat 9.55550-AV1, 9.55550-AV2, 9.55550-AV4
Audi (VAG) Tip-tronic, G 052 025-A2, G 052 162 A1 / A2 / A6, G 052 990 A2, G 055 025 A2, G 055 005 A1 / A2 / A6
BMW LT 71141, LA2634, ETL7045E, ETL8072B, Voith G607 (H55.6335XX), Allison C4, TES-295
Chrysler MS 7176, MS 7176D, MS 7176E, MS 9602, ATF+, ATF+2, ATF +3, ATF +4
Citroën Z 000169756, # 9730 AC, #9735-EJ, JWS 3309, ZF TE-ML 03D / 04D / 09 / 14A / 14B / 16L / 17C
Fiat 9.55550-AV1, 9.55550-AV2, 9.55550-AV4, Ford MERCON, MERCON V, MERCON SP
General Motors GM DEXRON III G, III H, GM DEXRON II D, II E
Honda ATF Z1 (except CVTs), # 082000-9001, ATF DW-1 (except CVTs)
Hyundai ReD1, SP II, SP III, ATF 9638, # 040000C90SG
Infiniti ATF FMS, MATIC S, MATIC D, MATIC-J, MATIC K, MATIC W
Isuzu ATF Z1 (except CVTs), H50235, SCS, Jaguar M1375.4, JLM 20237, JLM 20238, Jaguar Fluid 8432
Kia ATF SP-III, ATF SP-3, ReD1, # UM040 CH020, Land Rover M1375.4, # TYK500050, STC 4863
Lexus ATF WS, ATF Type T-IV, JWS 3324, NWS 9638
MB 236.3, MB 236.5, MB 236.7, MB 236.9, MB 236.10, MB 236.11, MB 236.12, MB 236.14, MB 236.15, A0019892203
Mitsubishi Diamond (USA) / Dia Queen PSF, ATF-PA, ATF-J2, ATF-J3, SP II, SP III, PSF 3, AYC Fluid
Nissan ATF FMS, MATIC S, MATIC D, MATIC J, MATIC K, MATIC W, ATF D3M
Peugeot Z 000169756, # 9730 AC, #9735-EJ, JWS 3309, Porsche # 999.917.547.00 (A2), # 043 205 28
Renault DPO, Elfmatic J6, Renaultmatic D2, Renaultmatic D3
Subaru # KO410Y0700, ATF HP, SKU: SOA868V9241, Suzuki JWS 3314 / 3317 / 2384K
Toyota ATF DIII, ATF WS, ATF Type T, Type T-II, Type T-III, Type T-IV, JWS 2312D, JWS 3309, JWS 3324, LF
Volvo # 97342, # 1161521, # 1161540, # 97340, Aisin Warner JWS 3309, JWS 2312D, CLIP, FF ATF, AW-F21
VW (VAG) G 052 025-A2, G 052 162 A1 / A2 / A6, TL 52 162, G 052 990 A2, G 055 025 A2, G 055 005 A1 / A2 / A6



Tronso DCT Fluid

NEXLUB Tronso ATF+4 transmission fluids are formulated with high purity synthetic base stocks. This transmission fluid is the recommended fluid for use in FCA Group (formerly known as Chrysler Group) automatic transmissions. Designed to maintain its viscosity through excellent oxidation stability and use of long lasting viscosity modifiers. Tronso ATF+4 is recommended for use in all transmissions, hydraulic systems, and power steering units manufactured by American, European, Korean, Japanese and other manufactures from around the world specifying Chrysler ATF+4, ATF+3 or ATF+2 type fluids.



1L, 4L, 5L, 20L, 208L



Performance Levels:

BMW 83 22 0 306 816, 83 22 0 397 244, 83 22 0 440 214, 83 22 2 147 477, 83 22 2 148 578, 83 22 2 148 579
BMW 83 22 2 167 666, 83 22 2 409 710, DCTF-1, DKG, DTF 1, MTF- LT-3, MTF-LT-5
Audi G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527, G 052 529
Audi G 052 726, G 052 798, G 055 529, G 070 726, S-tronic, TL 52 182
CITROËN 1618078480, 9730 A8, 9734 S2, DCS, JWS 2271
DS (CAPSA) 1618078480, 9730 A8, 9734 S2, DCS, JWS 2271
FIAT 9.55550-DA11, 9.55550-MZ2, 9.55550-MZ6, Tutela Transmission Gearforce
Ford 1 490 761, 1 490 763, POWERSHIFT, WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1, WSS-M2C936-A
Honda MTF-III, Jaguar Landrover PENTOSIN FFL-3, Lexus #lf, #0888, 0888581001, JWS 2271, LF, LV 75W MT
MB 236.24, SLS A 001 989 86 03, Mitsubishi Diamond Queen SSTF-1, Nissan DCT Fluid, GR6, LV MT-1
PEUGEOT 1618078480, 9730 A8, 9734 S2, JWS 2271, Renault BOT 450, DC4, EDC
Porsche PENTOSIN FFL-3, 000 043 20, 000 043 305 63, 043 207 29
Porsche 043 207 30, 999 917 080 00, 999 917 546 00, PDK, TF 0870
SEAT G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527
SEAT G 052 529, G 052 726, G 052 798, G 055 529, G 070 726, TL 52 182
SKODA G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527
SKODA G 052 529, G 052 726, G 052 798, G 055 529, G 070 726, TL 52 182
Suzuki 99000-22B27-036, Toyota 0888581001, JWS 2271, LF, LV 75W MT, Volvo 1161520-7, 1161838, BOT 341
VW DSG, G 009 317, G 052 171, G 052 178, G 052 182, G 052 512, G 052 527
VW G 052 529, G 052 726, G 052 798, G 055 529, G 070 726, TL 52 182

Tronso Fluid

NEXLUB Tronso is a multi-purpose transmission fluid, designed for use in automatic gearboxes, where GM Type A Suffix A is quoted. Its special formula enables very smooth operation of torque converters and fluid couplings of automatic transmissions.



1L, 4L, 5L, 20L, 208L



Performance Levels:

- GM Type A Suffix A

Tranzo CVT Fluid

NEXLUB Tranzo CVT fluid is a premium full synthetic lubricant formulated for use in a wide variety of North American, European, and Asian vehicles equipped with continuously variable transmissions (CVT). A well-balanced fluid that provides exceptional metal-to-metal frictional properties to help prevent belt and chain slipping and help extend transmission life. It provides superior performance for antishudder durability and reduced noise, vibration and harshness.



1L, 4L, 5L, 20L, 208L



Performance Levels:

BMW 83 22 0 136 376, 83 22 0 429 154, EZL 799, EZL 799 A
Audi G 052 180, G 052 516, Multitronic, TL 52 116, TL 52 180, TL 52 516
CITROËN AMMIX CVTF DFE, AMMIX CVT Fluid DC, AMMIX CVT, Fluid DFE, CVTF 3320, CVT Fluid DFC, Fluid TC
Chrysler CVTF+4, NS-2
Chery CVT
Daihatsu 1 490 761, 1 490 763, POWERSHIFT, WSS-M2C200-D2, WSS-M2C200-D3, WSS-M2C200-E1, WSS-M2C936-A
Dodge 05191184AA, CVTF+4, NS-2
DS (CAPSA) 9735 EF, Elfmatic CVT, Elfmatic CVT MV
FIAT Tutela Car CVT N.G
Ford CVT23, CVT30, MERCON C, WSS-M2C928-A, WSS- M2C933-A, XT-7QCFT
Honda 1940713, 1940714, CVTF I-Green2, DEX-CVT, HP CVTF 95529854, VT40
Hyundai CVT-1, Genuine CVTF, SP-CVT 1, SP III (CVT models only)
Infiniti NS-1, NS-2, NS-3
Jeep 05191184AA, CVTF+4, NS-2, VTF
Kia CVT-1, SP-CVT 1, SP III (CVT models only)
Lexus CVTF 3320, CVT FE, Fluid FE, Fluid TC
Lifan CVT
Mazda CVTF 3320, JWS 3320
MB A 001 989 46 03, MB 236.20
MG EM-CVTF
Mini 83 22 0 136 376, 83 22 0 429 154, COOPER EZL 799 A, EZL 799, ZF CVT V1
Mitsubishi CVTF ECO J4, Dia Queen CVTF-J1 (MMC Diaqueen CVT Fluid J1), Dia Queen CVTF-J4,
Dia Queen CVTF-J4+ (MMC Diaqueen CVT Fluid J4 and J4+), MZ313973, SP III (CVT models only)
Nissan 999MP-NS200P, KTF-1, N-CVT, NS-1, NS-2, NS-2V, NS-3
OPEL 7-speed CVT, HP CVTF 95529854, VT40
PEUGEOT 9735 EF, Elfmatic CVT, Elfmatic CVT MV
Renault CVT CK/SK/FK, Elfmatic CVT, Elfmatic CVT MV
Rover EM-CVTF, Unipart Transmatic ATF
Saturn 22688912, DEX-CVT
Seat G 052 180, G 052 516
SUBARU CV30, CVT III Fluid, CVT TR580, CVT TR690, ECVT, High Torque CVT, High Torque CVTF-LV, iCVTF
SUBARU i-CVTF FG, K0421Y0700, K0425Y0710, K0425Y0711, Linear-tronic chain CVT 3 Fluid,
Lineartronic chain CVT and CVT II Fluid, Lineartronic CVTF, Lineartronic High Torque (HT) CVT Fluid
Lineartronic II, NS-2, SOA748V0300
Suzuki CVTF 3320, CVTF FE, TC
Toyota 7-speed CVT, HP CVTF 95529854, VT40
VAUXHALL CVTF 4959
Volvo G 052 180, G 052 516
VW RDCF01, RDCF02, CVTs
ZOTYE 22688912, DEX-CVT

Tranzo NEO Fluid

NEXLUB Tranzo NEO fluid is a synthetic transmission fluid with a low viscosity formulation, superior friction control and dependable protection for use in most 6+ speed automatic transmissions recommended for use in passenger cars and light truck automatic transmissions that require a GM Dexron VI or earlier generation fluid.



1L, 4L, 5L, 20L, 208L



Performance Levels:

GENERAL MOTORS DEXRON II/III/IIIIH/VI
CHRYSLER M1375.4, MERCON LV, VOITH 55.6635, CITROEN P/N PR 9980, JWS 3309, JWS 3324, T-IV, AW-1, NWS 9638
AS 68RC (T IV), AUDI/VW G-052-162-A1/A2, BMW ETL-7045, 7045E, LA2634, ETL-8072B, 81 22 9 400 275
BMW P/N 833227542290, FIAT (ALL VEHICLES) TYPO T-IV, HONDA ACURA Z-1 PREMIUM, HONDAMATIC S
HYUNDAI / KIA SP IV, HYUNDAI SPH-IV, ISUZU BESCO ATF II, ATF III, JAGUAR ATF 3403 M115, JLM 20238
LT 71141, MAZDA ATF M III, MITSUBISHI DIAMOND SP-IV, MB ZF 4 HP20, 236.1/5/6/7/8/9/236.41
PEUGEOT ZF 4 HP20, PORSCHE ATF 3403-M115, SUBARU ATF, ATF HP, VOLVO T-IV, VOLVO 97340
TOYOTA TYPE T-III, T-IV, TOYOTA WS, TOYOTA P/N 08886-02305/08886-81015
ZF 5HP 18FL/19FL/24A, ZF 5HP 30, ZF TE-ML 09, SAAB P/N 93165147

Tranzo II Fluid

NEXLUB Tranzo II fluid is an automatic transmission fluid with excellent aging stability. Prevents the build-up of troublesome deposits. For vehicles with proven transmission technology. Maximum protection against wear and good friction characteristics. Good seal compatibility. Provides optimum protection against corrosion. For automatic transmissions, manual transmissions, steering systems, hydraulic systems and auxiliary drives in both passenger cars and commercial vehicles. Usage according to the prescribed specifications from the unit or vehicle and transmission manufacturers.



1L, 4L, 5L, 20L, 208L



Performance Levels:

GENERAL MOTORS DEXRON IID
CHRYSLER +3, VOITH H55.6335
VOLVO 97355, FORD ESP-M2C138-CJ / ESP-M2C166-H
ALLISON TES 389, ALLISON TES 228 (C4)
MB 236.1/236.5/236.7, ZF TE-ML-04D / 09 / 11A / 14A
BMW 81 22 9 400 272, BMW 81 22 9 400 275, BMW 81 22 9 407 738
TOYOTA TII/2, MAN 339 TYPE L2/V1,
OPEL 19 40 700 / 19 40 707
MITSUBISHI SP / SP2/ BTR
CAT TO-2

Tranzo III Fluid

NEXLUB Tranzo III fluid is a passenger car and light truck automatic transmission fluid for most pre-2006 automatic transmissions built by General Motors, Ford Motor Company and other makes requiring a high-performance, multi-purpose, power transmission fluid. It is formulated with premium, severely hydroprocessed base stocks and additives that helps provide oxidation and thermal stability, friction control, load-carrying ability, corrosion and wear protection. It helps protect against the formation of deposits, sludge, varnish, and foam. Tranzo III fluid helps provide outstanding durability.



1L, 4L, 5L, 20L, 208L




Performance Levels:

GENERAL MOTORS DEXRON III G, III F, III H
ALLISON TES-389, ALLISON C4
MAN 339 TYPE V1/Z1/V2/Z2
MB 236.1/236.10/236.5/236.6/236.9
HONDA ATF-Z1 (not for CVT), HONDA ATF DW-1
AISIN WARNER JWS 3309
BMW 83 22 0 403 248, BMW 83 22 2 163 514, BMW 83 22 9 407 765 (LA 2634), BMW 83 22 9 407 807
BMW 7045E (3 Series), BMW ETL-8072B (5 Series), BMW LT71141 (ZF 5 Speed)
HYUNDAI ATF SP-II / SP-III
INFINITI Matic D / J / K
IDEMITSU K17-Jaguar X Type 2001-2005
JATCO ATF 3100 PL085
KIA ATF-SP-II / SP-III
CHRYSLER ATF+3, CHRYSLER ATF+4
LEXUS ATF Type T, LEXUS ATF Type T-II / T-III / T-IV
DAIHATSU ALUMIX ATF MULTI, LT 71141
FORD M, FORD TASA, FORD Mercon V / SP / LV, FORD Mercon ATF Type F, FORD XT-8-QMM5 [FRN5]
MAN 339 F, MAN 339 Z1 / Z2, MAN 339 V1 / V2
MAZDA ATF M-III / M-V
MB 236.1 / 236.2 / 236.3 / 236.5, MB 236.7 / 236.9 / 236.10 / 236.11
MITSUBISHI DIAMOND SP-II / SP-III
MOPAR AS68RC
NISSAN Matic D / J / K
PORSCHE JWS 3309
SUBARU ATF-5 / ATF-HP
SUZUKI 3314 / 3317 / 2384K
SUZUKI ATF OIL / ATF OIL SPECIAL
TOYOTA ATF Type T / T-II / T-III / T-IV
VOLVO 1161621, 97341
VW G 052 025-A2, G 052 162-A1
VW G 052 990-A1, G 052 990-A2
VW G 055 025-A1, G 055 025-A2
VOITH 55.6335.XX (G607)
VOITH 55.6336.3x
VOLVO 97340 / 97341
ZF TE-ML 03D / 04D / 09C
ZF TE-ML 11B / 14A / 14B
ZF TE-ML 16L / 17C

Long live your engine

NEXLUB

Automotive Gear Oils



**Discover Gear Oils
that perform in the
most demanding
of operating
conditions**

Switch NEO Synthetic Series

API GL-5

NEXLUB Switch Neo Gear Oils - are multipurpose lubricants designed to provide acceptable market general gear protection and lubricant life. The sulfur-phosphorus extreme pressure additive technology used in these oils provides good thermal and oxidation stability. These oils are fortified with rust and corrosion inhibitors, foam inhibitors, and pour point depressant.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| 75W-80 | 75W-90 | 85W-90 | 85W-140 | 80W-90 | 80W-140 |
|--------------------|--------------------|--------------------|--------------------|--------------------|--------------------|
| API GL-5 | API GL-5 | API GL-5 | API GL-5 | API GL-5 | API GL-5 |
| MIL-L-2105D | MIL-L-2105D | MIL-L-2105D | MIL-L-2105D | MIL-L-2105D | MIL-L-2105D |
| MAN 342 M-2 | MAN 342 M-2 | MAN 342 M-2 | | MAN 342 M-2 | |
| ZF 12E/16B/17B/21A | ZF 12E/16B/17B/21A | ZF 12E/16C/17B/21A | ZF 12E/16B/16D/21A | ZF 12E/16C/17B/21A | ZF 12E/16B/16D/21A |

Switch NEO Mineral Series

API GL-5

NEXLUB Switch Neo Gear Oils - are multipurpose lubricants designed to provide acceptable market general gear protection and lubricant life. The sulfur-phosphorus extreme pressure additive technology used in these oils provides good thermal and oxidation stability. These oils are fortified with rust and corrosion inhibitors, foam inhibitors, and pour point depressant.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| SAE 140 | SAE 90 |
|-------------|--------------------|
| API GL-5 | API GL-5 |
| MIL-L-2105D | MIL-L-2105D |
| | MAN 342 M-2 |
| ZF 16D | ZF 12E/16B/17B/21A |

Switch Max Synthetic Series

API GL-4

NEXLUB Switch Max Gear Oils - are formulated using paraffinic base stocks and contain a carefully balanced sulfur phosphorus extreme pressure additive package to provide gear protection, good rust and corrosion protection and long lubricant life. Recommended for use in automotive spiral bevel and hypoid differentials, power dividers, oil-lubricated steering axle wheel bearings and transaxles/ transmissions.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| 75W-80 | 75W-90 | 85W-90 | 85W-140 | 80W-90 | 80W-140 |
|-------------|-------------|-------------|-------------|-------------|-------------|
| API GL-4 | API GL-4 | API GL-4 | API GL-4 | API GL-4 | API GL-4 |
| MIL-L-2105B | MIL-L-2105B | MIL-L-2105B | MIL-L-2105B | MIL-L-2105B | MIL-L-2105B |

Swith Max Mineral Series

NEXLUB Switch Max Gear Oils - are formulated using paraffinic base stocks and contain a carefully balanced sulfur phosphorus extreme pressure additive package to provide gear protection, good rust and corrosion protection and long lubricant life. Recommended for use in automotive spiral bevel and hypoid differentials, power dividers, oil-lubricated steering axle wheel bearings and transaxles/ transmissions.

API GL-4

1L, 4L, 5L, 20L, 208L



Performance Levels:

SAE 140

SAE 90

API GL-4

API GL-4

MIL-L-2105B

MIL-L-2105B

Swith Mineral Series

NEXLUB Switch gear oils are rust & oxidation inhibited gear oils that are recommended for many automotive and industrial equipment where the equipment suppliers recommend the use of a straight mineral oil in SAE Viscosity Grades 90 (ISO 220) or 140 (ISO 460). These oils help provide long life for gears and bearings in gear cases where OEM recommends the use of a mineral oil.

API GL-1

1L, 4L, 5L, 20L, 208L



Performance Levels:

SAE 140

SAE 90

API GL-1


API GL-1

Long live your engine

NEXLUB

Antifreeze/ Coolant

Automotive Cooling System



**Premium Quality
Formulations for
Multi-Fleet
Applications**

Chilly 100 Coolant / Antifreeze 100%

NEXLUB Chilly coolant / antifreeze is OAT (Organic Acid Technology) based ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. Chilly coolant/ antifreeze is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.



1L, 4L, 5L, 20L, 208L



Performance Levels:

- BS 6580
- ASTM D3306
- SAE J1034, J1038
- Cummins 90T8-4
- CAT ELC (EC-1)
- Detroit Diesel 7SE298
- GM 1825, 1899M, 6277M
- TMC RP329
- Freightliner 48-22880

Chilly 60 Coolant / Antifreeze 60%

NEXLUB Chilly coolant / antifreeze is OAT (Organic Acid Technology) based ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. Chilly coolant/ antifreeze is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.



1L, 4L, 5L, 20L, 208L



Performance Levels:

- BS 6580
- ASTM D3306
- SAE J1034, J1038
- Cummins 90T8-4
- CAT ELC (EC-1)
- Detroit Diesel 7SE298
- GM 1825, 1899M, 6277M
- TMC RP329
- Freightliner 48-22880

Chilly 50 Coolant / Antifreeze

50%

NEXLUB Chilly coolant / antifreeze is OAT (Organic Acid Technology) based ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. Chilly coolant/ antifreeze is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.



1L, 4L, 5L, 20L, 208L



Performance Levels:

- BS 6580
- ASTM D3306
- SAE J1034, J1038
- Cummins 90T8-4
- CAT ELC (EC-1)
- Detroit Diesel 7SE298
- GM 1825, 1899M, 6277M
- TMC RP329
- Freightliner 48-22880

Chilly 33 Coolant / Antifreeze

33%

NEXLUB Chilly coolant / antifreeze is OAT (Organic Acid Technology) based ready-to-use, phosphate-free, silicate-free, nitrite-free and borate-free, ethylene glycol-based coolant that is designed to provide exceptional wet sleeve liner cavitation and corrosion protection of all cooling system metals. Chilly coolant/ antifreeze is formulated with organic corrosion inhibitors to provide total cooling system protection for on-road and off-road use.



1L, 4L, 5L, 20L, 208L



Performance Levels:

- BS 6580
- ASTM D3306
- SAE J1034, J1038
- Cummins 90T8-4
- CAT ELC (EC-1)
- Detroit Diesel 7SE298
- GM 1825, 1899M, 6277M
- TMC RP329
- Freightliner 48-22880

Long live your engine

NEXLUB

Hydraulic Oils



For mobile and static hydraulic applications of industrial and other equipment.

Liftol AW

NEXLUB Liftol AW hydraulic oils are designed to give excellent hydraulic pump protection. These oils help provide excellent antiwear protection, oxidation and corrosion inhibition, as well as foam and aeration suppression. All grades have excellent demulsibility characteristics. These oils exhibit excellent oxidation resistance which delivers good performance at higher temperatures and extended operating intervals. These oils have a high load carrying capacity and provides good protection against corrosion, foaming, and sludge building.

AW



1L, 4L, 5L, 20L, 208L



Performance Levels:

| VG 15 | VG 22 | VG 32 | VG 37 | VG 46 | VG 68 | VG 100 |
|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|------------------------|
| DIN 51524-2 HLP | DIN 51524-2 HLP | DIN 51524-2 HLP | DIN 51524-2 HLP | DIN 51524-2 HLP | DIN 51524-2 HLP | DIN 51524-2 HLP |
| ASTM D6158-05 HM | ASTM D6158-05 HM | ASTM D6158-05 HM | ASTM D6158-05 HM | ASTM D6158-05 HM | ASTM D6158-05 HM | ASTM D6158-05 HM |
| Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 | Eaton (Vickers) M-2950 |
| Eaton (Vickers) I-286S | Eaton (Vickers) I-286S | Eaton (Vickers) I-286S | Eaton (Vickers) I-286S | Eaton (Vickers) I-286S | Eaton (Vickers) I-286S | Eaton (Vickers) I-286S |
| ISO 11158HM | ISO 11158HM | ISO 11158HM | ISO 11158HM | ISO 11158HM | ISO 11158HM | ISO 11158HM |
| AFNOR NF-E 48-603 | AFNOR NF-E 48-603 | AFNOR NF-E 48-603 | AFNOR NF-E 48-603 | AFNOR NF-E 48-603 | AFNOR NF-E 48-603 | AFNOR NF-E 48-603 |
| DENISON HF-0/1/2 | DENISON HF-0/1/2 | DENISON HF-0/1/2 | DENISON HF-0/1/2 | DENISON HF-0/1/2 | DENISON HF-0/1/2 | DENISON HF-0/1/2 |
| | | Cincinnati P-68 | | Cincinnati P-70 | Cincinnati P-69 | |

Liftol HVLP

NEXLUB Liftol HVLP hydraulic oils are high viscosity index antiwear hydraulic oil. These oils are formulated to have a high viscosity index and a low pour point for use over a wider temperature range than conventional antiwear hydraulic oils. These oils provides excellent wear protection for hydraulic pumps and motors, has excellent oxidation resistance and thermal stability at high temperatures to minimize deposit formation and provide long service life, and protects hydraulic system components against rust and corrosion.

HVLP



1L, 4L, 5L, 20L, 208L



Performance Levels:

| VG 15 | VG 22 | VG 32 | VG 46 | VG 68 | VG 100 | VG 150 |
|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|----------------------------|
| DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP | DIN 51524 Part 3 Type HVLP |

Liftol R&O

NEXLUB Liftol R&O hydraulic oils are is a rust and oxidation (R&O) inhibited, circulating oils developed for use in circulation systems, centrifugal air compressors, geared turbines, lightly loaded enclosed gear drives and many other industrial applications. The good oxidation stability provided by the multi-component inhibitor system resists oil breakdown during exposure to high temperature conditions. The highly refined base stocks and multi-component oxidation inhibitor system resist the formation of harmful sludge and varnish deposits. The rust inhibitor protects components against corrosion.

R&O



1L, 4L, 5L, 20L, 208L



Performance Levels:

| VG 32 | VG 46 | VG 68 | VG 100 | VG 150 | VG 220 |
|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|-------------------------|
| DIN 51517-2 (HL) | DIN 51517-2 (HL) | DIN 51517-2 (HL) | DIN 51517-2 (HL) | DIN 51517-2 (HL) | DIN 51517-2 (HL) |
| DIN 51524-1 | DIN 51524-1 | DIN 51524-1 | DIN 51524-1 | DIN 51524-1 | DIN 51524-1 |
| BS 489 | BS 489 | BS 489 | BS 489 | BS 489 | BS 489 |
| ASTM D4304 TYPE 1 | ASTM D4304 TYPE 1 | ASTM D4304 TYPE 1 | ASTM D4304 TYPE 1 | ASTM D4304 TYPE 1 | ASTM D4304 TYPE 1 |
| GEK 101941A, GEK 46506E | GEK 101941A, GEK 46506E | GEK 101941A, GEK 46506E | GEK 101941A, GEK 46506E | GEK 101941A, GEK 46506E | GEK 101941A, GEK 46506E |
| GEK 27070, GEK 28143A | GEK 27070, GEK 28143A | GEK 27070, GEK 28143A | GEK 27070, GEK 28143A | GEK 27070, GEK 28143A | GEK 27070, GEK 28143A |
| MIL-L-17672D | MIL-L-17672D | MIL-L-17672D | MIL-L-17672D | MIL-L-17672D | MIL-L-17672D |
| US STEEL 126 | US STEEL 126 | US STEEL 126 | US STEEL 126 | US STEEL 126 | US STEEL 126 |

Long live your engine

NEXLUB

Automotive & Industrial Greases



**Wide Range
of Greasing
Solutions**

L9 Lithium EP Grease

EP

Nexlub L9 EP is an extreme pressure lithium soap based grease with high resistance to water washout and protects the lubricated parts against wear and corrosion. Use in lubrication of plain and rolling bearings, operated under high loads and in wet environment. It offers excellent mechanical stability, load carrying capacity, and corrosion protection. This grease offer enhanced water resistance and mechanical stability, which makes this grease a real multipurpose grease.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| Parameters | NLGI 00 | NLGI 0 | NLGI 1 | NLGI 2 | NLGI 3 |
|--------------------------|-------------|-------------|-------------|-------------|-------------|
| Thickener Type | Lithium | Lithium | Lithium | Lithium | Lithium |
| Work Penetration @ 25 °C | 400 - 430 | 355 - 385 | 310 - 340 | 265 - 295 | 220 - 250 |
| Color | Light Brown | Light Brown | Light Brown | Light Brown | Light Brown |
| Operating Temp Range °C | -20 to 130 | -20 to 130 | -20 to 130 | -20 to 130 | -20 to 130 |

L7 Lithium MP Grease

MP

Nextlub L7 MP is multi purpose lithium soap based lubricating greas. This grease contains antioxidants, rust, corrosion inhibitors, and anti-wear additives. This product is recommended for the lubrication of rolling element bearings, electric motor bearings, water pumps, and sealed-for-life bearings. NLGI 1 and NLGI 2 are designed for general industrial lubrication which can be used through centralized lubrication systems operating at normal temperatures.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| Parameters | NLGI 00 | NLGI 0 | NLGI 1 | NLGI 2 | NLGI 3 |
|--------------------------|-------------|-------------|-------------|-------------|-------------|
| Thickener Type | Lithium | Lithium | Lithium | Lithium | Lithium |
| Work Penetration @ 25 °C | 400 - 430 | 355 - 385 | 310 - 340 | 265 - 295 | 220 - 250 |
| Color | Light Brown | Light Brown | Light Brown | Light Brown | Light Brown |
| Operating Temp Range °C | -20 to 130 | -20 to 130 | -20 to 130 | -20 to 130 | -20 to 130 |

C5 Calcium MP Grease

MP

This is a water-resistant calcium-soap thickened lubricating grease of NLGI 2 and NLGI 3 consistency. This is a good quality grease with excellent water resistance and good protection against corrosion. Used in nipples, spring leaves, chain drives, water pump, non-bearing axles, open and semi-open gear systems.



Performance Levels:

1L, 4L, 5L, 20L, 208L



| Parameters | NLGI 1 | NLGI 2 | NLGI 3 |
|--------------------------|-----------|-----------|-----------|
| Thickener Type | Calcium | Calcium | Calcium |
| Work Penetration @ 25 °C | 310 - 340 | 265 - 295 | 220 - 250 |
| Color | Yellow | Yellow | Yellow |
| Operating Temp Range °C | -10 to 60 | -10 to 60 | -10 to 60 |

Long live your engine

NEXLUB

nexlub.com

