BENTSAI B85 Inkjet Printer 4 Inch (100mm) Technical Specification

Operating system:	Linux
Display Screen:	5-inch color LCD capacitive touch screen
	·
External source interface:	USB interface, power interface, optical interface, extensible USB
	interface, extensible conveyor belt synchronizer interface,
	expandable three-color alarm lamp interface
Sensor:	Open cover detection sensor
Communication mode:	Extensible wifi (optional)
Trigger mode:	Hall sensor trigger, photo electric sensor trigger continuous printing
Status display:	Green-ready status, blue-printing status, red light-alarm status
Jet printing content:	text, number, symbol, picture, time, date, variable counter, variable
	QR code (QR code, DM code), variable barcode, variable text, etc.
Jet printing font:	Vector font, dot matrix font
Jet printing accuracy:	300 dpi
Jet printing rows:	A single sprinkler head can have up to 10 rows & up to 40 rows
Nozzle height:	4 nozzles 100 mm
Jet printing distance:	2-5 mm (Distance between nozzle & object)
Jet printing speed:	Fastest 30 m/min
Ink type:	Water based, Solvent, Ink capacity- 42 ml
Ink color:	red, yellow, blue, black, invisible, Green, White, Magenta
Working environment:	0-40°C
Working humidity:	10% - 80% RH Storage capacity- 8 GB
Power:	input- AC 100-245V Output- 9V / 5A
Size:	239mm*182mm*117mm



