

## OVERVIEW



### I6585TP

- Zero gap Bonding technology, low parallax writing and wider viewing angles
- 4mm anti-glare toughened glass with high haze OC for clearer display against ambient light interference
- Light-sensitive brightness adjustment and DC dimming support (de-flashing) for a more eye-protection display
- 4K Ultra HD display ,support full channel 4K UI display
- Front Type C\*1+ USB3.0\*2 + on-board USB3.0\*1, supports switching with channels
- Support for Wireless projection
- ±1mm High precision infrared touch control for smooth writing
- Supports dual pens and dual colour displays for easy multi-person collaboration

Notes: Product visuals are for general reference. The availability and layout of ports may vary across different models.



## Screen Parameters

<b>LCD Size</b>	65"
<b>Type of Panel</b>	IPS/VA
<b>Respond Time</b>	8ms
<b>Visual Ratio</b>	16/9
<b>Max Visual Area</b>	1428.48 (H) ×803.52 (V) mm
<b>Resolution</b>	3840 (H) ×2160 (V)
<b>Pixel pitch</b>	0.372×0.372mm
<b>Frequency</b>	60Hz
<b>Display Colors</b>	1.07B (10bit)
<b>Color saturability</b>	72%
<b>Contrast ration(Typ)</b>	4000:1
<b>Viewing Angle</b>	178°(H/V)
<b>Light source</b>	DLED
<b>Brightness</b>	450cd/m2
<b>Life Span</b>	≥40000hrs

## Audio-video Parameters

<b>Speaker</b>	<b>Soundtrack</b>	2.0
	<b>Power</b>	2×15W
	<b>woofer:</b>	20W (Optional)

## System

<b>System Version</b>	Android 14.0
<b>CPU</b>	Octa-core A55
<b>GPU</b>	Mali-G52MP4
<b>RAM</b>	8 GB
<b>ROM</b>	128 GB



## Touch parameter

<b>Touch specifications</b>	Non-contact infrared sensing technology
<b>Support Systems</b>	Windows/Android/Linux/Mac OS X/Chrome
<b>Touch Points</b>	20 Points Touch
<b>Min.Identifier</b>	2mm
<b>Input mode</b>	Opaque object (finger, pen, etc)
<b>Respond time</b>	≤10ms
<b>Touch depth</b>	±1mm
<b>Writing height</b>	≤3mm
<b>Writing display</b>	Single Stylus pen two-colour
<b>Output coordinates</b>	32767 (W) ×32767(D)

## I/O Interface

<b>HDMI IN</b>	2 (HDMI 2.0)
<b>HDMI OUT</b>	1(Optional)
<b>DP IN</b>	1(Optional)
<b>VGA IN</b>	1
<b>Type C Full Functions</b>	1(Optional)
<b>USB 2.0</b>	1(Android)
<b>USB 3.0</b>	1(Follow)
<b>TOUCH</b>	1
<b>AUDIO IN</b>	1
<b>Line OUT</b>	1
<b>RS232</b>	1
<b>MIC IN</b>	1(Optional)
<b>TF Card</b>	1
<b>LAN IN</b>	1
<b>LAN OUT</b>	1(Optional)

## I/O Interface

<b>USB3.0</b>	2
<b>TOUCH USB</b>	1 (USB 2.0)
<b>HDMI IN</b>	2 (HDMI 2.0)
<b>Type C</b>	1



## Wireless

Bluetooth	Version	2
	Working Frequency	2.4GHz
	Working Distance	0~10m
Wi-Fi	Version	802.11ac/b/g/n/a/ax
	Working Frequency	2.4GHz/5GHz
	Working Distance	0~10m

## Structure

Bare dimension	1488.4×896.6×87.2mm
Packing dimension	1630×220×1050mm
Machine+wall mount thickness	116.5mm
VESA hole site	600×400mm
Wall mounting screw specifications	M8×25mm
Net weight	45 KGS
Gross weight	56 KGS

## Power

Voltage	100-240V~ 50/60Hz 4A
Max. power consumption	280W
Standby power consumption	≤0.5W

## Accessories

Power cord	×1
Stylus pen	×2
Wall mount	×1
Operation manual	×1

The product images in this specification are for illustrative purposes only. The actual product effect (including but not limited to appearance, colour and size) may vary slightly.

