

## OFFICE OF THE PRINCIPAL, ATHMALLIK COLLEGE

At/P.O.-Athmallik Dist: Angul Pin:759125 Ph-(+91)8114868048 Estd:1978 E-mail-id: athmallik.college@gmail.com

No. 35.6 Date .. 24. 04.25

# OFFICE OF THE PRINCIPAL ATHMALLIK COLLEGE, ATHMALLIK Dist-Angul

e-mail id- athmallik.college@gmail.com

### QUOTATION CALL NOTICE

Sealed quotations are invited from different Registered Firms/ Authorized dealers/ Suppliers having valid license DGS & GeM rate contract Registration/TIN/PAN, GST and Income Tax clearance for supply of Desktop Computers, Multifunctional Printers, UPS, LED TV, Wireless Mick with Cameras for virtual meeting along with the requisite documents. The quotation should reached the undersigned on or before May 02,2025 by 5 PM through speed post / Registered Post. The authority reserves the right to accept or reject any or all quotations without assigning any reason thereof.

For more details please visit our official college website: <a href="https://www.athmallikcollege.in">https://www.athmallikcollege.in</a>
For contact-9937890283, 9337066395

S/d-Princippal
Athmallik College
Athmallik

Безжор.	Specification	
Items	Specification	
Cabinet Form Factor	Tower/Micro Tower (15.1 to 26 Litres)	
Chipset Number	Intel H670/Intel® H770 or higher Chipset	
Processor Make	Intel	
Processor	x86 64-bit architecture	
Processor Generation	13 Or higher	
Processor Description	Intel Core i3 or higher	
Processor Number	Intel Core i3 13100 or higher	
Number of Cores and Threads per Processor	Max Turbo Frequency 4.5Ghz, Minimum 4 Cores and 8 Threads or higher	
Operating System	Windows 11 Home Factory Preloaded	
RAM Size (GB)	DDR-4 8GB 3200 (16 X1) or higher (2 DIIM Slots)	
RAM Expandability up to (using spare DIMM Slots in GB)	64 GB or higher	
Integrated Graphics	Intel UHD Graphics 770 or higher	
Supported for discrete NVIDIA/AMD Graphics Card up to 6GB	Yes	
Type of Drives used to populate the Internal Bays	NVMe SSD	
Total HDD Capacity (GB)	NA	
Total SSD Capacity (GB)	512GB NVMe SSD	
Optical Drive	Optional	
Drive Bays	Two 3.5" (2.5") HDD	
	1 PCI Express 4.0 x16,	
Slots for Upgradation	1 PCI Express 3.0 x1,	
3013 101 098,000101	1 PCI (Full Height), 2 M.2 slots for WLAN & SSD	
	LAN: Integrated 10/100/1000M	
LAN	Front: 1 headphone/microphone combo; 3 Super Speed USE	
Ports and Connectors	5Gbps signalling rate; 2 SuperSpeed USB 10 Gbps signalling rate; 1 USB Type-C, total 6nos USB in front for easy access Rear: 1 HDMI; 1 Serial Port; 1 line in; 1 line out; 1 power connector; 1 RJ-4S; 1 DP; 2 USB 2.0	
Firmware Trusted Platform Module	TPM 2.0	
Hardware Security lock slot	Security lock slot	
Power Supply	180-260Watt Internal power supply with minimum 90% efficiency	
	Bidder should submit OEM bid specific authorization & the same authorization may be verified by the respective OEM i required.	
	OEM must have the ISO 9001,14001, ISO 20001, ISO 27001 Certificate	
Certification	Microsoft Windows, Energy star 8.0 certified	
	Bidder should submit BIS, BEE, EPEAT, UL, RoHS Certificate of products at the time of participation of the Bid.	
Keyboard Mouse	USB Keyboard; USB Optical Mouse	
Monitor	19.5" LED Display with CTO Certified and same must be belongs to the same OEM	
Years of Warranty	3 Year Onsite Warranty	

	600 VA Line Interactive UPS Specifications			
SI. No.	Feature	General Specifications		
1	UPS Capacity (total)	600VA/360W		
2	Input Voltage	230 VAC nominal		
3	Input Frequency	45 - 65 Hz		
4	Brownout Transfer	145 VAC typical		
5	Over-voltage Transfer	290 VAC typical		
6	Voltage on Battery	230 VAC typical (stepped approximated sine wave)		
7	Frequency – On Battery	50Hz typical		
8	Transfer Time	@50 Hz : 6 ms typical, 10 ms max		
9	Air Ventilation	Should have Side and Back Honey bee Perforation for heat dispersion		
10	Protection from Humidity & Dust	UPS Should have conformal paint coating on PCB for Insulation for Dust and Humidity.		
11	Battery Saver Option	UPS Should have Battery Saver Option to increase the life of the Battery upto 5 years		
12	No Load Shutdown	UPS Should work on loads of 2-3 watts also		
13	AC Surge Protection	Full time, 160 joules		
14	Automatic Re start of UPS	In case the UPS backup is totally drained and automatic switched off, when the grid power resumes the UPS Should Auto Start without human interference.		
15	Type (maintenance-free)	12V, 7.2 Ah		
16	Typical recharge time	4- 6 hours		
17	Operating Temperature	0°C to 40°C		
18	Storage Temperature	-15°C to 45°C		
19	3 power outlets	With battery backup and surge protection		
20	Power Cord	1.2 meters		
21	Runtime for Single PC load (60W ± 15W)	27 min (normal mode)		
22	Runtime for Workstation PC (100W ±15W)			
23	Battery Saver (to save on battery life)	Thru toggle button on front panel		
24	Certification	BIS		
25	Designed and Manufactured in India	Yes		
26	Warranty	2 yeasrs		

	Generic	
Description of Stores	Multifunction Machine Printer with Minimum 1 Year On Site Warranty, including Cartridge and Power Cord/Adapter	
Core Function	Print, Scan and Copy	
Print Technology	Laser	
Cartridge Technology	Composite Cartridge	
Type of Printing	Monochrome (Black)	
RAM Size (MB)	256	
Storage Capacity (in GB)	0	
Features	Fax	
Operating System Compatibility	Windows 10 and Above, Linux, Mac OS, Windows Server	
	Printing	
Print Paper Size	A4 and Legal	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Monochrome (Black) (in PPM)	26 to 30	
Minimum Print Speed per Minute as per ISO/IEC 24734 in A4 Size-Colour (in PPM)	Not Applicable	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Mono (in PPM)	Not Applicable	
Minimum Speed per Minute as per ISO/IEC 24734 in A3 Size- Color (in PPM)	Not Applicable	
Auto Duplexing Printing/Coping (2-sided Feature)	Yes	
	Scanning	
Maximum Scan Area (Platen/Flatbed Size)	A4 and Legal	
A4 Scan Speed -Colour (Image Per Minute) @ 300 x 300 dpi	11 to 20	
Scan To Functions	Email	
A4 Scan Speed - Mono (Image Per Minute) @ 300 x 300 dpi	11 to 20	
	COPYING	
Reduction and Enlargement Feature	Yes	

	PAPER HANDLING
Original Document Feeder Type (For Scanning and Copying)	Automatic Document Feeders (ADF)
Feeder Capacity (Number of Sheets) (For Scanning and Copying)	31 to 40
Number of Main Paper Tray	1
Total Paper Tray Combined Capacity (Number) at 75 GSM	101 to 200
Bypass Tray Facility	No
If Yes, Bypass Tray Capacity	0
Connectivity	
Connectivity	USB Port,Ethernet Port,Wi-Fi
Accessories Provided	USB Cable
	Performance
Cartridge/Ink/Toner supplied with Machine as per IS/ISO/IEC: 19752/2017 for Black (Number of Prints)	
Minimum Yield of the Cartridge/Ink/Toner Supplied with Machine as per IS/ISO/IEC: 19798:2017 for Cyan, Yellow and Magenta Color (Number of Prints)	0
Minimum Duty Cycle (Number of Prints/Month)	10,001 to 20,000
	POWER
Power Supply	Single Phase AC 220 - 240 V, 50 - 60 Hz
Maximum Power Consumption (in Watt)	1300
Environmental	
Minimum Operating Temperature (Degree C)	10
Maximum Operating Temperature (Degree C)	30

Minimum Operating Humidity (%RH)	20	
Maximum Operating Humidity (%RH)	80	
	Dimension	
Standard Machine Weight with Single Tray (in Kg)	11	
	Certification	
BIS CRS Compliance	Yes as per IS 13252 (Part 1)	
Maximum Number of Prints covered under Product warranty (Whichever is earlier)	30000	
EPR Registration in respect of the manufacturer/authorised importer as per E waste rules as amended up to date	Yes	
Agreed to Provide a copy of EPR Registration Certificate to the Buyer on Demand	Yes	

	Caraga Cino	65
	Screen Size	350Nits or better
	Brightness (cd/m²)  Contrast Ratio	1200:1
		400,000:1
	Dynamic Contrast Ratio	8.0
General Features	Response Time (ms)	3840 x 2160
	Display resolution (H x V, pixels)	
	HDR (High Dynamic Range) compatiblity	Yes (HDR10, HLG)
Marie Company	Aspect Ratio	16:9
	Portrait/Tilt Compatibility	Yes
	Dimming type	Frame Dimming
	Display Device	LCD
	Panel Type	IPS
	Backlight type	Direct LED
Display features	Color gamut (NTSC)	69%
	Operation time	16/7
	Haze (%)	1 %
	Viewing Angle (Right/Left)	178 (89/89) degree
	Viewing Angle (Up/Down)	178 (89/89) degree
	HDMI Signal	4096 x 2160p (24, 50, 60 Hz 3840 x 2160p (24, 25, 30, 50 60 Hz), 1080p (30, 50, 60 Hz 1080/24p, 1080i (50, 60 Hz), 720p (30, 50, 60 Hz), 720/24p, 576p, 576i 480p,480i
Audio Sport	Speaker Position	Down Firing
Audio Specs	Audio Power Output	10W + 10W
	Pro settings	Yes (Simple Pro settings men
Professional	HDMI auto wake-up	Yes
features	Operating System	Android TV
	On-board Storage (GB)	16GB
	RAM	3GB
	Wi-Fi Certified	Yes
Network Specs	Wireless LAN	Integrated
	USB playback codecs	MPEG1:MPEG1/MPEG2 PS:MPEG2/MPEG2 WEBM:AV1/AC4/ogg/AAC
Convenience	On Screen Clock	Yes
features	Sleep Timer	Yes
	On/Off Timer	Yes
	Chromecast built-in	Yes
	Apple AirPlay	Yes
	IP Control	Yes
Control Specs	RS-232C Control	Yes
	HDMI-CEC	Yes
No. of Contract of	HDCP	HDCP2.3 (for HDMI1/2/3)
	Composite Video Input (s)	1 (Side, Mini jack)

	HDMI inputs total	3 (3Side)
Inputs and outputs	Analog Audio Input (s) (Total)	1 (Side Analog Conversion)
	Digital Audio Output (s)	1 (Side)
	USB ports	2 (Side)
	Ethernet inputs	1 (Side)
Design features	VESA* Hole Pitch (W x H)	300 x 300 mm
	Rated Power Consumption	226W
Environment Specs	Power Consumption (in Standby)	0.5 W
Livil Office Specs	Dynamic Backlight Control	Yes
	Power Saving Mode / Back Light Off Mode	Yes
	Dimension of TV without Stand (W x H x D)	1462 x 842 x 71 mm
Measurements	Dimension of TV with Stand (W x H x D)	1462 x 912 x 338 mm
	Dimension of Package Carton (W x H x D)	1588 x 965 x 184 mm
A SELECTION OF THE PARTY OF THE	Weight of TV without Stand	20.4 kg
Weight	Weight of TV with Stand	21.3 kg
	Weight of Package Carton (Gross)	28 kg



Visit the Logitech Store

AVAILABLE OFFERS

Year

Home / IT Security / Computer Accessories / WEBCAM / Logitech Master Series Graphite M

Share 📢

@ BUR DISCOUNT The Ships within 5 days Logitech Master Series Graphite MX Brio 4K

220,999 - ISK OST MRP #94.995 0.86% OFF

224,779 (Incl. of all taxes)

Login

Ultra Hd Web Camera, 960-001548 t FORES BLACE (2)

Order Quantity- I

EMI starts at \$2202/month. No Cost EMI available **EMI options** 

Get up to \$4,000° on a min, order value of \$5,498

Get up to £3,500° on a min, order value of £8,498 First-time 828 users only, T&C opply

First-time 98T users only, 76C apply

#### **Bulk quantity Discounts!!**

Select	Quantity	Discounted price per piece(incl of all toxes)
--------	----------	---

0 2-3 F23,98014

0 4-5 223,740 53 0 £23,500 93 6-7

#23 34119 O 8-more

FFATURES

Country of Origin

Package Contains

Connectivity Focus Type

More Details

Switzerland

USB-C to USB-C Cable

**Advanced Autofocus** 

MX Brio, Mount Clip

with Removable Adapter, USB-C to C 3.0 Cable, User Documentation

## ADD TO CART

0

Connec with a Product Expert

0

**BUY NOW** 

More Logitech WEBCAM products More WEBCAM products



Worranty as per



100% Original Products



Secure payments



100% Buyer protection



Brands

O Check Delivery Details Enter Procede Check

PRLPAID

Available

PART COD

Unavailable

Available

RETURN

Available Return period 7 days



Model No

DESCRIPTION

Country of Origin **Switzerland** Connectivity USB-C to USB-C Cable Focus Type **Advanced Autolocus** MX Brio, Mount Clip with Removable Adapter, USB-C to C 3.0 Cable, User Documentation Package Contains Microphone Type **Dual Beamforming** Width 98 mm Zoom 4x Digital Zoom Type of Product

960-001548

Web Camera MODRICARGRET **Part No.** Height 44 mm

137 g Weight Lens Type Gloss Interloce USB 3 0 Color Graphite

4K/30 fps, 1060p/60 fps Resolution 8.5 MP Sony STARVIS Image Sensor



