

## SALES SPECIFICATION

### LEAD OCTOATE 30%

#### Product Information

Chemical name: Lead 2-Ethylhexanoate CAS N°: Click or tap here to enter text.

Product name: Lead Octoate 30% HS code: Click or tap here to enter text.

#### General description

Lead Octoate 30% is a viscous, oil-soluble metal carboxylate used as a through-drier in alkyd-based coatings and inks. It enhances deep-film curing when combined with surface-active driers such as cobalt octoate. This formulation offers reliable performance in medium to high-build systems, promoting uniform oxidative cross-linking throughout the film.

#### Properties

Property	Value
Name	Lead Octoate 30%
Appearance	Viscous Liquid
Color	Yellow
Odor	Typical
Boiling Point	175–210°C
Flash Point	>61°C
Autoignition Temperature	>200°C
Vapor Pressure (at 200°C)	<3 mbar
Water Solubility	Insoluble

## Storage and handling:

- Shelf Life: 12 months from the date of manufacture under proper storage conditions.
- Store in sealed containers in a cool, dry, and well-ventilated area.
- Avoid exposure to heat, flame, sunlight, and moisture.
- Use suitable PPE when handling (gloves, goggles, protective clothing).
- Stir thoroughly before use, as some settling may occur.