

SALES SPECIFICATION

LEAD OCTOATE 32%

Product Information

Chemical name: Lead 2-Ethylhexanoate CAS N°: Click or tap here to enter text.

Product name: Lead Octoate 32% HS code: Click or tap here to enter text.

General description

Lead Octoate 32% is a metal carboxylate used as a through-drier in alkyd-based paints and coatings. It promotes deep-film oxidative curing, helping to improve film hardness, toughness, and overall durability when used in conjunction with surface driers like cobalt octoate. This product ensures a more uniform and complete curing profile in medium to high-build coatings.

Properties

Property	Value
Name	Lead Octoate 32%
Mental content % (+/-0.2)	32
Non-Volatile 120°C g/Hr (+/-5)	62
Color	Pale Yellow
Specific Gravity 30°C	1.230
Viscosity at 30°C (+/-3)	20
Packing	22/25 kg M.S. Drums & 160/220 kgs M.S. Barrel

Storage and handling:

- Shelf Life: 12 months from the date of manufacture when stored under proper conditions.
- Store in tightly sealed containers in a cool, dry, and well-ventilated area.
- Keep away from heat, sunlight, and moisture.
- Use appropriate personal protective equipment (PPE) during handling.
- Stir well before use, as slight settling may occur over time.