

SALES SPECIFICATION

LEAD OCTOATE 36%

Product Information

Chemical name: Lead 2-Ethylhexanoate CAS N°: Click or tap here to enter text.

Product name: Lead Octoate HS code: Click or tap here to enter text.

General description

Lead Octoate 36% is a high-metal-content metal carboxylate drier used in alkyd-based paints and coatings. It functions as a through-drier, accelerating the oxidative polymerization process deep within the film, especially in conjunction with surface driers like cobalt octoate. Lead Octoate helps achieve a uniform cure and improves film hardness, durability, and resistance properties.

Properties

Property	Value
Name	Lead Octoate
Mental content % (+/-0.2)	36
Non-Volatile 120°C g/Hr (+/-5)	70
Color	Pale Yellow
Specific Gravity 30°C	1.34
Viscosity at 30°C (+/-3)	27
Packing	22/25 kg M.S. Drums & 160/220 kgs M.S. Barrel

Storage and handling:

- Shelf Life: 12 months from the date of manufacture under recommended storage conditions.
- Store in tightly closed containers in a cool, dry, and well-ventilated area.
- Protect from direct sunlight, moisture, and heat sources.
- Use appropriate PPE (gloves, goggles, protective clothing) when handling.
- Agitate thoroughly before use to ensure uniformity.