

Solutrade St. Petersburg

FL 33702

Tel: +1 (407) 603-6019 7901 4 TH N STE 300 Fax: +1 (844) 333-0296 www.solutrade.co info@solutrade.com

SALES SPECIFICATION

Styrene Acrylic 45%

Product Information

Styrene-Acrylic Copolymer Emulsion CAS N°: Chemical name: Click or tap

here to enter text.

Product name: Styrene Acrylic 45% HS code: Click or tap

here to enter text.

General description

Styrene Acrylic 45% is a styrene-acrylic copolymer emulsion formulated for economical paint systems. It forms a hard, glossy, and flexible film with excellent wet scrub and abrasion resistance, making it ideal for interior coating applications where performance and costefficiency are important.

Properties

Property		Value	
Name		Styrene Acrylic 45%	
Appearance		Milky White Viscous Emulsion	
Solids Content		45% ± 2%	
Viscosity @ 30°C (RVT, Spindle No. 4, 10 rpm)		1500 – 2000 cP	
Monomer Residue		< 0.3%	
Minimum Film Forming Temperature (MFFT)		17°C	
pH		8.0 – 10.0	
Film Characteristics		Hard, Tough, Flexible, Glossy	



Solutrade 7901 4 TH N STE 300 Fax: +1 (844) 333-0296 St. Petersburg

FL 33702

www.solutrade.co info@solutrade.com

Tel: +1 (407) 603-6019

Storage and handling:

- Store in a cool, dry, and well-ventilated place
- Keep containers tightly closed
- Stir well before use
- Shelf Life: 12 months in unopened original containers

