

Plasma Cutting INVERTER

KEY BENEFITS Applications 1

- On-site maintence
 - Service tasks
- Small construction sites
 - General installations
- Air ducting installation(HVAC)
 - Rental 🖷

Control Panel



PERFECT IGNITION RESPONSE

/ Less heat input / Less distortion

CE (DI (D) 3)

PC 40 AIR

Precise, accurate, infinite amperage control and heat output

PC 40 AIR





Protections-Equipped with temperature, voltage and current sensors for high protection.




Compressor inside internal compressor or exernal

440V Tested In Production compressor air supply







TECHNICAL DATA(subject to change without notice.)

	PC 40 AIR
Power Supply Voltage	1-230
Effective Current	25 A
Rated Input Power	4.7kVA
Rated Input Current	32 A
Duty Cycle(40°⊂ 10min)	40% 40 A
	100% 30 A
Grid frequency	50/60Hz
No Load Voltage	32 V
CUTTING CURRENT RANGE	20-40 A
Insulation class	н
Protection class	IP 23
Cooling	AF
Dimensions I x w x h	480 x 210 x 340mm
Weight	17.9 kg
Severance Cut(MM)	Carbon Steel ≤16
Production Cut(MM)	Carbon Steel ≤14 Stainless Steel ≤14 Aluminum ≤14 Copper ≤ 5
Order information	

