





SHOWER FILTER INSTALLATION INSTRUCTIONS

What's this for?

- The instruction tells you how to start enjoying your new shower filter and quickly install.
- Match standard 1/2" threaded connector (the universal size in North America and Europe).
- For best results, keep water temperature between 39 and 176 °F

Installation Guide

	Step1 : Rinse The Shower Filter —Place the shower filter under a faucet and let the water flush for about 20 seconds or until the water is clear. —Then turn the shower filter upside down to flush it again.
	Step2 : Remove Shower Head or Bracket —Remove the existing shower head from the shower arm by turning it counter-clockwise. —OR if you have a hand shower, remove the shower bracket.
	Step3 : Attach Shower Filter to Shower Arm —Clean any excess material from the shower arm threads. (Wrap tape around the threads 2-3 times if leak after install the shower filter) —Place shower filter (Upside with mesh washer) and hand tighten to the shower arm by turning it clockwise.
	Step4 : Attach Shower Head to Shower Filter —Attach the shower head or bracket on to the shower filter, then hand tighten by turning it clockwise. —Turn on the water to check if it works normally.

Thank you for choosing this shower filter and we hope you enjoy using it. Please take a few moments to read these instructions before installing the filter, and keep them in a safe place for future reference.

FILTER CARTRIDGE REPLACEMENT INSTRUCTIONS

What's this for?

- The instructions tell you how to replace the filter cartridge for your shower filter
- High Output Luxury Shower Filters last for 12, 000 gallons (about 6 months)

Replacement Guide




shower filter
(Upside with Vortex)



filter cartridge




shower filter
(Downside)



Step1 : Open the Shower Filter

- Disassemble the shower filter, by holding the top section of the shower filter and rotating the bottom section counter-clockwise.
- Once open, the filter cartridge can be removed.




Step2 : Replace Filter Cartridge

- Remove the old filter cartridge from the shower filter. If there is debris left inside, rinse the inside of the filter under a tap.
- Insert the new filter (concave facing up and flat facing down) cartridge and re-assemble the shower filter.

NOTE:

We recommend changing the cartridge every six months. If your water contains high levels of chlorine and other impurities, you may need to change this more frequently.



Step3 : Rinse the Shower Filter

- Place the shower filter under running water for 60 seconds.
- Turn shower filter over and run water in the opposite direction.
- The water may initially run turbid, continue rinsing the shower filter until the water runs clear.

Contact Us:

Please do not hesitate to contact us. We are here to help your situation that you meet. We will replace or repair your product.

Email:

mikechen@eyakult.com(USA)
zhongly@eyakult.com(Canada)