CARRIER RACK ASSEMBLY GUIDE

ATTENTION! Please ensure that the carrier rack installed properly and the bolts are tightened. Improper installation can make your bike extremely unsafe and dangerous to use. Please see your dealer or a qualified bike shop for assistance.



INSTALLATION:

To install the rack remove the seat from the bike. The carrier rack attaches to the seat by an 8mm locking bolt and a longer quick release than the existing one comes with your bike. (Both supplied with the rack) The tail light is great for your safety especially at poor light and nights. Insert the batteries while controlling their polarity. It has four modes. The batteries last much longer on flashing modes. Always keep the tail light clean and avoid direct exposure to water.

Clearance between the left brace and disc brake

ATTENTION!

There are two holes on each side of the carrier plates. These holes are designed to accommodate different positions of the seat to prevent the side braces from hitting the rear disc brake while the rear shock functioning. Please make sure that there is enough clearance between the left brace and the rear disc brake by using the proper choice of these two holes. Failing to do so may result damaging your rear disc brake and possible dangerous accident. If you normally ride your bike with the seat at the back side of the seat rail use the lower hole. (Fig 1) If the seat stays at the front side of the seat rail, use the top hole. (Fig. 2) You may not to install the side brace if you are not using panniers. You also may use only the right brace if you use a single side pannier.

WARNING!

Never use panniers without installing the carrier's braces. It simply may result dangerous movement of the panniers into the spokes and hazardous accident. Attach the braces securely using the supplied bolts, washers and locking nuts. The braces are angles slightly outward to avoid touching the disc brake. (**Fig 3**) For your safety make sure that the bolts and all three quick releases are securely tightened before any ride. Never carry bulky, heavy items or infants with your carrier rack. It can result dangerous or fatal accident.

Maximum recommended carrying load: 15Lbs (7kg)

Clearance between the left brace and disc brake



Fig. 3



