



BROOKLYN AUDIO

Line 10

Description:

Line array element for medium to large indoor and outdoor applications.
Full-range bi-amped double 10"/2"/1" system with a 3 dimensional wave guide what makes the system a real line-source system.
Ultra fast BA rigging system, easy and safe rigging up to 16 cabinets.
Very good throw up to 100 meters (330 ft).
Different presets available for all possible combinations with or without subs.

Transducers:

Low: 2*10" neodymium cone driver
Impedance: 16 Ohm
AES power 1400Watt/75V
Sensitivity: 98 dB 1W/1m

Mid/High: 2"/1" coaxial neodymium compression driver behind a 3D waveguide*
Impedance: 16 Ohm
AES power: 150 watt/48V
Sensitivity: 118 dB 1W/1m
*passive filter between the 2" and 1" driver

Usable bandwidth 60Hz-20kHz +/-3dB
Phase: +/-40° 300Hz-20kHz

Directivity:
Horizontal: 120°
Vertical: Depends of the splay between and the number of cabinets.

Electrical connections: 2 Speakon NL4 connectors, low 1+/1- high 2+/2-

Physical data:

WxHxD: 620x312x620mm
Weight: 34kg
Material: 15mm birch plywood
Finish: Black PU coating*
Grille: Aluminium anodized with integrated rigging.
Availble colours: Blank or black anodized
Rigging: Brooklyn-Audio rigging with 5 angles 0-8°
Safety factor>10 up to 16 cabinets
Flybumper: BABUMP eight/ten