

Prospect sub

Description:

The Prospect sub is a self powered sub cabinet with an 18" neodynium driver with an X-max of +/-19mm in a basreflex cabinet.

In combination with the other Prospect series cabinets it wil give the sound a massive body down to 25 Hz.

Four different presets available for 60 and 100Hz also as cardoide and end-fire.

Transducers:

Low: 18" neodymium cone driver with water resistant cone

Voice coil: 4,5"

AES power 1600 watt/109V

Acoustical:

Maximum peak SPL: 133 dB

Usable bandwith: 30Hz-100Hz +0/-3dB (25Hz - 6 dB)

Directivity: Omni directional

Physical data:

WxHxD: 530x700x650mm

Weight: 52kg

Material:18mm birch plywoodFinish:Black PU coating*Grille:Steel powdercoatedRigging:M20 pole mount

Amplifier:

Power: 2100 watt class-D amp-module

DSP: 24 bit 48kHz AD/DA conversion and 26 bit processing

 Gain:
 32 dB

 Voltage gain:
 x 80

 Input impedance:
 10 kOhm

 Input sensitivity:
 1,15V/3,43 dBU

Max input level: 15 dBU

AC mains power: 90-400V, 50/60Hz

Protection: Thermal shutdown, short circuit/overload/HF output

clip limiter, permanent signal limiter, temperature controlled fan

Max environment temp.: 40°C

Electrical connections: Powercon in and out, XLR in and out.