

SPECIFICATIONS

CCT	5,600K	CRI	96+
TLCI	99+	CQS	95+
SSI (D56)	87+	TM-30 RF (Average)	95
TM-30 RG (Average)	103	Max Power Consumption	221W
Max Power Output	200W	Lumens	20,000lm
Beam Angle (No Reflector)	110.0°	Beam Angle (Hyper Reflector)	25.9°
Operating Voltage (DC Power Supply)	48V / 5.2A	Operating Voltage (AC Power Supply)	100V ~ 240V / 2.5A ~ 5.0A
Operating Temperature	-10°C ~ 40°C / 14°F ~ 104°F	Storage Temperature	-20°C ~ 80°C / -4°F ~ 176°F
Control Methods	On-board, Sidus Link App	Firmware Upgradeable	Sidus Link
Wireless Operating Range (Bluetooth)	≤100m / ≤328.1ft	Screen Type	LCD
Cooling Method	Active Cooling	Max Light Output	7,890 lux @ 1m (No Accessory) / 55,800 lux @ 1m (Hyper Reflector)

★ DIMENSIONS

Lamp Head w/o Mounting Bracket	207 x 115 x 115cm / 81.5 x 45.3 x 45.3in	Lamp Head w Mounting Bracket	207 x 119 x 200cm / 81.5 x 46.9 x 78.7in
Power Supply	170 x 84 x 31mm	Power Cable	300cm / 118.11in

★ WEIGHT

Lamp Head	1.56kg / 3.44lbs
Power Supply	790g / 1.74lbs
Total with Case	3.71kg / 8.18lbs

▶ WHAT IN THE BOX

amaran 200d S
Bowens Mount Protection Cover
Bowens Mount Hyper Reflector
AC Power Supply
AC Power Cable