

## SPECIFICATIONS

CCT	2,700K - 6,500K	CRI	95+
TLCI	98+	CQS	97+
SSI (D32)	90+	SSI (D56)	89+
TM-30 RF (Average)	97	TM-30 RG (Average)	101
Max Power Consumption	229W	Max Power Output	200W
Lumens	17,000lm	Beam Angle (No Reflector)	111.4°
Beam Angle (Hyper Reflector)	26.1°	Operating Voltage (DC Power Supply)	AC 100V ~ 240V / 0.95A ~ 2.5A
Operating Temperature	-10°C ~ 40°C / 14°F ~ 104°F	Storage Temperature	-20°C ~ 80°C / -4°F ~ 176°F
Control Methods	On-board, Sidus Link App	Firmware Upgradeable	Sidus Link
Wireless Operating Range (Bluetooth)	≤100m / ≤328.1ft	Screen Type	LCD
Cooling Method	Active Cooling	Max Light Output	6,400 lux @ 1m (No Accessory) / 45,400 lux @ 1m (Hyper Reflector)

## ★ DIMENSIONS

Lamp Head w/o Mounting Bracket	20.7 x 11.5 x 11.5cm / 8.15 x 4.53 x 4.53in	Lamp Head w Mounting Bracket	20.7 x 11.9 x 20cm / 8.15 x 4.69 x 7.87in
Power Supply	17 x 8.4 x 3.1cm / 6.69 x 3.31 x 1.22in		

## ★ WEIGHT

Lamp Head	1.56kg / 118.11in
Power Supply	790g / 1.74lbs
Total with Case	3.712kg / 8.18lbs

## 📦 WHAT IN THE BOX

amaran 200x S
Bowens Mount Protection Cover
Bowens Mount Hyper Reflector
AC Power Supply
AC Power Cable