

## SPECIFICATIONS

CCT	2,500K - 7,500K
TLCI	95+
SSI (P3200)	83+
TM-30 RF (Average)	92
Max Power Consumption	360W
Lumens	19,389 lm (@5,600K)
Beam Angle (Hyper Reflector)	64.8°
Operating Voltage (AC Power Supply)	100V ~ 240V / 2.5A / 50-60 Hz
Storage Temperature	-20°C ~ 80°C / -4°F ~ 176°F
Firmware Upgradeable	Sidus Link
Screen Type	LCD
Max Light Output	9,370 lux @ 1m (No Accessory) / 26,580 lux @ 1m (Hyper Reflector)

CRI	95+
CQS	97+
SSI (D56)	71+
TM-30 RG (Average)	101
Max Power Output	300W
Beam Angle (No Reflector)	89.6°
Operating Voltage (Fixture)	DC 48V / 7.5A
Operating Temperature	-10°C ~ 40°C / 14°F ~ 104°F
Control Methods	On-Board, Sidus Link App
Wireless Operating Range (Bluetooth)	≤100m / ≤328.1ft
Cooling Method	Active Cooling

## ★ DIMENSIONS

Lamp Head w/o Mounting Bracket	25.0 x 15.5 x 14.2cm / 9.8 x 6.1 x 5.6in
Power Supply	19.8 x 9.9 x 2.8cm / 7.8 x 3.9 x 1.1in

Lamp Head w/ Mounting Bracket	25.0 x 19.4 x 25.1cm / 9.8 x 7.6 x 9.9in
DC Power Cable	3m / 9.84ft

## ★ WEIGHTS

Lamp Head	2.63kg / 5.8lbs
Power Supply	888g / 1.96lbs
Total with Case	3.52kg / 7.76lbs

## 📦 WHAT'S IN THE BOX

1x amaran 300c
1x Bowens Mount Protection Cover
1x Bowens Mount Hyper Reflector
1x AC Power Supply
1x AC Power Cable
1x amaran 300c Carrying Case