

LITEPANELS  
GEMINI 1X1

RUNTIME\*  
**~1.6**  
HOURS

# Titon SERIES

**Power your story.**

Titon series Lithium-ion batteries are the perfect power choice for broadcast professionals to run cameras, lights and other power-hungry on-location equipment. From breaking news and live sportscasts to covering extreme weather and major events; Titon power keeps your story moving.

Choose from 90Wh, 150Wh and 240Wh capacities, in V-Mount or Gold Mount options to perfectly match your workflow. Titon batteries bring Anton/Bauer's superior mobile power technology to any broadcast camera operator, regardless of their existing battery mounting or charger choice. Know the exact remaining runtime - down to the minute - with the on-board LCD or through a camera viewfinder. Titon smart technology considers and calculates everything being powered by the battery - even devices powered by the high-speed USB and P-TAP ports - leaving crews free to focus on capturing the story.

The workhorse power solution for demanding crews working in the most extreme challenging situations. Titon 240 provides extended runtime to operate power hungry cameras and LED panels for hours versus minutes. High quality cells in a tough and rugged case ensure that Titon delivers consistent power to even the most demanding users in temperatures from -4F to 140F (-20C to 60C). Titon is the, reliable, travel-safe choice when there is only one chance to get the shot.



Run Cameras, Monitors, Lights and more with Titon series batteries from Anton/Bauer

**Global Support**

Seven service locations worldwide to support crews in the field.

**Travel Certified**

Titon 90 and 150 fully IATA certified for onboard carry-on. Fits industry travel cases and chargers.

**V-Mount and Gold Mount\***

Compatible with your way of working

Knowledge is power, know your runtime down to the minute

**On-board LCD screen**

Power for your camera, LED lights and everything else

**P-TAP and High Speed USB**



	Titon 90	Titon 150	Titon 240
<b>Capacity</b>	92Wh	156Wh	238Wh
<b>Height</b>	5.1" / 13cm	5.1" / 13cm	5.1" / 13cm
<b>Depth</b>	2.27" / 5.2cm	2.81" / 7.2cm	3.5" / 8.8cm
<b>Width</b>	3.8" / 9.7cm	3.8" / 9.7cm	3.9" / 9.9cm
<b>Weight</b>	1.76lbs. / 0.8kg	2.4lbs. / 1.1kg	2.9lbs. / 1.3kg
<b>Operating temperature range - Discharge</b>	-4°F to 140°F (-20°C to +60°C)		-4°F to 140°F (-20°C to +60°C)
<b>Maximum Discharge Rate</b>	10A		
<b>Output Voltage</b>	Nominal 14.2V Operating 10.0V - 16.3V	Nominal 14.4V Operating 10.0V - 16.8V	Nominal 14.4V Operating 10.0V - 16.8V



antonbauer.com

\*Runtime based on Titon 150.  
\*\*Runtime based on Titon 240 and @75% output.