

Blackmagic Web Presenter 4K



Blackmagic Web Presenter 4K is the ultimate HD and Ultra HD streaming solution that includes a professional hardware streaming engine for streaming up to 2160p60 directly to YouTube, Facebook, Twitter and more! Plus you can stream to the internet using Ethernet or connect a 5G or 4G phone to use mobile data! The built in USB connections also work like a webcam, so you can connect a computer and use any video software. You even get a monitoring output with video, audio meters, trend graphs and more!

\$675

Connections

SDI Video Inputs

1

SDI Video Outputs

1 x loop out, 1 x monitor out.

SDI Rates

1.5G, 3G, 6G, 12G

HDMI Video Outputs


1 x monitor out


Webcam Output

1 x USB-C up to 2160p60

Ethernet

Ethernet supports 10/100/1000 BaseT for live streaming, software control and software updates.





Standards

HD Video Input Standards

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30 1080i50, 1080i59.94, 1080i60

Ultra HD Video Input Standards

2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p50, 2160p59.94, 2160p60

Video Input Color Space

Rec.601, Rec.709, Rec.2020

3G SDI

Auto detects SMPTE level A or B on SDI input.

SDI and HDMI Monitor Out Video Standards

1080p50, 1080p59.94, 1080p60

Video Streaming Standards

720p25, 720p30, 720p50, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60 2160p23.98, 2160p24, 2160p25, 2160p29.97, 2160p30, 2160p50, 2160p59.94, 2160p60

Streaming

Direct Streaming

Blackmagic Web Presenter 4K supports direct live streaming over ethernet using Real Time Messaging Protocol (RTMP) in H.264, and Secure Reliable Transport (SRT) in H.264 and H.265.

Closed Captions

Web Presenter 4K supports embedding CEA-608 and CEA-708 closed captions in your live RTMP stream.

Control

Control Panel

Built in control panel with 2.2 inch color display for video preview, audio meters and status.

Device Control

Front panel, USB-C or ethernet.

Software

Compatible Services and Software

Facebook, Twitch, YouTube, Twitter, Restream.IO, Vimeo, BoxCast, Castr, AfreecaTV, Bilibili, DouYu, Weibo, Zoom, Skype, Microsoft Teams, QuickTime Player, FaceTime, OBS Studio, Open Broadcaster, VLC, Wirecast Play, Wowza Streaming Engine.

Operating Systems



Mac 11.0 Big Sur, Mac 12.0 Monterey or later.



Windows 10, 64-bit. Windows 11.



Linux



Power Requirements

Power Supply

1 x Internal 100 - 240V AC.

12V DC Input


1 x +12V DC 4-pin XLR.

Power Usage

25 W

Physical Specifications









Environmental Specifications

Operating Temperature

0° C to 40° C (32° - 104°F)

Storage Temperature

-20° to 45° C (-4° to 113° F)

Relative Humidity

0% to 90% non-condensing

What's Included

Blackmagic Web Presenter 4K

Warranty
3 year Limited Manufacturer's Warranty.
All items on this website are copyright Blackmagic Design Pty. Ltd. 2024, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. Privacy Policy.
Blackmagic Design Authorized Reseller