

SPECIFICATIONS

CCT	5,600K	CRI	96+
TLCI	99+	CQS	95+
SSI (D56)	86+	TM-30 RF (Average)	96
TM-30 RG (Average)	100	Max Power Consumption	77W
Max Power Output	65W	Lumens	7,195lm
Beam Angle (No Reflector)	107.8°	Beam Angle (Hyper Reflector - Mini)	13.9°
Operating Voltage (DC Power Supply)	19V / 4.73A	Operating Voltage (AC Power Supply)	100V ~ 240V / 1.5A
Operating Voltage (V-Mount Battery)	12V ~ 16.8V	Operating Temperature	-10°C ~ 40°C / 14°F ~ 104°F
Storage Temperature	-20°C ~ 80°C / -4°F ~ 176°F	Control Methods	On-board, Sidus Link App
Firmware Upgradeable	Sidus Link	Wireless Operating Range (Bluetooth)	≤80m / ≤262.5ft
Screen Type	LCD	Cooling Method	Active Cooling
Max Light Output	2,940 lux @ 1m (No Accessory) / 37,800 lux @ 1m (Mini Hyper Reflector)		

★ DIMENSIONS

Lamp Head w/o Mounting Bracket	11.7 x 11.1 x 11.1cm / 4.61 x 4.37 x 4.37in	Lamp Head w Mounting Bracket	11.7 x 11.1 x 23.1cm / 4.61 x 4.37 x 9.09in
Power Supply	147 x 64 x 37.4mm / 5.79 x 2.52 x 1.47in	Power Cable	410cm / 161.4in
Battery Plate	11 x 8.6 x 2.2cm / 4.33 x 3.39 x 0.87in		

★ WEIGHT

Lamp Head	695g / 1.53lbs
Power Supply	500g / 1.1lbs
Battery Plate	111g / 0.24lbs
Total with Case	2.621kg / 5.78lbs

▶ WHAT IN THE BOX

amaran COB 60d S
Bowens Mount Protection Cover
Bowens Mount Hyper Reflector (Mini)
Diffusion Cover for Hyper Reflector (Mini)
1/4-20in Mounting Pin
Tilting Stand Adapter with Umbrella Mount
Dual NP-F Battery Plate for DC Barrel (5.5mm)
AC Power Supply
AC Power Cable
EPP Carrying Case