

Specifications

Weight
1.1 kg

Dimensions
7.1 x 20.9 x 35 cm

Payload
2.2 kg

Tilting Angle
230 °

Rolling Angle
360 °

Panning Angle
360 °

Certifications
CE, EAC, KC, FCC, IC, NCC, RCM, SRRC, TELEC

Controllable Tilt Range
+175° to -55°

Powered by (batteries)
Li-Ion

Charging mode
USB port

Attachment Type
1/4"-20 standard tripod mount

Charging time
1,5 hours

Output Connection
Wi-Fi, USB-C port

Usage Time
Up to 7 hours

App
Manfrotto Gimbal App

Minimum Working Temperature
-10 °C

Maximum Working Temperature
45 °C

Product Contents

Gimbal, Versatile arm + tighten screw*1 set, anti-slip metal tripod, Sony USB control /camera charging cable: USB2.0 to Micro(A01), Sony USB control cable: Type C to Multi, Canon USB Cable USB 2.0 to

Mini(B01), 5D Mark IV USB Cable USB 3.0 to Micro 3.0(A02), Shutter release for Panasonic TYPE C to DC2.5, Nikon &EOS R USB control/gimbal charging cable: USB 2.0 to Type C(C01), Bottom quick release plate, ARCA quick release plate, lens supporting frame + fixed screw, Thumb screw to fix the camera (short)