

## Specifications

Weight  
1.656 kg

Dimensions  
17.5 x 24 x 42.9 cm

Payload  
4.6 kg

Tilting Angle  
230 °

Rolling Angle  
360 °

Panning Angle  
360 °

Certifications  
CE, EAC, KC, FCC, IC, NCC, RCM, SRRRC, TELEC

Controllable Tilt Range  
+175° to -55°

Powered by (batteries)  
Li-Ion

Charging mode  
Charger (USB port charging not supported)

Attachment Type  
1/4"-20 standard tripod mount

Charging time  
5 hours

Output Connection  
Wi-Fi, USB-C port

Usage Time  
Up to 12 hours

App  
Manfrotto Gimbal App

Minimum Working Temperature  
-10 °C

Maximum Working Temperature  
45 °C

Product Contents

Gimball, Sony USB cable:USB2.0 to Micro(A01), Canon USB Cable:USB 2.0 to Mini(B01), 5D Mark IVUSB Cable: USB 3.0 to Micro 3.0(A02), Shutter release for Panasonic (L1), Nikon&EOS R USB Cable: USB 2.0 to TypeC(C01), Bottom mounting plate, Upper quick release plate, Support frame for tilt axis and round holder and long screw, 18650 battery\*4, Underslung arm and tighten screw , Anti-slip tripod, Support frame for lens and fixed screw, Thumb screw to fix the camera, Micro USB charging cable, Battery charger, EPP box.