

SPECIFICATIONS

CCT	2,700K – 6,500K	CRI	97+
TLCI	99	CQS	96
SSI (P3200)	83	SSI (D56)	73
TM-30 RG (Average)	102	Max Power Output (Main Light)	2W
Max Power Output (Mirror Light)	1W	Lumens	200 lm
Battery Runtime	1 Hour 21 Mins @ 100% Output / 8 Hours 50 Mins @ 10% Output	Charge Time	Approx. 70 Mins (5V/1A)
Charging Input	USB Type-C	Battery Voltage	3.7V
Battery Capacity	800mAh, 2.96Wh	Noise Level	0dBA
Operating Temperature	-10°C - 40°C / 14°F - 104°F	Storage Temperature	-20°C - 80°C / -4°F - 176°F
Control Methods	On-board, amaran App, Sidus Link	Firmware Upgradeable	amaran App, Sidus Link
Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)	Cooling Method	Passive Cooling
USB-C Charging Cable Length	50cm / 1.64ft	Dimensions	3.54 x 2.28 x 0.63in / 9.0 x 5.8 x 1.6cm
Weight	0.19lbs / 85g	Max Light Output	235 lux @ 0.5m

★ DIMENSIONS

USB-C Charging Cable Length	50cm / 1.64ft	Dimensions	9.0 x 5.8 x 1.6cm / 3.54 x 2.28 x 0.63in
-----------------------------	---------------	------------	--

★ WEIGHTS

Weight	85g / 0.19lbs
--------	---------------

▶ WHAT'S IN THE BOX

1x amaran Go
1x amaran MagSafe Adapter Sticker
1x amaran USB-C Charging Cable (50cm)