

SPECIFICATIONS

CCT	2,700K - 6,500K
TLCI	97+
SSI (D56)	74
TM-30 RF (Average)	94
Max Power Consumption	63W
Max Light Output	3,270 lux @ 1m (No Accessory)
Beam Angle (No Reflector)	85°
Power Supply Methods	USB-C PD 3.0
Operating Voltage	AC 100V - 240V / 50 - 60Hz
Max Power in Silent Mode	11W (Silent Mode)
Storage Temperature	-20°C - 80°C / -4°F - 176°F

Firmware Upgradeable	amaran App
Screen Type	TFT

CRI	96+
SSI (P3200)	84
TM-30 RG (Average)	102
Max Power Output	56W
Chipset	Bi-Color
Lumens	6,041 lumens
Weather Resistance Rating	IP20
Operating Voltage (Fixture)	USB-C PD 20V/3.25A
Max Noise Level	28dBA
Operating Temperature	-10°C - 40°C / 14°F - 104°F
Control Methods	On-board, amaran App, DMX via USB-C

Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)
Cooling Method	Active Cooling

★ DIMENSIONS

Fixture	13.4 x 12.0 x 5.8cm / 5.28 x 4.72 x 2.28in
AC Cable	2.0m / 6.56ft

★ WEIGHT

Fixture	420g / 0.93lbs
Adapter Cable	270g / 0.60lbs
AC Cable	180g / 0.40lbs

1/4 to Baby Pin	180g / 0.40lbs
-----------------	----------------

▶ WHAT'S IN THE BOX

1x amaran Halo 60x
1x amaran AC to USB-C 65W Power Adapter (2.5m)
1x amaran IEC C5 AC Power Cable (2m)

1x amaran 1/4-20in to Baby Pin Adapter with Tilt
--