

## Specifications

Weight  
2 kg

Dimensions  
19.6 x 29 x 46 cm

Payload  
3.4 kg

Tilting Angle  
340 °

Rolling Angle  
340 °

Panning Angle  
360 °

Battery Life  
10 hours hrs

Certifications  
CE, EAC, KC, FCC, IC, NCC, RCM, SRRC, TELEC

Controllable Tilt Range  
+175° to -55°

Powered by (batteries)  
Li-Ion

Charging Mode  
USB-C

Attachment Type  
3/8" adapter, 1/4 inch thread hole on the bottom of the gimbal

Charging Time  
2,6 hours

Output Connection  
Wi-Fi, USB-C port

Usage Time  
Up to 10 hours

App  
Manfrotto Gimbal 300XM

Minimum Working Temperature  
-10 °C

Maximum Working Temperature  
45 °C

## Product Contents

USB 2.0 to Type-C; Type-C to Micro(A03); Type-C to TRS2.5 (T02); Type-C to Mini (B02); Type-C to Type-C (C02); Type-C to Multi Sony shutter cable; Type-C to 2.5mm Panasonic shutter cable(DC2.5mm); Tripod; Versatile handle; Quick release plate; Higher block; Short quick release plate (GimBoom); Lens holder screw; Camera fixed screw; 3/8 to 1/4 inch transition screw; Lens holder