


## KEY FEATURES

- N2-210X
- N2-220X



- NDI Certified
- Zoom: Optical 10X, 20X
- Video Output: NDI HX3, HDMI, SDI, USB C
- Horizontal Angel of View: 69°
- Video Resolution up to Full HD
- IP resolution up to 1080P60.
- RTSP, RTMP, SRT IP streaming
- AI Exposure, AI Focus
- Power: 12VDC, PoE



## OVERVIEW

Bolin's N-Series PTZ cameras support NDI® HX3 and are fully compatible with NDI-enabled hardware and software. They are built on the Blue Line platform, which provides gold-standard features at an affordable price.

Our PTZ camera manufacturing principles never compromise image quality, industrial video standards, or PTZ control operation. So, these budget-friendly cameras are made with Bolin care and quality.

The N2 NDI HX3 PTZ camera has a compact design and form factor. The two models N2-210X, N2-220X feature a 10x or 20x wide-angle view, with a high-quality Full HD image output over NDI®, HDMI, 3G-SDI (N2-220X only), USB, and IP video streams. They are perfect for studio, live production, house of worship, huddle rooms, video conference rooms, and ProAV use.

Interoperability | Low Latency | High Quality



**NDI HX3**  
**NDI Bridge (NDI 6 Ready)**

## FUNCTIONALITY

- N2-210X and N2-220X is equipped with Sony sensor to provide brilliant, high-quality images in 1080p60 resolutions with 10X or 20x optical zoom range.
- Compact design and USB 2.0 (C Type) video used for Huddle Space cloud based video conferencing application.
- N2-210X/N2-220X cameras deliver NDI HX3 streaming video to network with local HDMI video and USB streaming to PC software for conventional video production and cloud based video conferencing applications. N2-220X also provides 3G-SDI, lossless baseband video for live production and light broadcast use.
- Image parameter adjustments includes exposure, focus, iris, shutter speed, white balance, gamma, wide dynamic range, flip/mirror and more with configurable video settings.
- Another Gold Standard feature of the Blue Line is the Color Matrix. With it, you can easily make subtle and specific corrections to the colors in your camera's image.
- Built with Bolin's latest AI-powered facial analytics engine, which enables smart focus and smart exposure to provide faster, more precise focusing and improved auto exposure on faces in complex lighting environments.
- HDMI/SDI/USB and IP video has high-quality audio streaming embedded with support for Mic-in and Line-in audio input.
- Extremely quiet and smooth operation for Pan/Tilt movements combined with enhanced adaptive, variable, and super slow adaptive speed control provides accurate and effective operation experiences. Picture Profile Preset: Image parameter settings restored with presets and quick access operation.
- Support 1GB Ethernet network, independent PoE+ (IEEE 802.3at) power and 12VDC; Standard mounting and ceiling mounting with E-Flip function.
- Firmware updates, upgrade via IP interface to keep camera features and performance up to date.



N2-210X



N2-220X

# Product Specification

| Model No.                      | N2-210X  | N2-220X   |
|--------------------------------|--|---|
| Camera                         | 10X Full HD  | 20X Full HD   |
| Image Sensor                   | Sony Progressive scan CMOS image sensor 1/2.8 type   |   |
| Number of effective pixels     | 1920X1080, 2.13 MP   | 1920X1080, 2.13 MP  |
| Zoom                           | Optical Zoom 10X, Digital Zoom 16X   | Optical Zoom 20X, Digital Zoom 16X  |
| Focal Length                   | f= 4.34 mm (Wide) to 35.17 mm (Tele)   | f= 5.2 mm (Wide) to 104 mm (Tele)   |
| Aperture                       | F1.85 (Wide) to F2.63 (Tele)   | F1.6 (Wide) to F3.0 (Tele)  |
| Horizontal Angle of View       | 68.8 °(W)~8.8° (T)   | 55.8° (W)~3.2° (T)  |
| Vertical Angle of View         | 39.5° (W)~5.1° (T)   | -   |
| Min. object distance           | 10mm (Wide)  |   |
| Min. Illumination              | 0.5lux(color), 0.1lux(black)   |   |
| Shutter Speed                  | 1/25~1/100K sec  |   |
| Focus                          | Auto, Manual, One Push   |   |
| White Balance                  | Auto, Indoor, Outdoor, OPW, ATW, Manual, SVL USER  |   |
| Exposure                       | Auto, Manual, Shutter/Iris priority  |   |
| Image Adjustment               | Brightness, Color(Saturation), Contrast, Sharpness, HUE  |   |
| Back Light Compensation        | On/Off   |   |
| E-Flip                         | On/Off   |   |
| WDR                            | On/Off   |   |
| Image Stabilizer               | -  |   |
| Defog                          | Yes  |   |
| Mirror                         | Horizontal   |   |
| Day/Night                      | On/Off   |   |
| Contrast                       | Yes  |   |
| Color Gain                     | Yes  |   |
| Color Hue                      | Yes  |   |
| Color Matrix                   | Yes  |   |
| Black Level                    | -  |   |
| Gamma                          | Yes, 4 levels (0.45, 0.50, 0.55, 0.63)   |   |
| High Sensitivity               | Yes  |   |
| Scene                          | Default, Clear, Bright, Soft   |   |
| Focus Zone                     | Face Priority, All Area, Upper Area, Central Area, Lower Area  |   |
| AI Face Detection Focus        | Yes  |   |
| AI Face Auto Exposure          | Yes  |   |
| Noise Reduction                | 2D/3D, 0-100   |   |
| S/N Ratio                      | ≥50db  |   |
| OSD                            | Editable   |   |
| HDMI Signal System             |  |   |
| Video Format - HDMI            | 1920x1080p:60/59.94/50/30/29.97/25; 1280x720p:60/59.94/50/30/25  |   |
| Color Format                   | 8bit(RGB), 12bit(YUV422),  |   |
| Color Space                    | YUV, RGB   |   |
| OSD Menu Display               | YES  |   |
| SDI Signal System              |  |   |
| SDI Video Format               | -  | 1080p:60/59.94/50/30/29.97/25; 720p:60/59.94/50/30/25                             |
| Color Precision                | -  | 8bit(SDI), YCbCr, 4:2:2   |
| Color Space                    | -  | YUV   |
| Standard                       | -  | 3G-SDI, SMPTE424M/SMPTE292M,TE 425-A(3Gb/s), with SMPTE352 SDI Metadata Supported |
| True Dual Output               | -  | SDI and HDMI has same video format when HDMI outputs FHD and lower.               |
| OSD Menu Display               | -  | YES   |
| USB Signal System              |  |   |
| USB Port                       | USB2.0,Type C  |   |
| Encoder                        | H.264/MJPEG/YUV2   |   |
| USB Video Format               | 1920×1080p60/50/30/25fps ,1280X720p60/50/30/25fps  |   |
| Compatible Integration         | UVC, UAC   |   |
| Video Conference Compatibility | Most video conference platform in the market   |   |
| Network-IP Streaming           |  |   |
| Video Codec                    | NDI HX3, MJPEG, AVC/HEVC-H.264/265 by SoC  |   |
| Network Interface              | RJ45 port-Standard 1Gbps Ethernet  |   |
| IP Video - 1st Stream          | 1920×1080p60/59.94/50/30/29.97/25fps ,1280X720p60/59.94/50/30/25fps  |   |
| IP Video - 2nd Stream          | 704x576, 640x480, 640x360, 576x480, 352x228; Frame Rate P30/25   |   |
| True Dual Output               | Video resolution and framerate: IP and HDMI can be output with different format (SDI and HDMI will be the same, SDI is the same or lower than HDMI, USB is the same as IP) |   |
| IP Protocols                   | TCP/IP, ICMP, ARP, RTP, UDP, HTTP, DNS, DHCP, FTP, NTP, NDI  |   |
| Application Protocols          | RTP, RTSP, RTMP,RTMPS, SRT, NDI  |   |
| Multi-stream                   | 2 Streams (Up to 8 viewers at the same time)   |   |
| Audio Compression              | AAC-LC, Broadband Audio Encoding   |   |

# Product Specification

| Model No.                 | N2-210X  | N2-220X                                      |
|---------------------------|--|--|
| Camera                    | 10X Full HD  | 20X Full HD                                  |
| Network-IP Streaming      |  |  |
| Compatible Integration    | ONVIF2.4 (Profile S), VISCA Over IP, NDI   |  |
| OSD                       | Customized OSD   |  |
| Browser Support           | Cross Browser Compatibility - HTML5 support for Microsoft Edge, Google Chrome, Firefox, and Safari   |  |
| Latency - Codec           | NDI Certified, <100ms  |  |
| Bandwidth                 | 1Mbps - 100Mbps  |  |
|                           | Results may vary depending on network configuration and management settings.   |  |
| NDI Bridge                | Yes, with NDI 6 supported  |  |
| Interface                 |  |  |
| HDMI Video Output         | HDMI 1.4X1 Type A  |  |
| IP Video Stream           | Up to 1080p60  |  |
| SDI Video Output          | -  | 3G-SDI, standard / 75 Ω (BNC x 1)            |
| Camera Control Interface  | RJ45X1-RS422, RJ45X1-IP Control, IR Remote Control   |  |
| Control Protocol          | VISCA, VISCA Over IP, Pelco P/D, Onvif, NDI  |  |
| LAN Port                  | RJ45X1 (1000BASE-T Ethernet port)  |  |
| USB Port                  | USB2.0,Type C  |  |
| USB Protocol              | UVC, UAC   |  |
| Synchronization           | Internal synchronization   |  |
| Tally Light               | Tally lamp in front, Red and Green Color   |  |
| Dip Switch                | Camera bottom panel: 8 PIN x 2   |  |
| Firmware Upgrade          | Upgrade via IP for camera system MCU and Encoder   |  |
| IR ID                     | ID selector for IR controller, total 3   |  |
| Power Connector Type      | DC12V (IEC60130-10 (JEITA standard RC-5320A) TYPE4 )   |  |
|                           | INPUT: RJ45, PoE(IEEE802.3af)  |  |
| Audio Input               | MIC/LINE input, 3.5mm audio jack   | USB port to 3.5mm audio jack                 |
|                           | AAC (Bit Rate(bps)48K*/64k / 96K / 128k; Sampling Rate(bps)44.1k / 48k   |  |
| Audio Output              | -  | USB port to 3.5mm audio jack-(Not Activated) |
| Audio Output              | Embedded with HDMI, SDI, IP, USB streaming, 24bit Stereo, sample rate: 44.1KHz, 48KHz, PCM24   |  |
| Audio S/N Ratio           | ≥85dB  |  |
| Audio THD+N               | ≤0.05%   |  |
| Audio Noise (RMS)         | ≤-90dB   |  |
| Mechanical                |  |  |
| Pan Movement              | Horizontal:±170 degrees continuous pan (Zoom Adaptive Speed Range: 0.05°～100°/S )  |  |
| Tilt Movement             | Vertical:+90 degrees to -30 degrees (Zoom Adaptive Speed Range: 0.05°～70°/S)   |  |
| Speed Proportional        | Pan/Tilt Speed proportional to zoom range  |  |
| Preset Position           | 255 positions, Speed 100°/s, Accuracy: 0.05° 9 presets on remote controller  |  |
| Preset Speed              | 0~5 Level Adjustable   |  |
| Preset Memory             | YES, ( Picture Profile Preset-Preset Memory for image parameters, like: Backlight Compensation, White Balance, R-Gain/B-Gain, Auto Exposure, Bright, Iris, Shutter, Gain, Aperture, Effect, Noise Reduction, Mirror, Gamma, Ex-COMP, Color Hue, Contrast etc.) |  |
| Motionless Preset         | On/Off   |  |
| PTZ Trace Memory          | Yes, 4 (Supported via IP interface)  |  |
| Cruise                    | Yes, 12  |  |
| Adaptive PT               | Zoom range adaptive Pan/Tilt speed   |  |
| Pan/Tilt Direction        | Normal, Invert   |  |
| Quietness                 | NC35 or less   |  |
| Home Position             | Support  |  |
| Environmental             | Indoor   |  |
| General                   |  |  |
| Body                      | Partial Magnesium Alloy  |  |
| Mount                     | Ceiling mount, Wall mount, Tripod  |  |
| Size of Tripod Screw Hole | 1/4"-20UNC with safety joint   |  |
| Operating Temperature     | 55.8° (W)~3.2° (T)   |  |
| Operating Humidity        | ≤80% Suitable for Use  |  |
| Power Input               | DC±12V, PoE (IEEE802.3 af Type 1 Calss 3)  |  |
| Power Consumption         | Min:10W(Static state with no movement); Max:13W(Fully loaded operation)  |  |
| Dimension                 | 143x143x161mm (LxWxH)  |  |
| Weight                    | 1.5kg (Net weight)   |  |
| Body Color                | Available in Black, (White - Special Order)  |  |
| Accessory                 |  |  |
| Power Supply              | 12VDC 2A X1, Universal various power core.   |  |
| Remote Controller         | Full Function IR Controller X1   |  |
| Serial Control Adaptor    | RS232/RS422 adapter cable x1 For serial RS232/422 control  |  |

## ORDER INFORMATION

- Visit Bolin Technology Website