

NANO PRO 98WH

NANO PRO

Mount Type	V-Mount
Voltage	14.4 V
Capacity	6.8Ah / 98Wh
Load	13A / 156W (Max)
D-Tap In- & Output	2* 10-16.8V / 13A
USB-A Output	5V/3A 9V/2A 12V/1.5A Supports fast charging protocols including QC2.0, QC3.0, FCP, and BC1.2.
USB-C1 Input/Output	5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W(Max)
USB-C2&C3 Output	5V/3A 9V/2A 12V/1.5A 18W(Max)
Operating Temperature	-20°C to +55°C
Charging Temperature	0°C to +40°C
Storage Temperature	-20°C to +45°C
Dimensions	108.7(L)mm×74(W)mm×54.4(H)mm
Weight	612g

NANO PRO 150WH

NANO PRO 150

Mount Type	V-Mount
Voltage	14.4 V
Capacity	10.2Ah / 147WH
Load	15A (MAX) / 180W (MAX)
D-Tap In- & Output	2* 10–16.8V / 15A (Max)
USB-A Output	5V/3A 9V/2A 12V/1.5A Supports fast charging protocols including QC2.0, QC3.0, FCP, and BC1.2.
USB-C1 Input/Output	5V/3A 9V/3A 12V/3A 15V/3A 20V/5A 100W(Max)
USB-C2&C3 Output	5V/3A 9V/2A 12V/1.5A 18W(Max)
Operating Temperature	-20°C to +55°C
Charging Temperature	0°C to +40°C
Storage Temperature	-20°C to +45°C
Dimensions	108.7(L)mm×74(W)mm×72.7(H)mm
Weight	838g