



### Nexus BP-190SL – Smart V-Mount Battery with LCD & USB-C

#### BP-190SL

Voltage	14.4 V
Capacity	12.8Ah / 184Wh
Load	15A (MAX) / 180W (MAX)
Mount Type	V-Mount
D-Tap In- & Output	2* 10-16.8V / 15A (Max)
USB-C In- & Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (PD 100W Max) (USB-C cable with built-in E-Mark chip supports 100W input/output)
USB-A Output	5V/2A, 9V/2A, 12V/1.5A
Operating Temperature	-20°C to +55°C
Charging Temperature	0°C to +40°C
Storage Temperature	-20°C to +45°C
Dimensions	154(L) × 100(W) × 66(H) mm
Weight	1154g

### Nexus BP-250SL – Smart V-Mount Battery with LCD & USB-C

#### BP-250SL

Voltage	14.4 V
Capacity	17.4Ah/251Wh
Load	18A(Max)/250W(Max)
Mount Type	V-Mount
D-Tap In- & Output	2*10-16.8V/18A(Max)
USB-C In- & Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (PD 100W Max) (USB-C cable with built-in E-Mark chip supports 100W input/output)
USB-A Output	5V/2A, 9V/2A, 12V/1.5A
Operating Temperature	-20°C to +55°C
Charging Temperature	0°C to +40°C
Storage Temperature	-20°C to +45°C
Dimensions	154(L) × 100(W) × 85(H)mm
Weight	1580g

### Nexus BP-300SL – Smart V-Mount Battery with LCD & USB-C

#### BP-300SL

Voltage	14.4 V
Capacity	20.4Ah / 294Wh
Load	18A(Max)/250W(Max)
Mount Type	V-Mount
D-Tap In- & Output	2*10-16.8V/18A(Max)
USB-C In- & Output	5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/5A (PD 100W Max) (USB-C cable with built-in E-Mark chip supports 100W input/output)
USB-A Output	5V/2A, 9V/2A, 12V/1.5A
Operating Temperature	-20°C to +55°C
Charging Temperature	0°C to +40°C
Storage Temperature	-20°C to +45°C
Dimensions	154(L) × 100(W) × 85(H)mm
Weight	1638g