

SPECIFICATIONS

CCT	2,500K~7,500K	G/M Adjustable	±1.00G
CRI	≥95	TLCI	≥96
CQS	≥96	TM-30 RF (Average)	94
TM-30 RG (Average)	103	SSI (P3200)	≥83
SSI (D56)	≥74	Beam Angle (No Accessory)	45°
Max Power Output	60W	Max Power Consumption	≤78W
Operating Current	4.5A	Voltage (AC Power Supply)	15V DC
Voltage (D-Tap Battery)	12-16.8V DC	Voltage (NP-F Battery)	6.5V-8.4V DC
Battery Charging (Type)	Sony NP-F Style	DC Input	2-Pin DC Self-locking Waterproof
AC Power Cable	Self-locking IEC C13 AC Power Cable (1.5m)	Operating Temperature	-20°C ~ 45°C / -4°F ~ 113°F
Control Methods	On-board, Sidus Link App	Connectivity	Bluetooth 5.0 (Sidus Mesh)
Bluetooth Operating Range	≥80m / 262.5ft	Firmware Upgradeable	Sidus Link OTA
		Cooling Method	Active Cooling
Display Type	OLED	Estimated LED Lifetime (L70)	50,000 Hours
Mounting	1/4-20in * 3, Tilting Support Column	Certifications	CE, FCC, cTUVus, KC, NCC, ROHS
Estimated Color Shift Over Lifetime (CCT)	2% over 6,000 Hours		
Max Light Output	6,300 lux @ 1m		

★ DIMENSIONS

Fixture	27.1*21.3*4.34cm / 10.67*8.39*1.7in	Aperture	26.90 * 21.00cm / 10.5*8.2in
Soft Box (Collapsed)	20*20*2.5cm / 7.8*7.8*.98in	Soft Box (Built)	41*34*10cm / 16.1*13.3*3.9in
Carrying Case	27.4*21.8*9.5cm / 10.79*8.58*3.74in		

★ WEIGHT

Fixture	1.880kg / 4.145lbs		
Soft Box	0.17kg / .37lbs		
Power Supply	0.50kg / 1.1lbs		
Mounting Bracket	0.24kg / .53lbs		