

## SPECIFICATIONS

CCT	2,300K - 10,000K	CRI	96
TLCI	97	SSI (P3200)	84
SSI (D56)	74	TM-30 RG (Average)	101
TM-30 RF (Average)	93	Max Power Output	120W
Max Power Consumption	140W	Color Chipset	RGBWW
Lumens	13,855 lumens	Power Supply Method	DC, USB-C PD
Beam Angle (No Accessory)	45°	Beam Angle (Control Grid)	45°
Operating Voltage (Fixture)	DC 24V, PD 28V	Operating Voltage (AC Power Supply)	AC 110V ~ 220V
Operating Temperature	-10°C - 40°C / 14°F - 104°F	Storage Temperature	-20°C - 80°C / -4°F - 176°F
Control Methods	On-board, amaran App, Sidus Link	Firmware Upgradeable	amaran App, Sidus Link
Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)	Cooling Method	Fan Cooling
Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)	Cooling Method	Fan Cooling
Fixture Dimensions	14.0 x 10.0 x 1.4in	Fixture Weight	1.6kg / 3.5lbs
Max Light Output	13,490 lux @ 1m		

## ★ DIMENSIONS

Fixture	35.5 x 25.6 x 3.6cm / 14.0 x 10.0 x 1.4in	Softbox	41.5 x 30.5 x 10.3cm / 16.3 x 12.0 x 4.0in
Light Control Grid	42.0 x 31.4 x 7.0cm / 16.5 x 12.2 x 2.8in	Ace Lock to Light Stand Adapter	9.0 x 7.5 x 2.5cm / 3.5 x 3.0 x 1.0in
AC Power Cable	2m / 6.56ft	Power Adapter Cable	2.5m / 8.20ft
Carrying Case	44.0 x 28.0 x 10.0cm / 17.3 x 11.0 x 3.9in		

## ★ WEIGHT

Fixture	1.6kg / 3.5lbs
Softbox	350g / 0.8lbs
Light Control Grid	150g / 0.3lbs
Ace Lock to Light Stand Adapter	180g / 0.4lbs
Carrying Case	400g / 0.9lbs

## 📦 WHAT'S IN THE BOX

1x amaran Pano 120c
1x amaran Pano 120c Softbox
1x amaran Pano 120c Light Control Grid
1x amaran Pano 120c Diffuser
1x amaran Ace Lock to Light Stand Adapter
1x amaran 150W DC Locking Power Adapter
1x amaran AC Power Cable
1x amaran Pano 120c Kit Carrying Case