

SPECIFICATIONS

CCT	2,300K - 10,000K	CRI	96
TLCI	97	SSI (P3200)	84
SSI (D56)	74	TM-30 RG (Average)	101
TM-30 RF (Average)	93	Max Power Output	60W
Max Power Consumption	65W	Color Chipset	RGBWW
Lumens	6,790 lumens	Power Supply Method	USB-C PD
Beam Angle (No Accessory)	45°	Beam Angle (Control Grid)	45°
Operating Voltage (Fixture)	DC 20V	Operating Voltage (AC Power Supply)	AC 110V ~ 220V
Operating Temperature	-10°C - 40°C / 14°F - 104°F	Storage Temperature	-20°C - 80°C / -4°F - 176°F
Control Methods	On-board, amaran App, Sidus Link	Firmware Upgradeable	amaran App, Sidus Link
Wireless Operating Range	≤80m / ≤262.5ft (Bluetooth)	Cooling Method	Fan Cooling
Fixture Dimensions	10.0 x 6.1 x 1.2in	Fixture Weight	610g / 1.3lbs
Max Light Output	22,220 lux @ 0.5m		

★ DIMENSIONS

Fixture	25.5 x 15.5 x 3.0cm / 10.0 x 6.1 x 1.2in	Softbox	31.5 x 20.5 x 10.5cm / 12.4 x 8.0 x 4.1in
Light Control Grid	32.0 x 20.0 x 17.0cm / 12.6 x 7.9 x 6.7in	Ace Lock to Light Stand Adapter	9.0 x 7.0 x 2.5cm / 3.5 x 3.5 x 1.0in
AC Power Cable	2m / 6.56ft	Power Adapter Cable	2.5m / 8.20ft
Pano 60c Kit Carrying Case	33.5 x 17.5 x 9.0cm / 13.19 x 6.89 x 3.54in	Light Stand (Folded)	43cm / 1.41ft
Light Stand (Extended)	2m / 6.56ft	Pano 60c 2-Light Kit Carrying Case	49.0 x 30.0 x 20.0cm / 19.29 x 11.81 x 7.87in

★ WEIGHT

Fixture	610g / 1.3lbs
Softbox	260g / 0.6lbs
Light Control Grid	80g / 0.2lbs
Ace Lock to Light Stand Adapter	180g / 0.4lbs
Pano 60c Kit Carrying Case	250g / 0.55lbs
Pano 60c 2-Light Kit Carrying Case	2.2kg / 4.85lbs

📦 WHAT'S IN THE BOX

1x amaran Pano 60c
1x amaran Pano 60c Softbox
1x amaran Pano 60c Light Control Grid
1x amaran Pano 60c Diffuser
1x amaran Ace Lock to Light Stand Adapter
1x amaran AC Power Cable
1x amaran Pano 60c Kit Carrying Case