

PRO173-T

BROADCASTING MONITOR

Introducing the PRO173-T Broadcasting Monitor – Precision Meets Performance!

Elevate your visuals with the **PRO173-T Broadcasting Monitor**, designed to deliver exceptional performance in any setting. Featuring **tempered glass**, it's

built to withstand the demands of **outdoor production** and resist impacts, ensuring unmatched durability and reliability for professionals who demand the best.

Key Features

- **Flexible Video Input/Output Options** – It has the inputs and outputs necessary for video production.
- **Peaking Focus Assist & Check Field** – Achieve precise focus with our Peaking Assist and mono/primary color options for uncompromised color accuracy.
- **Pixel-to-Pixel Display Mode** – See your content as it was meant to be seen, with pixel-perfect detail.
- **Customizable Functionality** – Four user-defined buttons allow instant access to your most-used functions, giving you control that fits your workflow.
- **Image Adjustments** – From Screen Markers and Image Flip options to Aspect Ratio control and zoom features, every setting is yours to fine-tune.
- **Built-In Audio Output** – Enjoy the convenience of a front-panel headphone jack and a built-in speaker for audio monitoring.


Designed for both **carry-on and desktop use**, the PRO173-T Broadcasting Monitor adapts to your on-set and studio environments. The **optional hardcase** provides an ideal solution especially for outdoor production use. Equipped with a **battery plate system**, it offers flexible power solutions, supporting **V-Mount battery plate**.

Get ready to redefine your visual standards with the PRO173-T Broadcasting Monitor. It's more than a monitor – it's your essential tool for **outstanding visual performance** and **exceptional control**.



 www.fortinge.com

 fb.com/fortingevideo

 Zümrütevler Mh. Ertuğrul Sk. No:10
Akratek Plaza
Maltepe – Istanbul / Turkey

 +90 (216) 418 11 03

 info@fortinge.com

Head
Office

 Záhony u. 7. Graphisoft Park D épület 1. emelet 1031 Budapest, Hungary

 sales@fortinge.com

Fortinge
Europe

PRO173-T

BROADCASTING MONITOR

SPECIFICATIONS

| General | |
|---------------------|---------------------------|
| Screen Size | 17.3" |
| Resolution | 1024×768 |
| Viewing Angle | 80°/80°(L/R) 60°/80°(U/D) |
| Aspect Ratio | 16:9 |
| Brightness | 400 cd/m ² |
| Contrast Ratio | 600:1 |
| Backlight | LED |
| Input Voltage | DC 9 24V |
| Power Consumption | ≤ 26W |
| Working Temperature | -10°C~50°C |
| Storage Temperature | -20°C~60°C |
| Unit Size | 426L×297H×35.1D mm |
| Unit Weight | 2750 g |

| Input | |
|-----------|---------------------------|
| 1 X BNC | 3G SDI |
| 1 X HDMI | HDMI |
| 3 X BNC | YPbPr |
| 1 X DV-I | DVI-I |
| 1 X BNC | Video |
| 2 X RCA | Audio (L/R) |
| Output | |
| 1 X BNC | 3G SDI |
| 1 X HDMI | HDMI |
| 3 X BNC | YPbPr |
| 1 X BNC | Video |
| Audio | |
| Audio Out | Stereo Headphone, Speaker |

| Advanced Features |
|--|
| <ul style="list-style-type: none"> • Peaking Focus Assist (Red highlight over parts of the monochrome image in focus) • Center Marker • Screen Marker (80%, 85%, 90%, 93%, 96%, 2.35:1) • Image Freeze • Image Flip (H, V, H/V) • Camera Mode • Pixel-to-Pixel • Check Field (Red, Green, Blue, Mono) • Built-in LED tally indicators |

| SDI Support Format |
|--|
| 480i/576i |
| 720p(60/59.94/50/30/29/25/24/23.98) |
| 1080p(60/59.94/50/30/29.97/25/24/23.98) |
| 1080i(60/59.94/50) |
| HDMI Support Format |
| 480i/576i/480p/576p |
| 720p(60/59.94/50/30/29/25/24/23.98) |
| 1080i(60/59.94/50) |
| 1080p(60/59.94/50/30/29.97/25/24/23.98) |
| 4K UHD 3840x2160p (30/29.97/25/24/23.98Hz) |
| 4096x2160p (24Hz) |



www.fortinge.com

fb.com/fortingevideo

Zümrütevler Mh. Ertuğrul Sk. No:10

Akratek Plaza

Maltepe – Istanbul / Turkey

+90 (216) 418 11 03

info@fortinge.com

Záhony u. 7. Graphisoft Park D épület 1. emelet 1031 Budapest, Hungary

sales@fortinge.com

FORTINGE